Feed-through terminal block - RTO 8-TC - 3050002

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(http://download.phoenixcontact.com)

Feed-through terminal block with bolt connection technology and transparent safety contact hood, cross section: 2.5 – 35 mm², AWG: 14 - 2, width 20.2 mm, color: gray

Why buy this product

- Four bridge shafts per terminal block
- Terminal point always freely accessible

Key commercial data

Packing unit	25 pc
Minimum order quantity	10 pc
GTIN	4 046356 431415
Weight per Piece (excluding packing)	85.56 g
Custom tariff number	85369010
Country of origin	China

Technical data

General

Note	Note: the BE-RT... path extension is to be used for non-insulated cable lugs (see accessories).
Number of levels	1
Number of connections	2
Color	gray
Insulating material	PA
Inflammability class according to UL 94	V0
Maximum load current	125 A (with 35 mm² conductor cross section)
Rated surge voltage	8 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Nominal current I_N	125 A

Feed-through terminal block - RTO 8-TC - 3050002

Technical data

General

Nominal voltage U_N	1000 V
Open side panel	ja
Number of positions	1

Dimensions

Width	20.2 mm
Length	84 mm
Height	63.20 mm
Height NS 35/7,5	63.8 mm
Height NS 35/15	71.3 mm

Connection data

Note	Connection bolts
Connection method	Bolt connection
Conductor cross section solid min.	2.5 mm²
Conductor cross section solid max.	35 mm²
Conductor cross section AWG/kcmil min.	14
Conductor cross section AWG/kcmil max	2
Conductor cross section stranded min.	2.5 mm²
Conductor cross section stranded max.	35 mm²
Min. AWG conductor cross section, stranded	14
Max. AWG conductor cross section, stranded	2
Min. cross section for cable lug connection	2.5 mm²
Max. cross section for cable lug connection	35 mm²
Screw thread	M8
Tightening torque, min	6 Nm
Tightening torque max	10 Nm

Classifications

eCl@ss

eCl@ss 4.0	27141120
eCl@ss 4.1	27141120
eCl@ss 5.0	27141120
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27141120

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897

Feed-through terminal block - RTO 8-TC - 3050002

Classifications

ETIM

ETIM 4.0	EC000897
ETIM 5.0	EC000897

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Approvals

Approvals

Approvals

ABS

Ex Approvals

Approvals submitted

Approval details

ABS

Accessories

Accessories

Bridge

Plug-in bridge - FBS 2-10 - 3005947

Plug-in bridge, Number of positions: 2, Color: red

End block

Feed-through terminal block - RTO 8-TC - 3050002

Accessories

End clamp - CLIPFIX 35 - 3022218

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

---

End clamp - CLIPFIX 35-5 - 3022276

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

---

End clamp - E/NS 35 N - 0800886

End clamp, width: 9.5 mm, color: gray

End clamp - E/UK - 1201442

End clamp, for assembly on NS 32 or NS 35/7.5 DIN rail

End clamp - E/UK 1 - 1201413

End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

---

End cover

Feed-through terminal block - RTO 8-TC - 3050002

Accessories

End cover - D-RT 8 - 3049194

Cover, width: 2.2 mm, color: gray

Path extension - BE-RT 8 - 3049916

Path extension

Labeled terminal marker

Zack marker strip - ZB 16,3 CUS - 0824946

Zack marker strip, Can be ordered: Strip, white, Labeled according to customer specifications, Mounting type: Snap into tall marker groove, For terminal block width: 16.3 mm, Lettering field: 10.5 x 16.25 mm

---

Zack marker strip - ZB 20,3 CUS - 0824948

Zack marker strip, Can be ordered: Strip, white, Labeled according to customer specifications, Mounting type: Snap into tall marker groove, For terminal block width: 20.3 mm, Lettering field: 10.5 x 20.25 mm

---

Mounting rail

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733

DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

---

Feed-through terminal block - RTO 8-TC - 3050002

Accessories

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681

DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119

DIN rail 35 mm (NS 35)

DIN rail - NS 35/ 7,5 WH UNPERF 2000MM - 1204122

DIN rail 35 mm (NS 35)

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704

DIN rail, unperforated, Width: 35 mm, Height: 7.5 mm, Length: 2000 mm, Color: silver

---

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421

DIN rail, material: Galvanized, perforated, height 7.5 mm, width 35 mm, length: 2 m

---

Feed-through terminal block - RTO 8-TC - 3050002

Accessories

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434

DIN rail, material: Galvanized, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM - 0801762

DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

End cap - NS 35/ 7,5 CAP - 1206560

DIN rail end piece, for DIN rail NS 35/7.5

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm

---

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714

DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m

---

Feed-through terminal block - RTO 8-TC - 3050002

Accessories

DIN rail perforated - NS 35/15 WH PERF 2000MM - 0806602

DIN rail 35 mm (NS 35)

DIN rail - NS 35/15 WH UNPERF 2000MM - 1204135

DIN rail 35 mm (NS 35)

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000 mm

---

DIN rail perforated - NS 35/15 ZN PERF 2000MM - 1206599

DIN rail, material: Galvanized, perforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/15 ZN UNPERF 2000MM - 1206586

DIN rail, material: Galvanized, unperforated, height 15 mm, width 35 mm, length: 2 m

---

Feed-through terminal block - RTO 8-TC - 3050002

Accessories

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM - 1201895

DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m

---

End cap - NS 35/15 CAP - 1206573

DIN rail end piece, for DIN rail NS 35/15

DIN rail, unperforated - NS 35/15-2,3 UNPERF 2000MM - 1201798

DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

---

Partition plate

Partition plate - TPN-UK - 3003062

Partition plate, Length: 110 mm, Width: 2 mm, Height: 69 mm, Color: gray

---

Socket spanner

Tool - SHN 13 - 1209923

Socket wrench, wrench size 13 mm

Terminal marking

Feed-through terminal block - RTO 8-TC - 3050002

Accessories

Zack marker strip - ZB 16,3:UNPRINTED - 0820222

Zack marker strip, Strip, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Snap into tall marker groove, For terminal block width: 16.3 mm, Lettering field: 10.5 x 16.25 mm

---

Zack marker strip - ZB 20,3:UNPRINTED - 0820248

Zack marker strip, Strip, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Snap into tall marker groove, For terminal block width: 20.3 mm, Lettering field: 10.5 x 20.25 mm

---

Drawings

Circuit diagram

Phoenix Contact 2014 © - all rights reserved
http://www.phoenixcontact.com