



- MATERIALI:**
- BLOCCHETTO: PA 46 (STANYL) 30% F.V. NERO V-0
  - TERMINALE: LEGA STOL 76 DURO
- FINITURA:**
- VERSIONE DA NASTRO PRESTAGNATO Spess.4 u min
- IMBALLO:**
- SFUSI IN SCATOLE - 1200 pz./scatola, 8 scatole/cartone
- MATERIALS:**
- HOUSING: PA 46 30% G.F.V-0 BLACK
  - TERMINALS: ALLOY C19010 (STOL 76)
- PLATINGS:**
- TIN PREPLATED STRIP: 4 u MIN.
- PAKAGING:**
- LOOSE PCS IN CARDBOARD BOXES (1200 pcs/box; 8 boxes/carton)

SPQ: 9600 pz.

FORATURA CONSIGLIATA SU PCB (Spess.1.5 mm)  
RECOMMENDED PCB LAYOUT. PCB THICKNESS= 1.5 mm

STD. DESCR: "SERIAL CONNECTOR OVERMOLDED 5 CKT"

EC NO. Z2002-0064 DRWN: F. Gottardo 15-11-01 CHK: M. Testaguzza 15-11-01 APPR: G. Zuin 15-11-01	QUALITY SYMBOLS MAJOR M = SIGNIF. S = CRITICAL C =	GENERAL TOLERANCES: (UNLESS SPECIFIED)	SCALE 5 : 1	DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	FIRST ANGLE PROJECTION <input type="checkbox"/> mm <input type="checkbox"/> INCH <input checked="" type="checkbox"/> mm ONLY	DIMENSIONS: <input type="checkbox"/> mm <input type="checkbox"/> INCH <input checked="" type="checkbox"/> mm ONLY	SHT REV
	DESCRIPTION MAJOR M = SIGNIF. S = CRITICAL C =	mm    INCH 4 PLACES ±0.    ±. 3 PLACES ±0.    ±. 2 PLACES ±0.05    ±. 1 PLACE ±0.10    ±. ANGULAR: ± 2°	DRAWN BY & DATE F. Gottardo 23-07-99 CHECKED BY & DATE M. Testaguzza 23-07-99 APPROVED BY & DATE R. Martucci 23-07-99	TITLE: CONNETTORE SERIALE A 5 VIE SERIAL CONNECTOR 5 CKT	CAD FILENAME 94234009.DGN	MATERIAL NO. 94234-1005	DRAWING NO. SD-94234-009
REV B2	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.				SIZE A3	