

tesa® 4952

Double-sided PE-foam mounting tape

PRODUCT INFORMATION

Product Description

tesa® 4952 is a double-sided PE-foam tape for constructive mounting applications. It consists of a highly conformable PE-foam backing and a tackified acrylic adhesive. tesa® 4952 has been externally certified for furniture mirror mounting.

Product benefits:

- Versatile adhesive for high immediate adhesion on numerous substrates
- Fully outdoor suitable: UV, water and ageing resistant
- Compensates for differing thermal expansion of dissimilar materials
- High immediate bonding strength even at low bonding pressure
- Very good cold shock absorption

Main Application

- Furniture mirror mounting
- Mounting of car mirrors
- Mounting functional trims & profiles
- Mounting of decorative panels

Technical Data

■ Backing material	PE foam	■ Tensile strength	10 N/cm
■ Colour	white	■ Type of liner	glassine
■ Total thickness	1150 µm	■ Thickness of liner	70 µm
■ Type of adhesive	tackified acrylic	■ Colour of liner	brown
■ Elongation at break	200 %	■ Weight of liner	80 g/m ²

Adhesion to

■ Steel (initial)	6.5 N/cm	■ Steel (after 14 days)	8.0 N/cm
■ ABS (initial)	5.0 N/cm	■ ABS (after 14 days)	8.0 N/cm
■ Aluminium (initial)	5.0 N/cm	■ Aluminium (after 14 days)	8.0 N/cm
■ PC (initial)	5.0 N/cm	■ PC (after 14 days)	8.0 N/cm
■ PE (initial)	2.7 N/cm	■ PE (after 14 days)	2.8 N/cm
■ PET (initial)	5.0 N/cm	■ PET (after 14 days)	7.0 N/cm
■ PP (initial)	2.8 N/cm	■ PP (after 14 days)	5.5 N/cm
■ PS (initial)	5.0 N/cm	■ PS (after 14 days)	7.5 N/cm
■ PVC (initial)	5.0 N/cm	■ PVC (after 14 days)	8.0 N/cm

For latest information on this product please visit <http://l.tesa.com/?ip=04952>

Page 1 of 2 / As of 04/30/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.

Properties

■ Temperature resistance short term	80 °C	■ Resistance to chemicals	+
■ Temperature resistance long term	80 °C	■ Softener resistance	o
■ Tack	+	■ Static shear resistance at 23°C	+
■ Ageing resistance (UV)	+	■ Static shear resistance at 40°C	+
■ Humidity resistance	++		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

tesa® 4952 has been tested and approved by LGA institute for mirror mounting. Report number IWQ FSG 329 1189.

Peel Adhesion:

- immediately: foam splitting on Steel, Aluminium, ABS, PC, PS, PET, PVC
- after 14 days: foam splitting on Steel, Aluminium, ABS, PC, PS, PET, PVC

For latest information on this product please visit <http://l.tesa.com/?ip=04952>

Page 2 of 2 / As of 04/30/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.