# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(http://phoenixcontact.com/download)

Installation ground terminal block, Screw connection, Cross section: 0.2 mm² - 4 mm², AWG: 24 - 12, Width: 5.2 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

## Why buy this product

- The installation terminal block features a particularly low-profile design and is suitable for wiring in flat installation distributors

## Key commercial data

| | |
|---|---|
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| GTIN | 4 046356 643993 |
| Weight per Piece (excluding packing) | 19.5 g |
| Custom tariff number | 85369010 |
| Country of origin | Germany |

## Technical data

### General

| | |
|---|---|
| Note | Assembly instructions:<br>For secure fastening of the neutral busbar, supports must be set at the beginning and end of each terminal strip as well as every 20 cm on longer terminal strips. |
| Number of levels | 3 |
| Number of connections | 5 |
| Color | gray |
| Insulating material | PA |
| Inflammability class according to UL 94 | V0 |
| Maximum load current | 30 A (with 4 mm² conductor cross section and 3-pos. terminal block) |
| | 24 A (with 2.5 mm² conductor cross section) |
| Rated surge voltage | 4 kV |
| | 6 kV |
| Pollution degree | 3 |

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Technical data

### General

| | |
|---|---|
| Surge voltage category | III |
| Insulating material group | I |
| Maximum load current | 30 A (with 4 mm² conductor cross section and 3-pos. terminal block) |
| Nominal current $I_N$ | 24 A (with 4 mm² conductor cross section) |
| Nominal voltage $U_N$ | 400 V (phase conductor/phase conductor) |
| | 250 V (phase conductor/PE) |
| Maximum load current | 30 A (with 4 mm² conductor cross section and 3-pos. terminal block) |
| Open side panel | ja |
| Shock protection test specification | DIN EN 50274 (VDE 0660-514):2002-11 |
| Back of the hand protection | guaranteed |
| Finger protection | guaranteed |
| Surge voltage test setpoint | 7.3 kV |
| Result of surge voltage test | Test passed |
| Power frequency withstand voltage setpoint | 1.89 kV |
| Result of power-frequency withstand voltage test | Test passed |
| Checking the mechanical stability of terminal points (5 x conductor connection) | Test passed |
| Bending test rotation speed | 10 rpm |
| Bending test turns | 135 |
| Bending test conductor cross section/weight | 0.2 mm² / 0.2 kg |
| | 2.5 mm² / 0.7 kg |
| | 4 mm² / 0.9 kg |
| Result of bending test | Test passed |
| Conductor cross section tensile test | 0.2 mm² |
| Tractive force setpoint | 10 N |
| Conductor cross section tensile test | 2.5 mm² |
| Tractive force setpoint | 50 N |
| Conductor cross section tensile test | 4 mm² |
| Tractive force setpoint | 60 N |
| Tensile test result | Test passed |
| Tight fit on carrier | NS 35 |
| Setpoint | 1 N |
| Result of tight fit test | Test passed |
| Requirements, voltage drop | ≤ 3.2 mV |
| Result of voltage drop test | Test passed |
| Temperature-rise test | Test passed |
| Conductor cross section short circuit testing | 2.5 mm² |
| Short-time current | 0.3 kA |
| Conductor cross section short circuit testing | 4 mm² |
| Short-time current | 0.48 kA |
| Short circuit stability result | Test passed |

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Technical data

### General

| | |
|---|---|
| Ageing test for screwless modular terminal block temperature cycles | 192 |
| Result of aging test | Test passed |
| Proof of thermal characteristics (needle flame) effective duration | 30 s |
| Result of thermal test | Test passed |
| Test specification, oscillation, broadband noise | DIN EN 50155 (VDE 0115-200):2008-03 |
| Test spectrum | Service life test category 2, bogie mounted |
| Test frequency | $f_1$ = 5 Hz to $f_2$ = 250 Hz |
| ASD level | 6.12 $(m/s^2)^2$/Hz |
| Acceleration | 3.12 g |
| Test duration per axis | 5 h |
| Test directions | X-, Y- and Z-axis |
| Oscillation, broadband noise test result | Test passed |
| Test specification, shock test | DIN EN 50155 (VDE 0115-200):2008-03 |
| Shock form | Half-sine |
| Acceleration | 30g |
| Shock duration | 18 ms |
| Number of shocks per direction | 3 |
| Test directions | X-, Y- and Z-axis (pos. and neg.) |
| Shock test result | Test passed |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C |
| Static insulating material application in cold | -60 °C |

### Dimensions

| | |
|---|---|
| Width | 5.2 mm |
| End cover width | 2.2 mm |
| Length | 93.5 mm |
| Height NS 35/7,5 | 51.5 mm |
| Height NS 35/15 | 59 mm |
| Height | 51.20 mm |

### Connection data

| | |
|---|---|
| Note | Please observe the current carrying capacity of the DIN rails. |
| Connection method | Screw connection |
| Conductor cross section solid min. | 0.2 mm² |
| Conductor cross section solid max. | 4 mm² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 12 |
| Conductor cross section stranded min. | 0.2 mm² |
| Conductor cross section stranded max. | 4 mm² |
| Min. AWG conductor cross section, stranded | 24 |
| Max. AWG conductor cross section, stranded | 12 |

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Technical data

### Connection data

| | |
|---|---|
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.25 mm² |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 2.5 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve min. | 0.25 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve max. | 2.5 mm² |
| 2 conductors with same cross section, solid min. | 0.2 mm² |
| 2 conductors with same cross section, solid max. | 1.5 mm² |
| 2 conductors with same cross section, stranded min. | 0.2 mm² |
| 2 conductors with same cross section, stranded max. | 1.5 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.75 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. | 0.25 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. | 0.75 mm² |
| Stripping length | 9 mm |
| Internal cylindrical gage | A3 |
| Screw thread | M3 |
| Tightening torque, min | 0.5 Nm |
| Tightening torque max | 0.6 Nm |

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 4.0 | 27141120 |
| eCl@ss 4.1 | 27141120 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141125 |

### ETIM

| | |
|---|---|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC001329 |
| ETIM 5.0 | EC001329 |

### UNSPSC

| | |
|---|---|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Classifications

### UNSPSC

| | |
|---|---|
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

## Approvals

### Approvals

Approvals

VDE Zeichengenehmigung / IECEE CB Scheme / EAC / UL Recognized

Ex Approvals

Approvals submitted

### Approval details

VDE Zeichengenehmigung

| | |
|---|---|
| Nominal current IN | 21 A |
| Nominal voltage UN | 400 V |

IECEE CB Scheme

EAC

UL Recognized

| | | B | C | D |
|---|---|---|---|---|
| mm²/AWG/kcmil | 26-12 | 26-12 | 26-12 | |
| Nominal current IN | 20 A | 10 A | | |
| Nominal voltage UN | 300 V | 300 V | | |

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

### Accessories

### End block

End clamp - CLIPFIX 35 - 3022218

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

---

End clamp - CLIPFIX 35-5 - 3022276

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

---

End clamp - E/NS 35 N - 0800886

End clamp, width: 9.5 mm, color: gray

---

### End cover

End cover - D-UTI/3 - 3076036

End cover, Length: 93.5 mm, Width: 2.2 mm, Height: 51.2 mm, Color: gray

---

Spacer plate - DP PS-5 - 3036725

Spacer plate, Color: red

---

### Installation terminal block

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

### Connection terminal block - AKG 16 BU - 0423014

Connection terminal block, Connection method Screw connection, Load current : 76 A, Cross section:  1.5 mm² - 16 mm², Width: 9.8 mm, Color: blue

---

### Connection terminal block - AKG 35 BU - 0424013

Connection terminal block, Connection method Screw connection, Load current : 125 A, Cross section:  2.5 mm² - 35 mm², Width: 14.3 mm, Color: blue

---

## Insulating sleeve

### Insulating sleeve - MPS-IH WH - 0201663

Insulating sleeve, Color: white

---

### Insulating sleeve - MPS-IH RD - 0201676

Insulating sleeve, Color: red

---

### Insulating sleeve - MPS-IH BU - 0201689

Insulating sleeve, Color: blue

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

Insulating sleeve - MPS-IH YE - 0201692

Insulating sleeve, Color: yellow

Insulating sleeve - MPS-IH GN - 0201702

Insulating sleeve, Color: green

Insulating sleeve - MPS-IH GY - 0201728

Insulating sleeve, Color: gray

Insulating sleeve - MPS-IH BK - 0201731

Insulating sleeve, Color: black

## Jumper

Plug-in bridge - FBS 2-5 - 3030161

Plug-in bridge, Length: 22.7 mm, Width: 9 mm, Number of positions: 2, Color: red

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

Plug-in bridge - FBS 3-5 - 3030174

Plug-in bridge, Length: 22.7 mm, Width: 14.2 mm, Number of positions: 3, Color: red

---

Plug-in bridge - FBS 4-5 - 3030187

Plug-in bridge, Length: 22.7 mm, Width: 19.4 mm, Number of positions: 4, Color: red

---

Plug-in bridge - FBS 5-5 - 3030190

Plug-in bridge, Length: 22.7 mm, Width: 24.6 mm, Number of positions: 5, Color: red

---

Plug-in bridge - FBS 10-5 - 3030213

Plug-in bridge, Length: 22.7 mm, Width: 50.6 mm, Number of positions: 10, Color: red

---

Plug-in bridge - FBS 20-5 - 3030226

Plug-in bridge, Number of positions: 20, Color: red

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

Plug-in bridge - FBS 50-5 - 3038930

Plug-in bridge, Number of positions: 50, Color: red

---

Plug-in bridge - FBSR 2-5 - 3033702

Plug-in bridge, Number of positions: 2, Color: red

---

Plug-in bridge - FBSR 3-5 - 3001591

Plug-in bridge, Number of positions: 3, Color: red

---

Plug-in bridge - FBSR 4-5 - 3001592

Plug-in bridge, Number of positions: 4, Color: red

---

Plug-in bridge - FBSR 5-5 - 3001593

Plug-in bridge, Number of positions: 5, Color: red

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

### Plug-in bridge - FBSR 10-5 - 3033710

Plug-in bridge, Number of positions: 10, Color: red

---

## Labeled terminal marker

### Zack marker strip - ZB 5 CUS - 0824962

Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.15 x 10.5 mm

---

### Zack marker strip - ZB 5,LGS:FORTL.ZAHLEN - 1050017

Zack marker strip, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.15 x 10.5 mm

---

### Zack marker strip - ZB 5,QR:FORTL.ZAHLEN - 1050020

Zack marker strip, Strip, white, labeled, can be labeled with: Plotter, Printed vertically: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.15 x 10.5 mm

---

### Zack marker strip - ZB 5,LGS:GLEICHE ZAHLEN - 1050033

Zack marker strip, Strip, white, labeled, can be labeled with: Plotter, Printed horizontally: Identical numbers 1 or 2, etc. up to 100, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.15 x 10.5 mm

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

### Marker for terminal blocks - ZB 5,LGS:L1-N,PE - 1050415

Marker for terminal blocks, Strip, white, labeled, Horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.15 x 10.5 mm

---

### Marker for terminal blocks - UC-TM 5 CUS - 0824581

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 10.5 x 4.6 mm

---

### Marker for terminal blocks - UCT-TM 5 CUS - 0829595

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, Lettering field: 4.6 x 10.5 mm

---

### Zack Marker strip, flat - ZBF 5 CUS - 0825025

Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.15 x 5.15 mm

---

### Zack Marker strip, flat - ZBF 5,LGS:FORTL.ZAHLEN - 0808671

Zack Marker strip, flat, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.15 x 5.15 mm

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

### Zack Marker strip, flat - ZBF 5,QR:FORTL.ZAHLEN - 0808697

Zack Marker strip, flat, Strip, white, labeled, Printed vertically: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 100, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.15 x 5.15 mm

---

### Zack Marker strip, flat - ZBF 5,LGS:GERADE ZAHLEN - 0810821

Zack Marker strip, flat, Strip, white, labeled, Printed horizontally: Consecutive numbers 2 - 20, 22 - 40, etc. up to 82 - 100, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.15 x 5.15 mm

---

### Zack Marker strip, flat - ZBF 5,LGS:UNGERADE ZAHLEN - 0810863

Zack Marker strip, flat, Strip, white, labeled, Printed horizontally: Odd numbers 1 - 19, 21 - 39, etc. up to 81 - 99, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.15 x 5.15 mm

---

### Marker for terminal blocks - UC-TMF 5 CUS - 0824638

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 5.2 mm, Lettering field: 4.6 x 5.1 mm

---

### Marker for terminal blocks - UCT-TMF 5 CUS - 0829658

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 5.2 mm, Lettering field: 4.4 x 4.7 mm

---

## Mounting rail

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733

DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

---

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681

DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119

DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/ 7,5 WH UNPERF 2000MM - 1204122

DIN rail 35 mm (NS 35)

---

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704

DIN rail, unperforated, Width: 35 mm, Height: 7.5 mm, Length: 2000 mm, Color: silver

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421

DIN rail, material: Galvanized, perforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434

DIN rail, material: Galvanized, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM - 0801762

DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

End cap - NS 35/ 7,5 CAP - 1206560

DIN rail end piece, for DIN rail NS 35/7.5

---

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714

DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail perforated - NS 35/15 WH PERF 2000MM - 0806602

DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/15 WH UNPERF 2000MM - 1204135

DIN rail 35 mm (NS 35)

---

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000 mm

---

DIN rail perforated - NS 35/15 ZN PERF 2000MM - 1206599

DIN rail, material: Galvanized, perforated, height 15 mm, width 35 mm, length: 2 m

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

DIN rail, unperforated - NS 35/15 ZN UNPERF 2000MM - 1206586

DIN rail, material: Galvanized, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM - 1201895

DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m

---

End cap - NS 35/15 CAP - 1206573

DIN rail end piece, for DIN rail NS 35/15

---

DIN rail, unperforated - NS 35/15-2,3 UNPERF 2000MM - 1201798

DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

---

## Neutral conductor rail

Neutral busbar - NLS-CU 3/10 SN 1000MM - 0402174

PEN conductor busbar, 3mm x 10 mm, length: 1000 mm

---

## Partition plate

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

Partition plate - ATP-PTI/3 - 3213990

Partition plate, Length: 103 mm, Width: 2.2 mm, Height: 49.3 mm, Color: gray

## Planning and marking software

Software - CLIP-PROJECT ADVANCED - 5146040

Multilingual software for easy planning of Phoenix Contact on DIN rails together with the integrated TRABTECH-select software module for planning comprehensive surge protection concepts.

Software - CLIP-PROJECT PROFESSIONAL - 5146053

Multi-lingual software for terminal strip project planning. A marking module allows professional labeling of markers and labels for marking terminal blocks, conductors, cables and devices. The additionally integrated software module TRABTECH-select for planning comprehensive surge protection concepts.

## Screwdriver tools

Screwdriver - SZS 0,6X3,5 - 1205053

Actuation tool, for ST terminal blocks, insulated, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

## Support

Support bracket - AB-UTI/3 - 3076038

Support bracket, Bracket for busbars, set every 20 cm, Length: 93.5 mm, Width: 2.2 mm, Height: 51.2 mm, Color: blue

## Terminal marking

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

### Zack marker strip - ZB 5 :UNBEDRUCKT - 1050004

Zack marker strip, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.1 x 10.5 mm

---

### Marker for terminal blocks - UC-TM 5 - 0818108

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK CLED, BLUEMARK LED, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 10.5 x 4.6 mm

---

### Marker for terminal blocks - UCT-TM 5 - 0828734

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 4.6 x 10.5 mm

---

### Zack Marker strip, flat - ZBF 5:UNBEDRUCKT - 0808642

Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.1 x 5.2 mm

---

### Marker for terminal blocks - UC-TMF 5 - 0818153

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK CLED, BLUEMARK LED, Plotter, Mounting type: Snap into flat marker groove, for terminal block width: 5.2 mm, Lettering field: 4.6 x 5.1 mm

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

Marker for terminal blocks - UCT-TMF 5 - 0828744

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Snap into flat marker groove, for terminal block width: 5.2 mm, Lettering field: 4.4 x 4.7 mm

---

Test plug terminal block

Test plugs - MPS-MT - 0201744

Test plugs, Color: silver

---

Test adapter - PAI-4-FIX-5/6 BU - 3035975

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Blue

---

Test adapter - PAI-4-FIX-5/6 OG - 3035974

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Orange

---

Test adapter - PAI-4-FIX-5/6 YE - 3035977

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Yellow

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

Test adapter - PAI-4-FIX-5/6 RD - 3035976

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Red

---

Test adapter - PAI-4-FIX-5/6 GN - 3035978

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Green

---

Test adapter - PAI-4-FIX-5/6 BK - 3035980

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Black

---

Test adapter - PAI-4-FIX-5/6 GY - 3035982

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Gray

---

Test adapter - PAI-4-FIX-5/6 VT - 3035979

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Violet

---

# Installation ground terminal block - UTI 2,5-PE/L/L - 3076029

## Accessories

Test adapter - PAI-4-FIX-5/6 BN - 3035981

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Brown

---

Test plugs - PS-5 - 3030983

Test plugs, Color: red

---

Test plugs - PS-5/2,3MM RD - 3038723

Test plugs, Color: red

---

### Warning label printed

Warning label - WS UT 2,5 - 3047923

Warning sign for UT terminal blocks

---

## Drawings

Circuit diagram



---

Phoenix Contact 2015 © - all rights reserved
http://www.phoenixcontact.com