


DO NOT SCALE
DIMENSIONS IN mm

METRIC



NOTES

- 1 NO BEAT IN LOCKING LANCE REQUIRED.
- 2 FOR HIGHER EXTRACTION FORCE APPLICATION.
- 3 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

GENERAL TOLERANCES ± 0.3

OBSOLETE		PRE-TINPLATED	PH. BRONZE	6-160526-8	
		PRE-TINPLATED	BRASS	6-160526-7	
	2/1	UNPLATED	BRASS	9-160526-4	
		TINPLATED	PH. BRONZE	6-160526-2	
		SILVERPLATED	BRASS	6-160526-1	
		SILVERPLATED	PH. BRONZE	6-160526-0	
		TINPLATED	PH. BRONZE	5-160526-9	
		UNPLATED	PH. BRONZE	5-160526-8	
		TINPLATED	BRASS	5-160526-7	
		UNPLATED	BRASS	5-160526-6	
		TINPLATED	PH. BRONZE	160526-4	
NOTES		FINISH	MATERIAL	PART NUMBER	REV

CUSTOMER DRAWING FOR REFERENCE ONLY
WILL NOT BE UPDATED

THIS DRAWING IS UNPUBLISHED
RELEASED FOR PUBLICATION



NAME
FASTIN-FASTON® Connector,
.250" sr. REC. CONTACT.

AL3	REVISED PER ECO-11-005140	RK	HMR	01APR11
LTR.	REVISION RECORD	DR.	CHK.	DATE
DR.: J.v.LIEMPT.	CHK.: A.BIJNEN.	APP.: L.v.SOEST.	DWG.No.	
DATE: 23 MAR 1992	DATE: -	DATE: -	C-160526	REV.LTR. AL3

SHEET
1 OF 1
A3

