#5247 - 24 AWG 15 Pair Foil Shield cUL 2464 PVC

Part NO: #5247
Product Code: RGW-1948

Product Description

Application:
Computer Cable for EIA RS-232 Applications

Muli-construction
15 Pair

Construction

	Tinned Copper
Construction	T0.20±0.008×7
Stranded Dia.(mm)	0.61
Insulation	**PVC**
Thickness(mm)	0.25
Insulation Dia.(mm)	1.10
Insulation Color	Red/Black,White/Black, Green/Black,Blue/Black, Red / Yellow, Red / Brown, Black/Yellow, Black / Brown Red / Orange, Green/ White Black/Orange, Red/White Green / Blue Red/Green, Red/Blue
Al-Pet Shield	**≥125%**
Drain wire	**Tinned Copper**
Construction	T0.20±0.008×7
Jacket Color	**PVC**
Thickness(mm)	0.90
Dia.(mm)	10.60
Jacket Color	Grey (RAL 7001)

Marking
Exxxxxx #5247 15PR 24 AWG SHIELDED 75C (UL) TYPE CM or AWM 2464 or c(UL) 60C TYPE CMG FT4 CE ROHS

PACKAGING
100M/Wooden Drum

RoHS GUIDELINE
We operate according to the following standards

Control Item	Standard	Testing Method	Testing Equipment
Cadmium content (Cd)	<0.01%	EN1122	ICP-AES
Lead content (Pb)	<0.1%	EPA3050B	ICP-AES
Mercury content (Hg)	<0.1%	EPA3052	ICP-AES
Chromium (VI) content	<0.1%	EPA3060(UN-VIS)	ICP-AES
Polybrominated Biphenyls(PBB)	Forbidden	GC/MS	
Polybrominated Diphenyl Ether (PBDE)	Forbidden	GC/MC	

Revision History
A0-1

Design



Electrical Characteristics

Max.Conductor DC Resistance at 20℃（Ω/Km）	<84.8
Rated Temperature(℃)	-30 to 80
Rated Voltage(V)	300 RMS
Min.Insulation DC Resistance at 20℃（MΩ*Km)	>200
Capacitance Cond to Cond. (pF/m)	98.43
Capacitance Cond to Shield. (pF/m)	164.05
Velocity of Propogation	60%
Nom Characteristic Impedance	75 Ohms
Nom Inductance (μH/m)	0.61
Max Recommended Current Amps@25C	1.5
UL Style	AWM/STYLE 2464 80 C /300VRMS CM 75C
CSA	c(UL) Type CMG 60C FT4
CE	EU Low Voltage Directive 2006/95/EC

Date:	**2013-04-22**
Page:	**1 / 1**

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.