

Features

Regulated Converters

- 2:1 and 3:1 Wide Input Voltage Ranges
- 1kVDC, 2kVDC and 3kVDC Isolation
- UL94V-0 Package Material
- Continuous Short Circuit Protection
- Low Ripple and Noise
- Remote On/Off Control
- Efficiency to 83 %

Description

Very high power density, 2:1 or 3:1 input voltage range and a wide operating temperature range -40°C~+71°C and extra features such as On/Off control are just some of the characteristics of this converter which is ideal for highly sophisticated industrial designs. The RS3 is available with 2kV or 3kV isolation options (1kVDC is standard)

Selection Guide

Part Number		Input Voltage Range (VDC)	Rated Output Voltage (VDC)	Output Current Full Load (mA)	Efficiency typ. (%)	Max Capacitive Load ⁽¹⁾
SIP8						
RS3-xx3.3S	(H2/H3)	4.5-9, 9-18 18-36, 36-72	3.3	600	73-75 77-78	4700µF
RS3-xx05S	(H2/H3)	4.5-9, 9-18 18-36, 36-72	5	600	76-79 80-81	4700µF
RS3-xx09S	(H2/H3)	4.5-9, 9-18 18-36, 36-72	9	333	77-80 81-82	3300µF
RS3-xx12S	(H2/H3)	4.5-9, 9-18 18-36, 36-72	12	250	80-81 83	2200µF
RS3-xx15S	(H2/H3)	4.5-9, 9-18 18-36, 36-72	15	200	80-81 83	2200µF
RS3-xx3.3D	(H2/H3)	4.5-9, 9-18 18-36, 36-72	±3.3	±300	73-75 75	±2200µF
RS3-xx05D	(H2/H3)	4.5-9, 9-18 18-36, 36-72	±5	±300	76-80 80-81	±2200µF
RS3-xx09D	(H2/H3)	4.5-9, 9-18 18-36, 36-72	±9	±167	77-81 81	±2200µF
RS3-xx12D	(H2/H3)	4.5-9, 9-18 18-36, 36-72	±12	±125	78-83 83	±1000µF
RS3-xx15D	(H2/H3)	4.5-9, 9-18 18-36, 36-72	±15	±100	79-83 83	±1000µF
RS3-xx3.3SZ	(H2/H3)	9-27 20-60	3.3	600	73 74	4700µF
RS3-xx05SZ	(H2/H3)	9-27 20-60	5	600	76-79 78	4700µF
RS3-xx09SZ	(H2/H3)	9-27 20-60	9	333	77 79	3300µF
RS3-xx12SZ	(H2/H3)	9-27 20-60	12	250	80 80	2200µF
RS3-xx15SZ	(H2/H3)	9-27 20-60	15	200	80 80	2200µF
RS3-xx3.3DZ	(H2/H3)	9-27 20-60	±3.3	±300	73 74	±2200µF
RS3-xx05DZ	(H2/H3)	9-27 20-60	±5	±300	77 78	±2200µF
RS3-xx09DZ	(H2/H3)	9-27 20-60	±9	±167	79 79	±2200µF
RS3-xx12DZ	(H2/H3)	9-27 20-60	±12	±125	80 80	±1000µF
RS3-xx15DZ	(H2/H3)	9-27 20-60	±15	±100	80 80	±1000µF

No suffix is standard isolation (1kVDC) e.g., RS3-0505S

*add suffix /H2 or /H3 for 2kVDC or 3kVDC isolation, e.g., RS3-0505S/H2, R3S-0505DZ/H3

ECONOLINE

DC/DC-Converter

with 3 year Warranty



3 Watt SIP8 Isolated Single & Dual Output



EN-60950-1 Certified
EN-60601-1 Certified
(Suffix /H3)

RS3

2:1 Input
(RS3-S/D)

xx = 4.5-9Vin = 05
xx = 9-18Vin = 12
xx = 18-36Vin = 24
xx = 36-72Vin = 48

3:1 Input
(RS3-SZ/DZ)

xx = 9-27Vin = 24
xx = 20-60Vin = 48


Refer to Application Notes

Electrical Specifications (measured at $T_A = 25^\circ\text{C}$, at nominal input voltage and rated output current unless otherwise specified)


Input Voltage Range		2:1 and 3:1		
Output Accuracy		Nominal Vin and full load	±2% typ.	
Line Voltage Regulation		LL to HL, full load	±0.5% max.	
Load Voltage Regulation		20% to 100% full load	±0.5% typ.	
Minimum Load		0%		
Output Ripple and Noise		20MHz limited	50mVp-p max.	
Switching Frequency		20% to 100% full load	200kHz typ.	
Efficiency at Full Load		see Selection Guide		
Quiescent Current		RS-05xxS_D	35mA typ.	
Nominal input Voltage		RS-12xxS_D	25mA typ.	
(Standard, /H2 and /H3)		RS-24xxS_D, SZ_DZ	20mA typ.	
		RS-48xxS_D, SZ_DZ	10mA typ.	
Isolation Voltage	Standard	(tested for 1 second)	1000VDC	
		(rated for 1 minute)	500VAC / 60Hz	
	/H2 Version	(tested for 1 second)	2000VDC	
		(rated for 1 minute)	1000VAC / 60Hz	
/H3 Version	(tested for 1 second)	3000VDC		
	(rated for 1 minute)	1500VAC / 60Hz		
Isolation Capacitance (2:1 and 3:1) (tested at 100kHz)		H1	200pF max.	
		H2/H3	30pF max.	
Isolation Resistance		1GΩ min.		
Short Circuit Protection (see note)		Continuous		
Operating Temperature Range		−40°C to +71°C		
Storage Temperature Range		−55°C to +125°C		
Relative Humidity		95% RH		
Package Weight		4.7g		
Packing Quantity		22 pcs per Tube		
MTBF (+25°C) (+71°C)		Detailed Information see Application Notes chapter "MTBF"	using MIL-HDBK 217F	3303 x10³ hours
			using MIL-HDBK 217F	745 x10³ hours

Note: To protect the converter under all fault conditions, an input fuse is required. The fuse should be rated at 5x the normal input current or at the maximum current the primary power supply can deliver, whichever is the lesser.

Derating-Graph (Ambient Temperature)




Typical Application




Typical Characteristics

RS3-0505S







RS3-4805D





Package Style and Pinning (mm)

3rd angle projection



Recommended Footprint Details



XX.X ± 0.5 mm
XX.XX ± 0.25 mm

Pin Connections

Pin #	Single	Dual
1	-Vin	-Vin
2	+Vin	+Vin
3	CTRL	CTRL
5	NC	NC
6	+Vout	+Vout
7	-Vout	Com
8	NC	-Vout

NC = No Connection

Notes

Note 1 Maximum capacitive load is defined as the capacitive load that will allow start up in under 1 second without damage to the converter

Certifications

EN General Safety	Report: PS-R7219C1	EN60950-1:2001 + A11:2004
EN Medical Safety	Report: PS071001601	EN60601-1:1990 + A11:1996

Pin 8 (NC*) This pin is used internally and must have no external connection.

Pin 5 (NC) Not connected internally.

Pin 3 (CTRL)

This pin provides an Off function which puts the converter into a low power mode. When the pin is 'high' the converter is OFF and when the pin is high 'Z' the converter is ON. There is no allowed low state for this pin.


Application Examples

TTL Remote CTRL Circuit

Control Pin Input Current: 10mA

Voltage Set Point Accuracy with external input/output capacitors refer to recommended test circuit: typ. ± 1% max. ± 2%

Control Pin (CTRL) Input Current, control voltage applied via 1K resistor, output voltage must reduce to OV: typ. 3mA max. 6mA



Voltage to be applied via a limiting resistor with a recommended value of 1K for RS3-05xx; 3.3K for RS3-12xx; RS3-24xx and 10K for RS3-48xx.

Isolated Remote CTRL Circuit

