

UNIVERSAL

PROTECTION FOR EVERYBODY

Enveloping, the UNIVERSAL fits everybody thanks to his B-Flex bridge and its pivoting temples.

The Universal impresses with its sporty design and technology. It's B-Flex bridge with memory retention is a unique design: flexible, its lightweight bridge adapts to everybody while reducing pressure points on the face. The temples pivot to allow the user to tilt the angle of the front and thus perfectly fit the face. Its dual injection straight sports temples grip guaranteeing flawless fit and ultra comfort.

Ref. UNIPSI - UNIPSF
Supplied with an adjustable cord

Europe Bollé Safety
95 Rue Louis Guérin
69100 Villeurbanne - France
tel: 00 33 (0) 4 78 85 23 64
fax: 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park
Leatherhead Road - Chessington
Surrey - KT19 2NY
tel. 00 44 (0)208 391 4700
fax 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk



The + product:

- Anti-scratch, anti-fog coatings
- Upper and lower protection
- Non slip noze B-Flex bridge
- Pivoting temples

+ New Technology

B FLEX

bolle
SAFETY

bolle-safety.com

STANDARDS MARKINGS :

Products ref.	LENSES													FRAMES														
	 Risks relating to radiations			Optical quality			 Mechanical Risks			Electrical Risks	Thermal Risks	 Coatings optional marking K: anti-scratch N: anti-fog				Standards	 Chemical Risks			Electrical Risks	 Mechanical Risks			Thermal Risks	 Coatings optional marking K: anti-scratch N: anti-fog			
	EN 170 - UV	EN 172 - Solar (100% UV)		Permanent wear	Intermittent wear	Short period	Low energy impact 45 m/s	Medium energy impact 120 m/s	High energy impact 190 m/s	Extremes of temperature impact	Electric arc short circuiting	Molten metals and hot solids	anti-scratch				anti-fog	Liquid drops	Large dust particles > 5 microns	Gas and fine dust particles < 5 microns	Electric arc short circuiting	Low energy impact 45 m/s	Medium energy impact 120 m/s	High energy impact 190 m/s			Extremes of temperature impact	Molten metals and hot solids
UNIPSI	2C-1,2			1			F			T			OK	OK			EN 166					F			T			
UNIPSF	5-3.1			1			F			T			OK	OK			EN 166					F			T			

UNIPSI



UNIPSF

CHARACTERISTICS :

Lenses	PC - 2,3 mm - Curve 9
Frame	PC
Temples	PC + TPR
Strap	Non applicable
Foam	Non applicable
Spare lenses	No

PACKAGING AND EAN 13 CODE :

	UNIPSI	UNIPSF
individual plastic bag	3660740006525	3660740006532
10 safety spectacles per box	3660740106522	3660740106539
300 safety spectacles per outer pack	3660740206529	3660740206536

Notified
laboratories
for
certification :

BSI
Product Services



DIN

INSPIC

bolle-safety.com