

HAKKO FA-400 ESD SAFE SMOKE ABSORBER

Desktop Type Smoke Absorber



- Desktop solder smoke absorber that can be mounted horizontally or vertically
- An optional arm stand makes a third mounting position available.

2 Way Plus Placement


Vertically mounted:



Horizontally mounted:



Using a stand:



Packing List

| | |
|--------|----------------------------------|
| FA-400 | Unit, Filter, Instruction manual |
|--------|----------------------------------|

Specifications

| Model No. | FA-400 |
|-------------------------|--|
| Power consumption | 50 Hz: 15 W (100 V), 18 W (110 V), 19 W (220 V), 22 W (230 V), 24 W (240 V) 60 Hz: 13 W (100 V), 15 W (110 V), 19 W (120 V), 16 W (220 V), 18 W (230 V), 19 W (240 V) |
| Noise level* | 50 Hz: 48 dB 60 Hz: 51 dB |
| Max. suction capacity** | Vertically: 1.0 m ³ /min. (50 Hz), 1.1 m ³ /min. (60 Hz) Horizontally: 0.4 m ³ /min. (50 Hz), 0.5 m ³ /min. (60 Hz) |
| Air velocity | Vertically: 1.0 m/s (50 Hz), 1.1 m/s (60 Hz) Horizontally: 2.6 m/s (50 Hz), 2.9 m/s (60 Hz) |
| Filter size | 130 (W) × 130 (H) × 10 (D) mm |
| Dimensions | 166 (W) × 212 (H) × 113 (D) mm |
| Weight*** | 0.91 kg |

* Measured at a distance of 1 m from the face of the unit

** Measured with a filter present

*** Without cord

Option

| Part No. | Name | Specifications |
|----------|-----------|----------------|
| C1568 | Arm stand | With knobs |