

## RE9RA11MW7

off-delay timing relay - 0.1..10 s - 240 V AC - solid state



### Main

Range of product	Zelio Time
Product or component type	Industrial timing relay
Discrete output type	Solid state
Component name	RE9
Time delay type	C
Time delay range	0.1...10 s

### Complementary

Width pitch dimension	22.5 mm
[Us] rated supply voltage	24...240 V AC at 50/60 Hz
Voltage range	0.85...1.1 Us
Connections - terminals	Screw terminals, clamping capacity: 2 x 1.5 mm <sup>2</sup> flexible with cable end Screw terminals, clamping capacity: 2 x 2.5 mm <sup>2</sup> flexible without cable end
Tightening torque	0.6...1.1 N.m
Setting accuracy of time delay	< +/- 20 %
Repeat accuracy	< 1 %
Reset time	>= 100 ms after time delay period
Switching time	>= 40 ms
Temperature drift	<= 0.1 %/°C
Continuous output current	<= 0.7 A at 20 °C
Minimum output current	10 mA at 20 °C
Overload current	<= 15 A during 10 ms conforming to VDE 0435 (part 303), 4.8.3/class II
Voltage drop	<= 3 V closed contact(s) 0.7 A
Leakage current	<= 1 mA open contact contact(s)
Power dissipation in W	<= 4 W
Electrical durability	> 100000000 cycles
Marking	CE
Overvoltage category	III conforming to IEC 60664-1
[Ui] rated insulation voltage	250 V IEC certified 300 V CSA certified
Supply disconnection value	> 0.1 Uc
Operating position	Any position without derating
Surge withstand	2 kV conforming to IEC 61000-4-5 level 3
CAD overall width	22.5 mm
CAD overall height	78 mm
CAD overall depth	80 mm
Product weight	0.11 kg

### Environment

Immunity to microbreaks	<= 2 ms during time delay period
Derating factor	None for > 20 °C
Standards	EN/IEC 61812-1
Product certifications	CSA GL UL

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ambient air temperature for storage	-40...85 °C
Ambient air temperature for operation	-20...60 °C
Relative humidity	15...85 % (3K3) conforming to IEC 60721-3-3
Vibration resistance	0.35 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
IP degree of protection	IP20 (terminals) IP50 (housing)
Pollution degree	3 conforming to IEC 60664-1
Dielectric strength	2.5 kV
Non-dissipating shock wave	4.8 kV
Resistance to electrostatic discharge	6 kV (in contact) conforming to IEC 61000-4-2 level 3 8 kV (in air) conforming to IEC 61000-4-2 level 3
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3 level 3
Resistance to fast transients	2 kV conforming to IEC 61000-4-4 level 3
Disturbance radiated/conducted	CISPR 11 group 1 - class A CISPR 22 - class A