



## Main

|   |   |
|---|---|
| Range                                       | TeSys   |
| Product name                                | TeSys D   |
| Product or component type                   | Contacteur  |
| Device short name                           | LC1D  |
| Contacteur application                      | Resistive load  |
| Utilisation category                        | AC-1  |
| Poles description                           | 4P  |
| Pole contact composition                    | 4 NO  |
| [Ue] rated operational voltage              | <= 1000 V AC 25...400 Hz for power circuit<br><= 460 V DC for power circuit   |
| [Ie] rated operational current              | 200 A (<= 60 °C) at <= 440 V AC AC-1 for power circuit  |
| Control circuit type                        | AC 50 Hz  |
| Control circuit voltage                     | 230 V AC 50 Hz  |
| [Uimp] rated impulse withstand voltage      | 8 kV conforming to IEC 60947  |
| Overvoltage category                        | III   |
| [Ith] conventional free air thermal current | 200 A at <= 60 °C for power circuit   |
| Irms rated making capacity                  | 1260 A at 440 V for power circuit conforming to IEC 60947   |
| Rated breaking capacity                     | 1100 A at 440 V for power circuit conforming to IEC 60947   |
| [Icw] rated short-time withstand current    | 1100 A <= 40 °C 1 s power circuit<br>250 A <= 40 °C 10 min power circuit<br>550 A <= 40 °C 1 min power circuit<br>950 A <= 40 °C 10 s power circuit                   |
| Associated fuse rating                      | 200 A gG at <= 690 V coordination type 2 for power circuit<br>250 A gG at <= 690 V coordination type 1 for power circuit  |
| Average impedance                           | 0.6 mOhm at 50 Hz - Ith 200 A for power circuit   |
| [Uij] rated insulation voltage              | 1000 V for power circuit conforming to IEC 60947-4-1<br>600 V for power circuit certifications CSA<br>600 V for power circuit certifications UL                       |
| Electrical durability                       | 0.8 Mcycles 200 A AC-1 at Ue <= 440 V   |
| Power dissipation per pole                  | 24 W AC-1   |
| Protective cover                            | Without   |
| Mounting support                            | Plate<br>Rail   |
| Standards                                   | EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14   |
| Product certifications                      | BV<br>CCC<br>CSA<br>DNV<br>GL<br>GOST<br>RINA<br>UL<br>LROS   |
| Connections - terminals                     | Power circuit : bars 1 5 x 25 mm<br>Control circuit : lugs-ring terminals - external diameter: 8 mm<br>Power circuit : lugs-ring terminals - external diameter: 25 mm |
| Tightening torque                           | Control circuit : 1.2 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm<br>screw : M3.5   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Control circuit : 1.2 N.m - on lugs-ring terminals - with screwdriver Philips No 2 screw : M3.5  
 Power circuit : 12 N.m - on lugs-ring terminals hexagonal 13 mm screw : M8  
 Power circuit : 12 N.m - on bars hexagonal 13 mm screw : M8

|                          |  |
|--------------------------|--|
| Operating time           | 6...20 ms opening<br>20...50 ms closing  |
| Safety reliability level | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 |
| Mechanical durability    | 8 Mcycles  |
| Operating rate           | 2400 cyc/h at $\leq 60$ °C   |

## Complementary

|                                 |  |
|---------------------------------|--|
| Coil technology                 | Without built-in suppressor module   |
| Control circuit voltage limits  | 0.3...0.6 Uc at 55 °C drop-out 50 Hz<br>0.85...1.1 Uc at 55 °C operational 50 Hz |
| Inrush power in VA              | 300 VA at 20 °C (cos $\phi$ 0.8) 50 Hz   |
| Hold-in power consumption in VA | 22 VA at 20 °C (cos $\phi$ 0.3) 50 Hz  |
| Heat dissipation                | 3...8 W at 50 Hz   |

## Environment

|   |   |
|---|---|
| IP degree of protection                               | IP2x front face conforming to IEC 60529   |
| Protective treatment                                  | TH conforming to IEC 60068-2-30   |
| Pollution degree                                      | 3   |
| Ambient air temperature for operation                 | -5...60 °C  |
| Ambient air temperature for storage                   | -60...80 °C   |
| Permissible ambient air temperature around the device | -40...70 °C at Uc   |
| Operating altitude                                    | 3000 m without derating in temperature  |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1  |
| Flame retardance                                      | V1 conforming to UL 94  |
| Mechanical robustness                                 | Vibrations contactor open 2 Gn, 5...300 Hz<br>Vibrations contactor closed 4 Gn, 5...300 Hz<br>Shocks contactor closed 15 Gn for 11 ms<br>Shocks contactor open 6 Gn for 11 ms |
| Height  | 158 mm  |
| Width   | 155 mm  |
| Depth   | 115 mm  |
| Product weight  | 2.86 kg   |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS                             | Compliant - since 0742 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product environmental profile    | Available   |
| Product end of life instructions | Available   |