

Datasheet

RS Pro PID Temperature Controller, 48 x 48mm, 3 Output Relay, SSR, 24 V ac/dc Supply Voltage

RS Stock No: **774-0263**



Product Details

RS Pro PID temperature controller is designed for measuring and controlling temperature and any process value. This controller has 3 output relays and operates at a voltage rating of 24 V ac/dc. It can be used in many applications with its universal process input, control outputs, selectable alarm functions. It measures 48 x 48 mm. It is mainly used in glass, plastic, petro-chemistry, textile, automotive and machine production industries.

Features and Benefits

- 4 digits process (PV) and 4 digits process set (SV) display
- Universal process input
- Dual or multipoint calibration for DC-voltage/DC-current input
- Configurable ON/OFF, P, PI, PD and PID control forms
- Auto-tune and self-tune PID
- Manual/automatic mode selection for control outputs
- Bumpless transfer
- Programmable heating, cooling and alarm functions for control outputs

**Specifications:**

Additional Functionality	On/Off
Communication Module Available	No
Configurable Outputs	Relay, SSR
Control Type	On/Off, P, PI, PD, PID Controller
Display Colour	Green, Red
Maximum Operating Temperature	+50°C
Minimum Operating Temperature	0°C
Panel Depth	87.5 mm
Size	48 x 48 mm
Display Type	LED
Input Type	Universal Input TC, RTD, Voltage/Current (dc)
IP Rating	IP20, IP65
Mounting Type	1/16 DIN Rail
Number of Outputs	3
Output Type	Relay, SSR
Supply Voltage	24 V ac/dc
Temperature Range	0 to +50°C
Standards Met	RoHS Compliant; UL Listed; GOST-R; CE Certified