

## M4/6.D1.1

ABB contact for United States of America



## General Information

---

<b>Extended Product Type:</b>	M4/6.D1.1
<b>Product ID:</b>	1SNA115204R2000
<b>EAN:</b>	3472591152043
<b>Catalog Description:</b>	M4/6.D1.1 Screw Clamp Terminal Blocks - Double deck - Grey
<b>Long Description:</b>	M4/6.D1.1 Screw Clamp Terminal Blocks - Feed-through - Grey,4mm <sup>2</sup> RatedCrossSection, 6mm Spacing G32, TH 35-7.5, TH 35-15 Rail

---

## Categories

---

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Screw Clamp Terminal Blocks

---

## Additional Information

---

<b>Ambient Temperature:</b>	-5 ... +40 °C
<b>Color:</b>	Grey
<b>Connecting Capacity-Main Circuit:</b>	Screw Clamp / Flexible 1x 0.22 ... 4 mm <sup>2</sup> Screw Clamp / Rigid 1x 0.2 ... 4 mm <sup>2</sup>
<b>Connection Type:</b>	Screw clamp
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
<b>Function:</b>	Feed-through
<b>Gauge Type:</b>	A4
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Insulation Material:</b>	Polyamide
<b>Mounting on DIN Rail:</b>	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
<b>Number of Levels:</b>	2
<b>Pollution Degree:</b>	3
<b>Product Main Type:</b>	M4/6.D1
<b>Product Name:</b>	Terminal block
<b>Rated Cross-Section:</b>	4 mm <sup>2</sup>
<b>Rated Current (I<sub>n</sub>):</b>	Main Circuit 32 A
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	8000 V
<b>Rated Short-time Withstand Current (I<sub>cw</sub>):</b>	for 1.0s 480 A
<b>Rated Voltage (U<sub>r</sub>):</b>	800 V
<b>Recommended Screw Driver:</b>	4 mm
<b>RoHS Date:</b>	20050818
<b>Spacing:</b>	6 mm
<b>Sub-Function:</b>	4 connections
<b>Sub-Function 2:</b>	With no partition on the lower deck
<b>Sub-Function 3:</b>	4 connections
<b>Sub-Function 4:</b>	With partial partition
<b>Wire Stripping Length:</b>	8.5 mm

---

## Certificates and Declarations (Document Number)

---

CSA Certificate:	TBD - OK in Ag.Base
Declaration of Conformity - CE:	1SND225002C1007
EAC Certificate:	1SND161009A1100
RoHS Information:	1SND230023F0206

---

## Classifications

---

ETIM 4.0:	EC000897 - Feed-through terminal block
ETIM 5.0:	EC000897 - Feed-through terminal block
Object Classification Code:	X

---

## Container Information

---

Package Level 1 Units:	50 piece
Package Level 1 Width:	163 mm
Package Level 1 Height:	57 mm
Package Level 1 Length:	130 mm
Package Level 1 Gross Weight:	1.00000 kg
Package Level 1 EAN:	3472591152043
Package Level 2 Units:	1000 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Gross Weight:	20.500 kg
Package Level 3 Units:	24000 piece
Product Packing Type:	Box

---

## Dimensions

---

Product Net Width:	6.0 mm
Product Net Height:	65.5 mm
Product Net Depth:	52.0 mm
Product Net Weight:	20.00 g

---

## Environmental

---

Ambient Air Temperature:	Storage -55 ... +110 °C Operation -55 ... +110 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

---

## Ordering

---

EAN:	3472591152043
Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010

---

## Technical UL/CSA

---

Flammability According to UL94:	V0
---------------------------------	----

---

