

#4141 - Blue 2 Core Microphone Cable



Part NO: #4141
Product Code: RGW-1934

Product Description

Application:

For Microphone Cable

Multi-construction

2 Core

Construction

2 Core	Tinned Copper
Construction	T0.12±0.008×32
Stranded Dia.(mm)	0.78
Insulation 1	PE
Thickness	0.31
Insulation Dia.(mm)	1.4±0.08×2C Twist
Insulation Color	According to the customer
Drain Wire	Tinned Copper
Construction(mm)	T0.12±0.008×30
Insulation 2	Semi-Conductive PE
Thickness	0.3
Insulation Dia.(mm)	3.40±0.15
Insulation Color	Black
Nylon Rip Cord	150D
Jacket	Flexible PVC
Thickness(mm)	1.60
Dia.(±0.15mm)	6.60
Jacket Color	Blue

Marking

2 Core Microphone Cable Screened 32/0.12mm PVC


PACKAGING

100M/Reel

Revision History

A0-1

Design



Electrical Characteristics

Max.Conductor DC Resistance at 20°C (Ω /Km)	<55.5
Rated Temperature(°C)	-20~80
Rated Voltage (V)	60
Min.Insulation DC Resistance at 20°C (MΩ *Km)	>200
Capacitance pF/m	165
Weight (kg/100m)	5.6

RoHS GUIDELINE

We operate according to the following standards

Control Item	Standard	Testing Method	Testing Equipment
Cadmium content (Cd)	<0.01%	EN1122	ICP-AES
Lead content (Pb)	<0.1%	EPA3050B	ICP-AES
Mercury content (Hg)	<0.1%	EPA3052	ICP-AES
Chromium (VI) content	<0.1%	EPA3060(UN-VIS)	ICP-AES
Polybrominated Biphenyls(PBB)	Forbidden	GC/MS	
Polybrominated Diphenyl Ether (PBDE)	Forbidden	GC/MC	

Date: 2013-03-29

Page: 1 / 1