

## TECHNICAL DATA

# SLIDEWAY LUBRICANT SPRAY

## Machine Tool Slideway Oil

### Description

ROCOL Slideway Lubricant is specially designed to overcome "stickslip" phenomena and provide smooth and precise movement of machine tool slideways, collets and chucks. The extreme pressure agents and anti-wear additives reduce wear, while the adhesive qualities of the lubricant reduce draining to a minimum, ensuring effective performance over a long period of time.

### Outstanding Features

- **Resists washing action of coolant and protects against corrosion**
- **Provides lasting lubrication**
- **Clings to vertical faces, and does not fling off rotating parts**
- **Easy to apply into inaccessible areas**

### Directions for use

Shake well before use, hold upright and spray from a distance of 15 to 30cm. Test compatibility with painted or coated surfaces, plastics and rubbers prior to application.

### Technical Data

<i>Appearance (Applied Film)</i>	: <i>Thin clear film</i>
<i>Solvent</i>	: <i>Dichloromethane</i>
<i>Propellant</i>	: <i>Carbon dioxide</i>
<i>Odour</i>	: <i>Characteristic</i>
<i>Base Fluid Type</i>	: <i>Solvent refined mineral oil</i>
<i>Silicone</i>	: <i>None</i>
<i>Storage</i>	: <i>Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.</i>

### Health and Safety

Further Technical Data and Health and Safety information (COSHH, MSDS) is available from the Customer Service Department, ROCOL Ltd., ROCOL House, Swillington, Leeds, LS26 8BS, England.

**Telephone:** 0113 232 2700, (When calling from outside UK: 44 113 232 2700).

**Fax:** 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: 5204a 12/04/96

#### **ROCOL Limited**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9002 registered company.

ROCOL is a trade mark of ROCOL Limited

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility