

Lightning/surge arrester type 1/2 - VAL-MS-AR-T1/T2 75 - 2801491

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




The VAL-MS-AR T1/T2 75 is a high-capacity SPD for Type 1 lightning as well as Type 2 switching surge currents, ideal for applications with both high load currents and high surge risk. VAL-MS BE-AR base provides a disconnect that separates the field wire from the protected mode for field diagnosis. Independent input and output terminals on the same side with ground terminals on the opposite end. All terminals are high-current screw clamping for stripped or ferruled, solid or stranded wires.

Why buy this product

- Versions with and without floating remote indication contact
- Separate field and house wire termination.
- Tool-free field wire disconnect and test point.
- IP20 touch safe when connected.
- T1/T2 plugs provide lightning and surge current class protection.



Key commercial data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 046356 879507
Weight per Piece (excluding packing)	222.22 g
Custom tariff number	85363010
Country of origin	United States
Note	Made to Order (non-returnable)

Technical data

Dimensions

Height	153 mm
Width	17.7 mm
Depth	77.5 mm

Ambient conditions

Degree of protection	IP20
	IP20 (when disconnect closed)
Ambient temperature (operation)	-40 °C ... 80 °C
Altitude	max. 3000 m

Lightning/surge arrester type 1/2 - VAL-MS-AR-T1/T2 75 - 2801491

Technical data

Ambient conditions

Permissible humidity (operation)	5 % ... 95 %
Permissible humidity (storage/transport)	5 % ... 95 %
Shock (operation)	10g
Vibration (operation)	2g (0 ... 200 Hz)

General

Housing material	PA
Inflammability class according to UL 94	V0
Color	black
Total surge current (8/20) μ s	50 kA
Total surge current (10/350) μ s	15 kA
Mounting type	DIN rail mounting with additional retaining screw
Type	DIN rail module, two-section, divisible
Surge protection fault message	Optical
Direction of action	L-L / L-PE

Protective circuit

IEC test classification	I / II
	T1 / T2
EN type	T1 / T2
Nominal voltage U_N	60 V DC
Maximum continuous operating voltage U_C	75 V DC
Maximum continuous operating voltage U_C (L-N)	75 V DC
Rated load current I_L	55 A (with 6 AWG)
Max. discharge current I_{max} (8/20) μ s	50 kA
Nominal discharge current I_n (8/20) μ s	12.5 kA
Impulse discharge current (10/350) μ s charge	6.25 As
Impulse discharge current (10/350) μ s, specific energy	39 kJ/ Ω
Impulse discharge current (10/350) μ s, peak value I_{imp}	12.5 kA
Voltage protection level U_p	≤ 0.7 kV
Residual voltage	≤ 0.6 kV (at 5 kA)
	≤ 0.65 kV (at 10 kA)
	≤ 0.7 kV
	≤ 0.55 kV (at 3 kA)
Max. backup fuse with branch wiring	160 A
Short-circuit resistance I_p with max. backup fuse (effective)	500 A

Connection, protective circuit

AWG conductor cross section	15 ... 2 (UL)
	20 ... 6
	12 ... 4

Lightning/surge arrester type 1/2 - VAL-MS-AR-T1/T2 75 - 2801491

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130802
eCl@ss 7.0	27130802

ETIM

ETIM 4.0	EC001675
ETIM 5.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Accessories

Accessories

Bridge

Wiring bridge - MPB 18/1-57 - 2809238



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 57-pos.

Wiring bridge - MPB 18/1- 2 - 2809209



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 2-pos.

Lightning/surge arrester type 1/2 - VAL-MS-AR-T1/T2 75 - 2801491

Accessories

Wiring bridge - MPB 18/1-12 - 2748593



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 12-pos.

Plug-in bridge - FBS 2-18 - 2801068



Plug-in bridge for cross-connections in the VAL-MS BE-AR terminal center, 2-pos., color: Red

Wiring bridge - MPB F600X16/ 1GS - 2818355



Wiring bridge flexible, diameter: 16 mm², with a fork-type cable lug on one side, length: 600 mm

Wiring bridge - MPB F600X16/ 1GS - 2818355



Wiring bridge flexible, diameter: 16 mm², with a fork-type cable lug on one side, length: 600 mm

Wiring bridge - MPB F200X16/ 1GS - 2818339



Wiring bridge flexible, diameter 16 mm², with a fork-type cable lug on one side, length: 200 mm

Lightning/surge arrester type 1/2 - VAL-MS-AR-T1/T2 75 - 2801491

Accessories

Wiring bridge - MPB 18/1-10/1.0.0 - 2830443



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 10 pitches with contact sequence 1-0-0

Wiring bridge - MPB 18/4-12 - 2809296



Wiring bridge for modules with connecting pitch 17.5 mm, 4-phase, 12-pos.

Wiring bridge - MPB 18/4- 8 - 2809283



Wiring bridge for modules with connecting pitch 17.5 mm, 4-phase, 8-pos.

Wiring bridge - MPB 18/3- 6 - 2809241



Wiring bridge for modules with connecting pitch 17.5 mm, 3-phase, 6-pos.

Wiring bridge - MPB 18/1-57 - 2809238



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 57-pos.

Lightning/surge arrester type 1/2 - VAL-MS-AR-T1/T2 75 - 2801491

Accessories

Wiring bridge - MPB 18/1-12 - 2748593



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 12-pos.

Wiring bridge - MPB 18/1- 9 - 2748580



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 9-pos.

Wiring bridge - MPB 18/1- 8 - 2748577



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 8-pos.

Wiring bridge - MPB 18/1- 6 - 2748564



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 6-pos.

Wiring bridge - MPB 18/1- 4 - 2809225



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 4-pos.

- MPB 18/1- 3 - 2809212

Lightning/surge arrester type 1/2 - VAL-MS-AR-T1/T2 75 - 2801491

Accessories

Wiring bridge - MPB 18/1- 2 - 2809209



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 2-pos.

Insertion bridge

Insertion bridge - EB 56-18 - 3009299



Insertion bridge, Number of positions: 56, Color: gray

Screwdriver tools

Screwdriver - SZS 0,8X4,0 VDE - 1212508



Screwdriver, slot-headed, VDE insulated, size: 0.8 x 4.0 x 100 mm, 2-component grip, with non-slip grip

Screwdriver - SZS 1,0X6,5 VDE - 1205079



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip

Screwdriver - SZS 0,4X2,5 VDE - 1205037



Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

Spare parts

Lightning/surge arrester type 1/2 - VAL-MS-AR-T1/T2 75 - 2801491

Accessories


Type 1/2 surge protection plug - VAL-MS-T1/T2 75/12.5 ST - 2801146



Replacement plug for VAL-MS-T1/T2 75/12.5... plug-in lightning/surge arrester.

Drawings

Circuit diagram



Dimensioned drawing

