Fiberscope for industry and the trades

High powered lens
Halogen lamp
Focus ring

The remarkable testo 318-2 fiberscope, probe length 457 mm, gives you an inside edge on diagnosing hundreds of maintenance and repair problems. The revolutionary flexible shaft adjusts into almost any position.

A high powered lens clearly focuses on objects as close as 19 mm while a powerful halogen lamp illuminates dark areas with the simple push of a button. While the sealed lens and shaft may be immersed in liquids without worry.

- **Get the inside picture, probe length 457 mm**
- **One hand operation with light switch and focus ring**
- **Powerful halogen lamp for optimum illumination**
- **Optional, clip on 45 degree mirror makes inspection a snap**

Inspecting a hard to reach point in a heating system

Fast and complete heat exchanger inspection with 45° mirror (optional)

testo 318-2

Probe length: 457 mm

testo 318-2, fiberscope, probe length 457 mm, incl. halogen lamp, batteries and instruction manual

Part no. 0632 0319

Ordering data for Accessories

	Part no.
Spare halogen lamp Extremely powerful for optimum illumination, even in dark areas	0213 0017
Clip on 45° mirror For inspections at hard to access points	0554 1320
Clip with magnet e.g. for quickly gathering small, loose metal parts in ducts, shafts etc.	0554 1321

Technical data

No. of pixels: 6,000
Field of view: 40°
Min. focus distance: 19 mm
Operating and storage temperature: -23 to +49°C
Shaft tip diameter: 10 mm
Max. bending radius: 203 mm
Light source: Halogen lamp (3200 K)
Housing: ABS (black)
Dimensions (handle): 152 x 36 x 62 mm
Weight: Approx. 227 g
Battery type: 2 AA

Warranty:

Excludes damage caused by misuse, accidents or modifications to the product. Warranty is void if the user opens the handle for any reason.

Important information:

- Never use on or near live parts
- Never use on or near live electrical circuits
- Never use in explosive atmospheres
- Not intended for medical or veterinary use
- Avoid over-bending the shaft
- Do not open the handle for any reason
- No user serviceable parts inside
- Do not submerse the handle in any liquid
- Do not immerse the shaft in any solvent for extended periods of time