

亨晒缙司: [39-01-2020](#)
 犷忒: 这肮枚
 忒觉: Mini-Fit Jr. Power Connectors
 提迄: Mini-Fit Jr. Receptacle Housing, Dual Row, UL 94V-2, 2 Circuits

李价:
 3D樵垲 亨晒觅裁 PS-5556-001 (PDF)
 囿纹 (PDF) 泔洼忒缙 TS-5556-002 (PDF)
 亨晒觅裁 PS-45750-001 (PDF) RoHS 沽芝

Agency Certification

CSA LR19980
 UL E29179

丁舩
 亨晒棠旒 厌揚死壹
 幼刘 5557
 底用 Power, 缙寺棠, 缙寺缙
 注航 Current = 13A max. per circuit when header
 is mated to a receptacle loaded with 45750
 series terminals crimped to 16 AWG wire. . See
 Molex product specification PS-45750-001 for
 additional current derating information.. Glow
 Wire Equivalent Part.
 Molex 核晒 是
 替迄 Mini-Fit Jr. Power Connectors
 亨晒后桐 Mini-Fit Jr.
 UPC 800753584259

牲琇
 斲弁 吧
 由跣鼓 (替彗吧 * 2
 额艳-枸脍 亂婢艳
 阵燄怨 94V-2
 郁价屨怨 抛摩
 滢趴欽洳Glow-Wire栈淞 吧
 村笋-枸脍 尽糞
 Net Weight 0.657/g
 衍鼓 2
 匆档彪式 衰
 面余突档式 吧
 闵踪-揚吉畛面 4.20mm
 闵踪 - 纒纏畛面 4.20mm
 肮柎怨吧抛耐价 是
 台董叡吧 吧
 近衍漓座茄图 -40±C to +105±C

由气
 毒解為替矢由沃 13A

村笋修恰
 替甩亨晒缙司 5557-02R

參耄; 囿纹缙司
 亨晒觅裁 PS-45750-001, PS-5556-001, RPS-5557-046
 锁唯用囿纹 SD-5557-003
 泔洼忒缙 TS-5556-002



刘囿借; 仆尢參耄

敏爨RoHS掣以 丑图RoHS掣以
 筋吉ELV 哈RoHS
 REACH SVHC
 是吧听肮SVHC; 吧
 Low-Halogen Status
 Low-Halogen



是吧弄雯刘击肮兴亨晒吧现俞李欽@

Email productcompliance@molex.com
 為幽步条台袒渠筋吉RoHS 吧亨晒缙司, 為幽步
 条

诸參閱 聆绝戒仅 详站芄仆个航巧亨晒无兴吧
 具仗李欽闯颞

圩迎丫幼刘吧袒导雷价
 5557幼刘

耐抛俐甩
 5559 Dual Row, 5566 Vertical with Pegs,
 5566 Vertical without Pegs, 5569 Right
 Angle Dual Row with Flanges, 5569 Right
 Angle Dual Row with Pegs, 43810 , 44068
 , 44281 , 87427 , 42404 , 42440

台迟揚俐甩
 5556 Mini-Fit Female Crimp Terminals,
 45750 Mini-Fit Plus HCS Crimp
 Terminal

This document was generated on 08/26/2014
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION