






Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT



Anforderungsstufe 1
Performance Level 1


Kontaktbereich vergoldet
Mating Area gold plating

Anschlussbereich verzinkt 4-6 µm
Terminal Area 4-6 µm tin plating


Koplanarität der Anschlüsse ≤ 0.1mm
Coplanarity Area of Termination ≤ 0.1 mm

Verpackt in Gurtverpackung
Verpackungseinheit: 280 Stück

- Tape on Reel Packaging
- Packaging unit: 280 pcs



Abspulrichtung - Reel off Direction



BA7-03 - Standard Bauhöhe

type7-03 - Standard Assembly Height

Information:				Tolerances		 All Dimensions in mm		Scale		3:1		Angaben zu entsprechender Ident-Nr. siehe Fertigungsunterlagen For further information about I.D. number see manufacturing document.			
Consider protection memo from DIN 34 All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.				Subject to modification without prior notice. Drawing will not be updated.				Designation							
								Messerl. SMC-Q 26-SMD-BA7-03 Male SMC-Q 26-SMD-type7-03							
				c		17.11.2005				www.ERNI.com		154785			
index		Date				H:00059745.SZA				SMC Q					

Consider protection memo from DIN 34