



ENGLISH

Datasheet

Stock No: 811-4340

RS Pro BASEC 2 Core Grey Unscreened 2182Y Solid PVC Power Cable H03VV-F, 0.75 mm² CSA 6 A, 300 V



NEW
LOWER
PRICE

Image representative of range

Product Details

BASEC approved H03VVF/2182Y 2 Core Cable

The 2182Y 2 core cable can be used with household applications in covered, dry, steamed and humid areas where low mechanical stress exists

Features and Benefits

- Flexible, 2 core cable with fine stranded copper conductors
- PVC sheath
- PVC insulation

Flexible PVC Cable

Specifications:

Number of Cores	2
Cross Sectional Area	0.75 mm ²
Sheath Colour	Grey
Current Rating	6 A
Voltage Rating	300 V
Outer Diameter	6.3mm
Sheath Material	Polyvinyl Chloride PVC
Harmonised Code	H03VV-F
Type	2182Y
Minimum Operating Temperature	-15°C
Maximum Operating Temperature	+70°C
Screened/Unscreened	Unscreened
Conductor Strand Type	Solid
Core Strands	24/0.2 mm
Insulation Material	PVC
Standards Met	BASEC
Conductor Resistance	26 Ω/km
Size of Strands	0.2 mm
Number of Strands	24
American Wire Gauge	18 AWG
Conductor Material	Copper