



Visual Signals XENON

BEACONS



Industrial Xenon / Audible Beacon > XA125 DIN Base Series

Product Overview

Suitable for light industrial applications, the XA125 has been designed to offer two warning signals in one unit. The beacon incorporates a Xenon tube producing 3 joules of flash energy and two piezo sounders located in the base of

the unit. The beacon has been designed to allow the customer to control either the visual of audible signal independently of each other. The audible options also offer a choice of either continuous tone or a pulsed one. A M12 sealing grommet in the base allows for cable entry and termination inside the enclosure.

Features

- Continuously rated
- Optional cage guard and mounting bracket options
- 360° visibility
- Combined audible & visual signal
- 3 point fix

Material

- UV Stable Polycarbonate Lens
- UV Stable ABS Plastic Base

Code No:	Voltage:	Light Source:	Current:
XA125-63	230v Ac ~	Xenon 3.0 J	120 mA •

- With both audible & visual signals operating at the same time



Kg 0.34

~ 50/60 **Hz**

°C -25+55

IP 65

FPM 60

dB 90

APPROVED AND CONFORMITIES



ADD THE FOLLOWING LENS CODES TO THE PRODUCT CODE WHEN ORDERING

01 02 03 04 05

INDUSTRIAL