

CAPACITANCE METER

Model : DM-9023

ISO-9001, CE, IEC1010



CAPACITANCE METER

Model : DM-9023

FEATURES	
* This Digital Capacitance Meter give a direct reading of capacitance on a 3 1/2 digits LCD display. Nine ranges give precision readings from 0.1 pF to 20,000 uF, which includes virtually all capacitors used in electronic engineering labs, production, service shops, and schools. It can be used to check tolerance, sort values, select precision values, measure unmarked capacitors, select matched sets, and measure cable, switch or PCB LAYOUT capacitance. Its battery operation, light weight, and small size make it a truly portable instrument.	
* Large LCD display, clear read-out even in bright conditions.	
* Low power consumption..	
* High accuracy in measuring	
* LSI-circuit use provides high reliability and durability.	
* Uses rotary ranges switch for easy operation.	
* Low battery voltage indicator.	
* Fast sampling rate.	

GENERAL SPECIFICATIONS	
Display	18 mm (0.7") LCD (Liquid Crystal Display), Max. indication 1999.
Range	9 Ranges with full scale values from 200 pF to 20,000 uF..
Overload Indication	Indication of " 1"
Zero adjust:	Front panel Adjustment control. This is limited to approx. 20 pF.
Out-of-Range indication	Indication of " 1" .
Sampling rate	0.5 second .
Operating Temperature	0 to 50 °C (32 to 122 °F).
Operating Humidity	Less than 80% RH.
Power Supply	DC 9V battery.
Battery Life	Approximately 200 hours on alkaline or 100 hours on carbon zinc battery with normal usage. (Typical consumption current 3 to 4 mA on 200 pF to 200 uF range).
Dimension	185 x 87 x 39 mm (7.3 x 3.4 x 1.5 inch).
Weight:	290 g/0.64 LB (including battery).

Standard Accessories	Test alligator clips (red & black 1 Pair. Spare Fuse (0.2A) 1 PC. Instruction Manual.....1 PC.
----------------------	--

ELEECTRICAL SPEECIFICATION					
Normal range	Max. In-range Display		Resolution		Test Frequency
200 pF	199.9	pF	0.1	pF	800 Hz
2 nF	1.999	nF	1	pF	800 Hz
20 nF	19.99	nF	10	pF	800 Hz
200 nF	199.9	nF	100	pF	800 Hz
2 uF	1.999	uF	1000	pF	800 Hz
20 uF	19.99	uF	0.01	uF	80 Hz
200 uF	199.9	uF	0.1	uF	8 Hz
2,000 uF	1,999	uF	1	uF	8 Hz
20,000 uF	19,990	uF	10	uF	8 Hz
pF = picofarad (10^{-12} Farad) nF = nanofarad (10^{-9} Farad) uF = microfarad (10^{-6} Farad)					
Accuracy (23± 5 °C)	* ± 1 % of full scale 1 d on 200 pF to 2000 uF ranges. * ± 1 % of full scale 1 d on 2,000 uF range. * ± 2 % of full scale 2 d on 20,000 uF ranges.				
Excitation Voltage	2.8 volts peak, maximum. POSITIVE input terminal's voltage is always higher than NEGATIVE terminal.				
Protection	The Meter is protected against damage from charged capacitors (more than DC 50 volt) by the fuse (0.2A).				