# AF265-40-11-13



## General Information

| | |
|---|---|
| **Extended Product Type:** | AF265-40-11-13 |
| **Product ID:** | 1SFL547102R1311 |
| **EAN:** | 7320500505120 |
| **Catalog Description:** | AF265-40-11-13 Contactor |

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

| | |
|---|---|
| **EAN:** | 7320500505120 |
| **Minimum Order Quantity:** | 1 piece |
| **Customs Tariff Number:** | 85364900 |

## Dimensions

| | |
|---|---|
| **Product Net Width:** | 184,4 mm |
| **Product Net Depth:** | 180 mm |
| **Product Net Height:** | 225,4 mm |
| **Product Net Weight:** | 5.55 kg |

## Container Information

| | |
|---|---|
| **Package Level 1 Units:** | 1 piece |
| **Package Level 1 Gross Weight:** | 6.38 kg |

## Environmental

| | |
|---|---|
| **Ambient Air Temperature:** | Close to Contactor Fitted with Thermal O/L Relay (0.85 - 1.1 Uc) -25...+50 °C<br>Close to Contactor without Thermal O/L Relay (0.85 - 1.1 Uc) -40...+70 °C<br>Close to Contactor for Storage -40...+70 °C |
| **Maximum Operating Altitude Permissible:** | 3000 m |

## Technical

| | |
|---|---|
| **Rated Operational Power AC-3 ($P_e$):** | (220 / 230 / 240V) 75 kW<br>(380 / 400V) 132 kW<br>(415V) 132 kW<br>(440V) 160 kW |
| **Rated Operational Current AC-1 ($I_e$):** | (690V) 40°C 400 A<br>(690V) 60°C 350 A<br>(690V) 70°C 290 A<br>(1000V) 40°C 350 A<br>(1000V) 60°C 300 A<br>(1000V) 70°C 240 A |
| **Number of Main Contacts NO:** | 4 |
| **Number of Main Contacts NC:** | 0 |
| **Number of Auxiliary Contacts NO:** | 1 |
| **Number of Auxiliary Contacts NC:** | 1 |
| **Rated Control Circuit Voltage ($U_c$):** | 50 Hz 100...250 V<br>60 Hz 100...250 V<br>DC Operation 100...250 V |
| **Coil Consumption:** | Pull-in at Max Rated Control Circuit Voltage 50Hz 385 V·A<br>Pull-in at Max Rated Control Circuit Voltage 60Hz 385 V·A<br>Holding at Max Rated Control Circuit Voltage 60Hz 17.5 V·A<br>Holding at Max Rated Control Circuit Voltage 50Hz 17.5 V·A<br>Holding at Max Rated Control Circuit Voltage DC 4.5 W<br>Pull-in at Max Rated Control Circuit Voltage DC 410 W |

## Technical UL/CSA

| | |
|---|---|
| **Maximum Operating Voltage UL/CSA:** | Main Circuit 600 V |