This is issued in strict confidence on condition that it is not used as a basis for manufacture or sale, and that it is not copied, reprinted or disclosed to a third party either wholly or in part without prior written consent of ITT Cannon.





A ± 0,38 (.015)	B ± 0,13 (.005)	C ± 0,13 (.005)	D ± 0,13 (.005)	E ± 0,38 (.015)	L ± 0,1 (.004)	W ± 0,25 (.012)	
53,04 (2.088)	38,38 (1.511)	47,04 (1.852)	7,90 (.311)	12,55 (.494)	0,9 (.035)	7.2 (.283)	

No mounting hardware selected

with 3,05 (.120) mounting hole



Signal contacts
not shown for clarity

Solder cup signal contacts



DESCRIPTION	MATERIAL	FINISH
Insulator	Polyester	None, (Color Dark Green)
Shells	Steel	Tin
Signal Contacts	Copper alloy	Gold over Ni in mating area, Tin on balance

Unless otherwise specified, dimensions are in mm & (in.)

Tolerances are (.XXX = mm)

Decimals	Angles
.X ± 0,20 (.008)	X° ± 1.0°
.XX ± 0,10 (.004)	
.XXX ± 0,05 (.002)	

Issue Date: 12-déc-07

Cannon | ITT Industries

CONNECTOR, RECEPTACLE, ELECTRICAL
D-SUBMINIATURE 25 POSITION SOLDER CUP

PART NO. **DB25SA197**