

DATA SHEET

For a complete data sheet, please also download:

- The IC04 LOCMOS HE4000B Logic Family Specifications HEF, HEC
- The IC04 LOCMOS HE4000B Logic Package Outlines/Information HEF, HEC

HEF40193B

MSI

4-bit up/down binary counter

Product specification
File under Integrated Circuits, IC04

January 1995

4-bit up/down binary counter



HEF40193B

MSI

DESCRIPTION

The HEF40193B is a 4-bit synchronous up/down binary counter. The counter has a count-up clock input (CP_U), a count-down clock input (CP_D), an asynchronous parallel load input ($\overline{\text{PL}}$), four parallel data inputs (P₀ to P₃), an asynchronous master reset input (MR), four counter outputs (O₀ to O₃), an active LOW terminal count-up (carry) output ($\overline{\text{TC}}_{\text{U}}$) and an active LOW terminal count-down (borrow) output ($\overline{\text{TC}}_{\text{D}}$).

The counter outputs change state on the LOW to HIGH transition of either clock input. However, for correct counting, both clock inputs cannot be LOW simultaneously. The outputs $\overline{\text{TC}}_{\text{U}}$ and $\overline{\text{TC}}_{\text{D}}$ are normally HIGH. When the circuit has reached the maximum count state of '15', the next HIGH to LOW transition of CP_U will cause $\overline{\text{TC}}_{\text{U}}$ to go LOW. $\overline{\text{TC}}_{\text{U}}$ will stay LOW until CP_U goes HIGH again. Likewise, output $\overline{\text{TC}}_{\text{D}}$ will go LOW when the circuit is in the zero state and CP_D goes LOW. When $\overline{\text{PL}}$ is LOW, the information on P₀ to P₃ is asynchronously loaded into the counter. A HIGH on MR resets the counter independent of all other input conditions. The counter stages are of a static toggle type flip-flop.



PINNING

- $\overline{\text{PL}}$ parallel load input (active LOW)
- P₀ to P₃ parallel data inputs
- CP_U count-up clock pulse input (LOW to HIGH, edge-triggered)
- CP_D count-down clock pulse input (LOW to HIGH, edge-triggered)
- MR master reset input (asynchronous)
- $\overline{\text{TC}}_{\text{U}}$ buffered terminal count-up (carry) output (active LOW)
- $\overline{\text{TC}}_{\text{D}}$ buffered terminal count-down (borrow) output (active LOW)
- O₀ to O₃ buffered counter outputs

- HEF40193BP(N): 16-lead DIL; plastic (SOT38-1)
- HEF40193BD(F): 16-lead DIL; ceramic (cerdip) (SOT74)
- HEF40193BT(D): 16-lead SO; plastic (SOT109-1)
- (): Package Designator North America

FAMILY DATA, I_{DD} LIMITS category MSI

See Family Specification

4-bit up/down binary counter

HEF40193B
MSI




Fig.3 Logic diagram (continued on Fig.4).

4-bit up/down binary counter


HEF40193B
MSI

Fig.4 Logic diagram (continued from Fig.3).

4-bit up/down binary counter


HEF40193B
MSI

FUNCTION TABLE

MR	$\overline{\text{PL}}$	CP_U	CP_D	MODE
H	X	X	X	reset (asyn.)
L	L	X	X	parallel load
L	H		H	count-up
L	H	H		count-down

Notes

1. H = HIGH state (the more positive voltage)
L = LOW state (the less positive voltage)
X = state is immaterial
-  = positive-going transition



Logic equations for terminal count:

$\overline{\text{TC}}_\text{U} = \overline{\text{O}}_0 \cdot \overline{\text{O}}_1 \cdot \overline{\text{O}}_2 \cdot \overline{\text{O}}_3 \cdot \overline{\text{CP}}_\text{U}$

$\overline{\text{TC}}_\text{D} = \overline{\text{O}}_0 \cdot \overline{\text{O}}_1 \cdot \overline{\text{O}}_2 \cdot \overline{\text{O}}_3 \cdot \overline{\text{CP}}_\text{D}$

AC CHARACTERISTICS

V_{SS} = 0 V; T_{amb} = 25 °C; input transition times ≤ 20 ns

	V _{DD} V	TYPICAL FORMULA FOR P (μW)	
Dynamic power dissipation per package (P)	5 10 15	600 f _i + Σ(f _o C _L) × V _{DD} ² 2700 f _i + Σ(f _o C _L) × V _{DD} ² 7500 f _i + Σ(f _o C _L) × V _{DD} ²	where f _i = input freq. (MHz) f _o = output freq. (MHz) C _L = load capacitance (pF) Σ (f _o C _L) = sum of outputs V _{DD} = supply voltage (V)

4-bit up/down binary counter

HEF40193B
MSI

AC CHARACTERISTICS

 $V_{SS} = 0$ V; $T_{amb} = 25$ °C; $C_L = 50$ pF; input transition times ≤ 20 ns

	V_{DD} V	SYMBOL	MIN.	TYP.	MAX.	TYPICAL EXTRAPOLATION FORMULA
Propagation delays						
$CP_U \rightarrow O_n$	5	t_{PHL}	210	415	ns	183 ns + (0,55 ns/pF) C_L
HIGH to LOW	10		85	165	ns	74 ns + (0,23 ns/pF) C_L
	15		60	120	ns	52 ns + (0,16 ns/pF) C_L
LOW to HIGH	5	t_{PLH}	170	340	ns	143 ns + (0,55 ns/pF) C_L
	10		70	140	ns	59 ns + (0,23 ns/pF) C_L
	15		50	100	ns	42 ns + (0,16 ns/pF) C_L
$CP_D \rightarrow O_n$	5	t_{PHL}	210	425	ns	183 ns + (0,55 ns/pF) C_L
HIGH to LOW	10		85	170	ns	74 ns + (0,23 ns/pF) C_L
	15		60	125	ns	57 ns + (0,16 ns/pF) C_L
LOW to HIGH	5	t_{PLH}	170	340	ns	143 ns + (0,55 ns/pF) C_L
	10		70	140	ns	59 ns + (0,23 ns/pF) C_L
	15		50	100	ns	42 ns + (0,16 ns/pF) C_L
$CP_U \rightarrow \overline{TC_U}$	5	t_{PHL}	125	250	ns	98 ns + (0,55 ns/pF) C_L
HIGH to LOW	10		50	100	ns	39 ns + (0,23 ns/pF) C_L
	15		35	70	ns	27 ns + (0,16 ns/pF) C_L
LOW to HIGH	5	t_{PLH}	95	185	ns	68 ns + (0,55 ns/pF) C_L
	10		40	80	ns	29 ns + (0,23 ns/pF) C_L
	15		30	60	ns	22 ns + (0,16 ns/pF) C_L
$CP_D \rightarrow \overline{TC_D}$	5	t_{PHL}	140	280	ns	113 ns + (0,55 ns/pF) C_L
HIGH to LOW	10		55	110	ns	44 ns + (0,23 ns/pF) C_L
	15		40	80	ns	32 ns + (0,16 ns/pF) C_L
LOW to HIGH	5	t_{PLH}	100	195	ns	73 ns + (0,55 ns/pF) C_L
	10		40	85	ns	29 ns + (0,23 ns/pF) C_L
	15		30	65	ns	22 ns + (0,16 ns/pF) C_L
$MR \rightarrow O_n$	5	t_{PHL}	195	390	ns	168 ns + (0,55 ns/pF) C_L
HIGH to LOW	10		80	160	ns	69 ns + (0,23 ns/pF) C_L
	15		60	120	ns	52 ns + (0,16 ns/pF) C_L
$MR \rightarrow \overline{TC_U}$	5	t_{PLH}	145	285	ns	118 ns + (0,55 ns/pF) C_L
LOW to HIGH	10		60	115	ns	49 ns + (0,23 ns/pF) C_L
	15		45	90	ns	37 ns + (0,16 ns/pF) C_L
$MR \rightarrow \overline{TC_D}$	5	t_{PHL}	365	730	ns	338 ns + (0,55 ns/pF) C_L
HIGH to LOW	10		130	265	ns	119 ns + (0,23 ns/pF) C_L
	15		100	205	ns	92 ns + (0,16 ns/pF) C_L
$\overline{PL} \rightarrow O_n$	5	t_{PHL}	185	360	ns	158 ns + (0,55 ns/pF) C_L
HIGH to LOW	10		75	150	ns	64 ns + (0,23 ns/pF) C_L
	15		55	110	ns	47 ns + (0,16 ns/pF) C_L

4-bit up/down binary counter

HEF40193B
MSI

	V _{DD} V	SYMBOL	MIN.	TYP.	MAX.	TYPICAL EXTRAPOLATION FORMULA
LOW to HIGH	5	t _{PLH}	145	290	ns	118 ns + (0,55 ns/pF) C _L
	10		60	120	ns	49 ns + (0,23 ns/pF) C _L
	15		45	90	ns	37 ns + (0,16 ns/pF) C _L

AC CHARACTERISTICS

V_{SS} = 0 V; T_{amb} = 25 °C; C_L = 50 pF; input transition times ≤ 20 ns

	V _{DD} V	SYMBOL	MIN.	TYP.	MAX.	TYPICAL EXTRAPOLATION FORMULA
Output transition times HIGH to LOW	5	t _{THL}	60	120	ns	10 ns + (1,0 ns/pF) C _L
	10		30	60	ns	9 ns + (0,42 ns/pF) C _L
	15		20	40	ns	6 ns + (0,28 ns/pF) C _L
	5	t _{TLH}	60	120	ns	10 ns + (1,0 ns/pF) C _L
	10		30	60	ns	9 ns + (0,42 ns/pF) C _L
	15		20	40	ns	6 ns + (0,28 ns/pF) C _L
Set-up time P _n → $\overline{\text{PL}}$	5	t _{su}	160	80	ns	see also waveforms Fig.6
	10		60	30	ns	
	15		50	25	ns	
Hold time P _n → $\overline{\text{PL}}$	5	t _{hold}	10	-70	ns	
	10		5	-25	ns	
	15		5	-20	ns	
Minimum CP _U or CP _D pulse width; LOW	5	t _{WCPL}	150	75	ns	
	10		50	25	ns	
	15		35	20	ns	
Minimum MR pulse width; HIGH	5	t _{WMRH}	180	90	ns	
	10		70	35	ns	
	15		60	30	ns	
Minimum $\overline{\text{PL}}$ pulse width; LOW	5	t _{WPLL}	120	60	ns	
	10		45	20	ns	
	15		30	15	ns	
Recovery time for MR	5	t _{RMR}	125	65	ns	
	10		70	35	ns	
	15		50	25	ns	
Recovery time for $\overline{\text{PL}}$	5	t _{RPL}	90	45	ns	
	10		35	15	ns	
	15		25	10	ns	
Maximum clock pulse frequency	5	f _{max}	2,5	5	MHz	
	10		7	14	MHz	
	15		9	18	MHz	

4-bit up/down binary counter


HEF40193B
MSI

Fig.6 Waveforms showing recovery times for $\overline{PL}$ and MR, minimum pulse widths for CP_U, CP_D, $\overline{PL}$ and MR, and set-up and hold times for P to $\overline{PL}$. Set-up times and hold times are shown as positive values but may be specified as negative values.

4-bit up/down binary counter

HEF40193B
MSI




Fig.7 Timing diagram.

APPLICATION INFORMATION

Some examples of applications for the HEF40193B are:

- Up/down difference counting
- Multistage ripple counting
- Multistage synchronous counting




Fig.8 Example of cascaded HEF40193B ICs.