

Euromas ABS / PC

Enclosure, ABS




T 240
Order no.: 03240000

Characteristics

Colour	light grey
Colour of enclosure group	Light grey, similar to RAL 7035; special colours on request
Protection class	IP 65
Enclosure material	ABS, PC (UV stabilised) and selected sizes in PC UL 94 V0 (additional UL 94 V0 versions on request), seal made of CR; for details see Technical Information
Scope of delivery	Lid and base, lid screws made of V2A, self-tapping screws for mounting bosses
Note	SV = version with quick-release fastener. IP = Ingress protection acc. to DIN EN 60529

Dimensions



A	250 mm
B	160 mm
C	90 mm
a1	243 mm
a2	224 mm
b1	153 mm
b2	115 mm
b3	134 mm
c1	15 mm
c2	84 mm

Important!

To compensate for pressure when temperatures change and cause moisture in the enclosure, we recommend that you use a [pressure compensation](#) element.

» [Additional information](#)

Technical documentation

Technical drawings Product drawing in DXF format:
[03240000 T 240.dxf](#) (741 KB)
3D product data in STEP format:
[03240000 T 240.stp](#) (751 KB)
Drawing for mechanical processing:
[03240000 T 240-G.dxf](#) (361 KB)
Product drawing in PDF format:
[03240000 T 240.pdf](#) (106 KB)

Works test certificates [670 WPZ-Euomas PC DE.pdf](#)(197 KB)
[670 WPZ-Euomas PC EN.pdf](#)(191 KB)

Technical information [M-V0-02-01 ENG.pdf](#) (55 KB)
[M-V0-02-01a.pdf](#) (55 KB)
[T-03-01 ENG.pdf](#) (54 KB)
[T-03-01a.pdf](#) (55 KB)
[M-02-02 EN 2012.pdf](#) (54 KB)

Material data » [Important information regarding the following material data](#)

Important information regarding the following material data:

Please note that the information in the material database is based on current knowledge. The tests on basic materials and dyestuffs were carried out and certified by the manufacturers of the material. Changes to the certified values and characteristics may occur during manufacture of the moulding compound and as a result of the addition of any dyestuffs. Any specific or tacit guarantee or warranty or assurance of characteristics or any other liability in connection with the use of the information contained in these certificates is excluded. The customer is not released from the obligation to check whether the materials used correspond to his conditions of use in accordance with the currently valid legal requirements.

×
 I have read and agreed to this information.

ABS MMIA Polyman
[Materialdatenblatt deutsch](#)
[Material datasheet english](#)
[UL-Karte/Card](#)
ABS Elix H605
[Materialdatenblatt deutsch](#)
[Material datasheet english](#)
[UL-Karte/Card](#)
ABS Cycolac GPM5500S
[Materialdatenblatt deutsch](#)
[Material datasheet english](#)
[UL-Karte/Card](#)

Downloads

Product brochure [Euomas ABS PC GB.pdf](#) (338 KB)

Suitable for the enclosure



Mounting panels, laminated paper

22000900

[M](#)

For EM/ET 239-241, M/T 240, M/T 241, M/T 250



Knurled screws

22003200

[RD](#)

For M/T 240-2401



Rubber feet, plug-in

22003300

[E](#)

For M/T 208-260



Wall brackets on rear, screw-on, polycarbonate

22004900

[WL](#)

For M/T 210-243, M/T 246-253



DIN rails DIN EN 60715 TH 15, galvanised steel

22002402

[TS 15](#)

For M/T 240-243, M/T 250



DIN rails DIN EN 60715 G 32, galvanised steel

22002300

[TS 32](#)

For M/T 240, M/T 241, M/T 250



DIN rails DIN EN 60715 TH 35, galvanised steel

22002310

[TS 35](#)

For M/T 240, M/T 241, M/T 250



Threaded inserts for mounting bosses

59002810 [DODGE M3x6,5](#) ND = 4.0 x 6.5
59002820 [DODGE M4x9,5](#) ND = 5.4 x 9.5



Screws (SHR) and distance bolts (DIBLZ) for mounting bosses in plastic enclosures

59006101 [SHR Z B4,5x7,8](#) SD = 4.5 / ND = 4.0 / KD = 7.5

* = Available on request