



PRODUCT DATA SHEET

RS stock nos: 227-0059

PLASTIC PADDING PRODUCT DATA SHEET

ULTIMA

1992

GENERAL DESCRIPTION:	Universal filler for all surfaces, steel, aluminium, galvanised/zinc, polycarbonate, glass fibre. Easy to apply, fast-setting and easy to sand. For panel and paintshop.
Setting Time:	~ 5 minutes 20° C
Tensile Strength:	~ 100 kg/cm ²
Heat Resistance:	Adhesion to mild steel 180° C Zinc coated/galvanised 110° C
Heat Conductivity:	< 0.1 Kcal/m.h.c
Electrical Conductivity:	10 ¹⁴ Ohm/cm ²
Chemical Resistance:	Water, oil, petrol, organic solvents, diluted acid and alkalis.
Density:	1.8 kg/dm ³
Colour:	Light beige
Storage Time:	1 year if stored below 20° C
Size Available:	955g, 3000g Cartridge.

HEALTH & SAFETY AT WORK ACT

Plastic Padding paste is based on a polyester resin, added to which there are a variety of mineral fillers. There is, however, no asbestos, asbestos substitute or quartz in Plastic Padding.

The Plastic Padding Hardener contains organic peroxide and plasticiser. In the event that the hardener has come into contact with eyes, wash with lukewarm water. It is further recommended that medical advice is sought. The dust which may be created when sanding down Plastic Padding is inert.

WARNING TEXT ON PACKAGING

Paste contains ca. 15% styrene. Flammable. Harmful by breathing. Irritating to eyes and skin. Use in well ventilated area. Keep out of reach of children.