# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(http://phoenixcontact.com/download)

Feed-through terminal block, Connection method: Push-in connection, Cross section: 0.14 mm² - 4 mm², AWG: 26 - 12, Width: 5.2 mm, Color: black, Mounting type: NS 35/7,5, NS 35/15

## Why buy this product

- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- The compact design and front connection enable wiring in a confined space
- In addition to the testing facility in the double function shaft, all terminal blocks provide an additional test connection

## Key commercial data

| | |
|---|---|
| Packing unit | 1 |
| GTIN | 4 046356 504089 |
| Custom tariff number | 85369010 |

## Technical data

### General

| | |
|---|---|
| Number of levels | 2 |
| Number of connections | 3 |
| Color | black |
| Insulating material | PA |
| Inflammability class according to UL 94 | V0 |
| Rated surge voltage | 8 kV |
| Surge voltage category | III |
| Insulating material group | I |
| Connection in acc. with standard | IEC 60947-7-1 |
| Maximum load current | 30 A (with 4 mm² conductor cross section) |
| Nominal current $I_N$ | 24 A |
| Nominal voltage $U_N$ | 800 V |

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Technical data

### General

| | |
|---|---|
| Maximum load current | 30 A (with 4 mm² conductor cross section) |
| Open side panel | ja |

### Dimensions

| | |
|---|---|
| Width | 5.2 mm |
| End cover width | 2.2 mm |
| Length | 60.5 mm |
| Height NS 35/7,5 | 36.5 mm |
| Height NS 35/15 | 44 mm |

### Connection data

| | |
|---|---|
| Connection in acc. with standard | IEC 60947-7-1 |
| Connection method | Push-in connection |
| Conductor cross section solid min. | 0.14 mm² |
| Conductor cross section solid max. | 4 mm² |
| Conductor cross section AWG/kcmil min. | 26 |
| Conductor cross section AWG/kcmil max | 12 |
| Conductor cross section stranded min. | 0.14 mm² |
| Conductor cross section stranded max. | 2.5 mm² |
| Min. AWG conductor cross section, stranded | 26 |
| Max. AWG conductor cross section, stranded | 14 |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.14 mm² |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 2.5 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve min. | 0.14 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve max. | 2.5 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm² |
| Minimum stripping length | 8 mm |
| Maximum stripping length | 10 mm |
| Internal cylindrical gage | A3 |

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 4.0 | 27141121 |
| eCl@ss 4.1 | 27141121 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Classifications

### ETIM

| | |
|---|---|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

### UNSPSC

| | |
|---|---|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

## Approvals

### Approvals

Approvals

CSA / UL Recognized / cUL Recognized / LR / GL / RS / ABS / VDE Zeichengenehmigung / IECEE CB Scheme / EAC / cULus Recognized

Ex Approvals

ATEX / IECEx / EAC Ex

Approvals submitted

### Approval details

CSA

| | B | C |
|---|---|---|
| mm²/AWG/kcmil | 26-12 | 26-12 |
| Nominal current IN | 20 A | 20 A |
| Nominal voltage UN | 600 V | 600 V |

UL Recognized

| | B | C |
|---|---|---|
| mm²/AWG/kcmil | 26-12 | 26-12 |

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Approvals

| | B | C |
|---|---|---|
| Nominal current IN | 20 A | 20 A |
| Nominal voltage UN | 600 V | 600 V |

cUL Recognized

| | B | C |
|---|---|---|
| mm²/AWG/kcmil | 26-12 | 26-12 |
| Nominal current IN | 20 A | 20 A |
| Nominal voltage UN | 600 V | 600 V |

LR

GL

RS

ABS

VDE Zeichengenehmigung

| | |
|---|---|
| mm²/AWG/kcmil | 0.2-4 |
| Nominal current IN | 24 A |
| Nominal voltage UN | 800 V |

IECEE CB Scheme

| | |
|---|---|
| mm²/AWG/kcmil | 0.2-4.0 |
| Nominal current IN | 24 A |
| Nominal voltage UN | 800 V |

EAC

cULus Recognized

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

### Accessories

### Documentation

Mounting material - PT-IL - 3208090

Operating decal for the push-in Technology

---

## End block

End clamp - CLIPFIX 35 - 3022218

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

---

End clamp - CLIPFIX 35-5 - 3022276

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

---

End clamp - E/NS 35 N - 0800886

End clamp, width: 9.5 mm, color: gray

---

## End cover

End cover - D-ST 2,5-TWIN - 3030488

End cover, Length: 60.5 mm, Width: 2.2 mm, Height: 29 mm, Color: gray

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

Cover segment - DS-ST 2,5 - 3036602

End cover segments, large segment: 32.25 x 13.83 x 0.9, small segment: 22.65 x 11.65 x 0.9, color: gray

End cover - D-ST 2,5-TWIN-0,8 OG - 3030512

End cover, Length: 60.5 mm, Width: 0.8 mm, Height: 29 mm, Color: orange

Spacer plate - DP PS-5 - 3036725

Spacer plate, Color: red

## Insulating sleeve

Insulating sleeve - MPS-IH WH - 0201663

Insulating sleeve, Color: white

Insulating sleeve - MPS-IH RD - 0201676

Insulating sleeve, Color: red

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

Insulating sleeve - MPS-IH BU - 0201689

Insulating sleeve, Color: blue

---

Insulating sleeve - MPS-IH YE - 0201692

Insulating sleeve, Color: yellow

---

Insulating sleeve - MPS-IH GN - 0201702

Insulating sleeve, Color: green

---

Insulating sleeve - MPS-IH GY - 0201728

Insulating sleeve, Color: gray

---

Insulating sleeve - MPS-IH BK - 0201731

Insulating sleeve, Color: black

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

Insulating sleeve - ISH 2,5/0,2 - 3002843

Insulating sleeve, Color: white

Insulating sleeve - ISH 2,5/0,5 - 3002856

Insulating sleeve, Color: gray

Insulating sleeve - ISH 2,5/1,0 - 3002869

Insulating sleeve, Color: black

## Jumper

Plug-in bridge - FBS 2-5 - 3030161

Plug-in bridge, Length: 22.7 mm, Width: 9 mm, Number of positions: 2, Color: red

Plug-in bridge - FBS 3-5 - 3030174

Plug-in bridge, Length: 22.7 mm, Width: 14.2 mm, Number of positions: 3, Color: red

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

Plug-in bridge - FBS 4-5 - 3030187

Plug-in bridge, Length: 22.7 mm, Width: 19.4 mm, Number of positions: 4, Color: red

---

Plug-in bridge - FBS 5-5 - 3030190

Plug-in bridge, Length: 22.7 mm, Width: 24.6 mm, Number of positions: 5, Color: red

---

Plug-in bridge - FBS 10-5 - 3030213

Plug-in bridge, Length: 22.7 mm, Width: 50.6 mm, Number of positions: 10, Color: red

---

Plug-in bridge - FBS 20-5 - 3030226

Plug-in bridge, Number of positions: 20, Color: red

---

Plug-in bridge - FBS 50-5 - 3038930

Plug-in bridge, Number of positions: 50, Color: red

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

Plug-in bridge - FBSR 2-5 - 3033702

Plug-in bridge, Number of positions: 2, Color: red

---

Plug-in bridge - FBSR 3-5 - 3001591

Plug-in bridge, Number of positions: 3, Color: red

---

Plug-in bridge - FBSR 4-5 - 3001592

Plug-in bridge, Number of positions: 4, Color: red

---

Plug-in bridge - FBSR 5-5 - 3001593

Plug-in bridge, Number of positions: 5, Color: red

---

Plug-in bridge - FBSR 10-5 - 3033710

Plug-in bridge, Number of positions: 10, Color: red

---

## Labeled terminal marker

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

### Zack marker strip - ZB 5 CUS - 0824962

Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.15 x 10.5 mm

---

### Zack marker strip - ZB 5,LGS:FORTL.ZAHLEN - 1050017

Zack marker strip, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.15 x 10.5 mm

---

### Zack marker strip - ZB 5,QR:FORTL.ZAHLEN - 1050020

Zack marker strip, Strip, white, labeled, can be labeled with: Plotter, Printed vertically: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.15 x 10.5 mm

---

### Zack marker strip - ZB 5,LGS:GLEICHE ZAHLEN - 1050033

Zack marker strip, Strip, white, labeled, can be labeled with: Plotter, Printed horizontally: Identical numbers 1 or 2, etc. up to 100, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.15 x 10.5 mm

---

### Marker for terminal blocks - ZB 5,LGS:L1-N,PE - 1050415

Marker for terminal blocks, Strip, white, labeled, Horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.15 x 10.5 mm

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

### Marker for terminal blocks - UC-TM 5 CUS - 0824581

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 10.5 x 4.6 mm

---

### Marker for terminal blocks - UCT-TM 5 CUS - 0829595

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, Lettering field: 4.6 x 10.5 mm

---

### Zack Marker strip, flat - ZBF 5 CUS - 0825025

Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.15 x 5.15 mm

---

### Zack Marker strip, flat - ZBF 5,LGS:FORTL.ZAHLEN - 0808671

Zack Marker strip, flat, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.15 x 5.15 mm

---

### Zack Marker strip, flat - ZBF 5,QR:FORTL.ZAHLEN - 0808697

Zack Marker strip, flat, Strip, white, labeled, Printed vertically: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 100, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.15 x 5.15 mm

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

### Zack Marker strip, flat - ZBF 5,LGS:GERADE ZAHLEN - 0810821

Zack Marker strip, flat, Strip, white, labeled, Printed horizontally: Consecutive numbers 2 - 20, 22 - 40, etc. up to 82 - 100, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.15 x 5.15 mm

---

### Zack Marker strip, flat - ZBF 5,LGS:UNGERADE ZAHLEN - 0810863

Zack Marker strip, flat, Strip, white, labeled, Printed horizontally: Odd numbers 1 - 19, 21 - 39, etc. up to 81 - 99, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.15 x 5.15 mm

---

### Marker for terminal blocks - UC-TMF 5 CUS - 0824638

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 5.2 mm, Lettering field: 4.6 x 5.1 mm

---

### Marker for terminal blocks - UCT-TMF 5 CUS - 0829658

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 5.2 mm, Lettering field: 4.4 x 4.7 mm

---

## Marker carriers

### Marker carriers - STP 5-2-ZB - 3037643

Double marker carrier, snaps onto the spring-cage terminal blocks ST 2.5..., labeled with ZB 5 or ZBF 5

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

Group marker label for terminal marking - GBS-ZB/26X6 - 0809298

Group marking label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with ESL 26x6 mm or EST 25x6 mm, in the foot part with Zack marker strip, length: 29 mm

---

## Mounting rail

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733

DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

---

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681

DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119

DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/ 7,5 WH UNPERF 2000MM - 1204122

DIN rail 35 mm (NS 35)

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704

DIN rail, unperforated, Width: 35 mm, Height: 7.5 mm, Length: 2000 mm, Color: silver

---

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421

DIN rail, material: Galvanized, perforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434

DIN rail, material: Galvanized, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM - 0801762

DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

End cap - NS 35/ 7,5 CAP - 1206560

DIN rail end piece, for DIN rail NS 35/7.5

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm

---

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714

DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail perforated - NS 35/15 WH PERF 2000MM - 0806602

DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/15 WH UNPERF 2000MM - 1204135

DIN rail 35 mm (NS 35)

---

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000 mm

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

DIN rail perforated - NS 35/15 ZN PERF 2000MM - 1206599

DIN rail, material: Galvanized, perforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/15 ZN UNPERF 2000MM - 1206586

DIN rail, material: Galvanized, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM - 1201895

DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m

---

End cap - NS 35/15 CAP - 1206573

DIN rail end piece, for DIN rail NS 35/15

---

DIN rail, unperforated - NS 35/15-2,3 UNPERF 2000MM - 1201798

DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

---

## Partition plate

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

Partition plate - ATP-ST-TWIN - 3030789

Partition plate, Length: 76.6 mm, Width: 2 mm, Height: 45 mm, Color: gray

## Planning and marking software

Software - CLIP-PROJECT ADVANCED - 5146040

Multilingual software for easy planning of Phoenix Contact on DIN rails together with the integrated TRABTECH-select software module for planning comprehensive surge protection concepts.

Software - CLIP-PROJECT PROFESSIONAL - 5146053

Multi-lingual software for terminal strip project planning. A marking module allows professional labeling of markers and labels for marking terminal blocks, conductors, cables and devices. The additionally integrated software module TRABTECH-select for planning comprehensive surge protection concepts.

## Reducing bridge

Reducing bridge - RB ST (2,5/4)-1,5 - 3038943

Reducing bridge, Length: 22.7 mm, Width: 10.4 mm, Number of positions: 2, Color: red

## Screwdriver tools

Screwdriver - SZF 1-0,6X3,5 - 1204517

Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

## Terminal marking

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

### Group marker label for terminal marking - GBS 5-25X12 - 0810588

Group marker label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with a 25 x 12 mm label or manually with the B-STIFT, in the foot part with ZB 5

---

### Zack marker strip - ZB 5 :UNBEDRUCKT - 1050004

Zack marker strip, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 5.1 x 10.5 mm

---

### Marker for terminal blocks - UC-TM 5 - 0818108

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK CLED, BLUEMARK LED, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 10.5 x 4.6 mm

---

### Marker for terminal blocks - UCT-TM 5 - 0828734

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Snap into tall marker groove, for terminal block width: 5.2 mm, Lettering field: 4.6 x 10.5 mm

---

### Zack Marker strip, flat - ZBF 5:UNBEDRUCKT - 0808642

Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into flat marker groove, for terminal block width: 5 mm, Lettering field: 5.1 x 5.2 mm

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

### Marker for terminal blocks - UC-TMF 5 - 0818153

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK CLED, BLUEMARK LED, Plotter, Mounting type: Snap into flat marker groove, for terminal block width: 5.2 mm, Lettering field: 4.6 x 5.1 mm

---

### Marker for terminal blocks - UCT-TMF 5 - 0828744

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Snap into flat marker groove, for terminal block width: 5.2 mm, Lettering field: 4.4 x 4.7 mm

---

## Test plug terminal block

### Test plugs - MPS-MT - 0201744

Test plugs, Color: silver

---

### Test adapter - PAI-4-FIX-5/6 BU - 3035975

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Blue

---

### Test adapter - PAI-4-FIX-5/6 OG - 3035974

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Orange

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

Test adapter - PAI-4-FIX-5/6 YE - 3035977

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Yellow

---

Test adapter - PAI-4-FIX-5/6 RD - 3035976

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Red

---

Test adapter - PAI-4-FIX-5/6 GN - 3035978

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Green

---

Test adapter - PAI-4-FIX-5/6 BK - 3035980

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Black

---

Test adapter - PAI-4-FIX-5/6 GY - 3035982

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Gray

---

# Feed-through terminal block - PT 2,5-TWIN BK - 3211252

## Accessories

### Test adapter - PAI-4-FIX-5/6 VT - 3035979

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Violet

---

### Test adapter - PAI-4-FIX-5/6 BN - 3035981

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Brown

---

### Test plugs - PS-5 - 3030983

Test plugs, Color: red

---

### Test plugs - PS-5/2,3MM RD - 3038723

Test plugs, Color: red

---

Phoenix Contact 2015 © - all rights reserved
http://www.phoenixcontact.com