

520 TVL Standard Camera

Art. no. TVCC20520

Page 1 of 2



- 520 TVL resolution
- 1/3" Sony Super HAD CCD
- Image optimisation with DSP technology
- Simple parameter setting with DIP switches and potentiometer
- Standard camera with compact housing design
- Integrated 230 V AC power supply unit

The Eyseo standard cameras come with various features at a very competitive price. They can be used with a plethora of lenses. This mid-range model is equipped with a 1/3" Sony Super HAD CCD. With 520 TV lines it delivers very detailed color images in high resolution with minimal image noise. Furthermore, the image sensor's high light sensitivity ensures excellent picture quality. The Eyseo standard series is compatible with C-Mount and CS-Mount lenses: with or without Auto-Iris function. A connector for a DC Auto-Iris plug is available. All models of the series feature AWB (Automatic White Balance), ELC (Electric Light Compensation), BLC (Back Light Compensation), and AGC (Automatic Gain Control) for optimizing image quality with backlight and other adverse lighting situations. Depending on the aperture, light-sensitivity is around 0.01 lux. Thus, the camera still delivers good images when the human eye cannot see anything anymore. This quality camera for video surveillance at the mid-range level operates on 230 V AC (for 12 V DC see the structurally identical TVCC20020). The camera also convinces with its low power consumption. Handy for installation: simple setup and configuration via easily accessible DIP switches.

520 TVL Standard Camera

Art. no. TVCC20520

Page 2 of 2

Technical Data:

Dimensions	(WxHxD) 55.5x40.5x99.0 mm
Connections	BNC, DC (5.5x2.1mm, 2-Pin)
Image sensor	1/3" Sony Super HAD CCD
Pixels (effective)	752(H) x 582(V) pixel
Pixels (total)	795(H) x 596(V) pixel
Aperture at minimum illumination (color)	1.0, 30
Width	56 mm
DSP	Nextchip
Electronic shutter	AES/AI
Backlight compensation	BLC
Height	41 mm
Camera outputs	1 x V s-s, 75 Ohm
Camera type	Standard camera
Length	99 mm
Max. operating temperature	50 °C
Max. humidity	85 %
Min. operating temperature	-10 °C
Minimum illumination (color)	0,01

Net weight	0.29 kg
Lens mount	CS/C
Lens control	DC
IP protection class	34
Signal-to-noise ratio	48
AC voltage supply	110-230 V
Control	DC
Power consumption	125 mA
TVL	520 TVL
Amplifier control	AGC, Off
Video output	FBAS (1 Vss, 75 Ohm)
Video system	PAL
White balance	AWB
Certifications	CE, UVV