

Datasheet

RS Pro 11 Way Commoning Block, Screw Down Termination, 10 to 2 AWG, 35 mm², 6 mm² CSA, Clear, 170A 450 V

RS Stock No: **388-2861**



Product Details

RS Pro 3-pole distribution block is compact and tough with PC construction. It allows the connection of one input to three outputs and guarantees a high standard of safety with a positive plug retention mechanism. The block has 3-receptacles and 1-plug with strain relief. The arm locking mechanism locks the plug and receptacle together when they are mounted. The base of this distribution block is equipped with two holes to allow mounting using M3.5 screws. This block comes with tin plated brass clamps for easy installation. It has a voltage rating of 250 V.

Features and Benefits

- 3 Receptacle + 1 plug with strain relief
- Arm lock mechanism locks the plug and receptacle together when they are mounted
- Made from PC: UL 94 - V0
- Colour: black
- Maximum operating temperature: 90°C
- Clamps: brass, tin plated
- Nominal section: 2.5 mm²
- Voltage rating of 250 V
- Base is equipped with two holes to allow mounting using M3.5 screws

**Specifications:**

Cable CSA	35 mm ² , 6 mm ²
Colour	Clear
Current Rating	170 A
Height	42 mm
Length	58 mm
Maximum Operating Temperature	+85°C
Number of Ways	11
Termination Method	Screw Down
Voltage Rating	450 V
Width	43 mm
Wire Size	10 to 2 AWG