

Type 2 surge arrester - BLT-T2-320-UT - 2906100

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Type 2 surge arrester for universal mounting in lights and cable connection boxes. Specifically for insulation class II with optical fault indication. Installation in branch or through wiring. Version: 230 V AC

Why buy this product

- L' signals the failure of the surge protective device due to disconnection of the power supply to the lights.
- Universal use for street, tunnel or object lighting
- Flexible installation
- Fixed via integrated elongated holes
- compact design
- Optical status indicator
- Stub or through-wiring connection
- Double or reinforced insulation



Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 055626 058078
Weight per Piece (excluding packing)	40.47 g
Custom tariff number	85363030
Country of origin	China

Technical data

Dimensions

Height	56 mm
Width	36.5 mm
Depth	34 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C

Type 2 surge arrester - BLT-T2-320-UT - 2906100

Technical data

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m (amsl (above mean sea level))
Permissible humidity (operation)	5 % ... 95 %

General

Standards/specifications	IEC 61643-11 2011
	EN 61643-11 2012
IEC test classification	II / III
	T2 / T3
	T3
EN type	T2 / T3
	T3
IEC power supply system	TT
Number of ports	One
SPD design	Voltage-limiting type
Mode of protection	L-N
Mounting type	4 mm screw
Color	traffic grey A RAL 7042
Housing material	PA 6.6
Pollution degree	2
Inflammability class according to UL 94	V-0
Protection class	II
Type	Installation module
Surge protection fault message	optical

Protective circuit

Nominal voltage U_N	100 V AC ... 277 V AC
Nominal frequency f_N	50 Hz (60 Hz)
Maximum continuous voltage U_C	320 V AC
Rated load current I_L	16 A
Nominal discharge current I_n (8/20) μ s	5 kA
Maximum discharge current I_{max} (8/20) μ s	10 kA
Short-circuit current rating I_{SCCR}	3 kA
Voltage protection level U_p	≤ 1.3 kV
Residual voltage U_{res}	≤ 1.3 kV (at I_n)
	≤ 1.3 kV (at U_{OC})
TOV behavior at U_T	400 V AC (5 s / withstand mode)
	528 V AC (120 min / safe failure mode)
Response time t_A	≤ 25 ns
Max. backup fuse with branch wiring	16 A AC (MCB B/C)
Max. backup fuse with V-type through wiring	16 A AC (MCB B/C)

Type 2 surge arrester - BLT-T2-320-UT - 2906100

Technical data

Connection data

Connection method	Screw terminal blocks
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
2 conductors with same cross section, stranded min.	0.2 mm ²
2 conductors with same cross section, stranded max.	1.5 mm ²
2 conductors with same cross section, solid min.	0.2 mm ²
2 conductors with same cross section, solid max.	1.5 mm ²
Screw thread	M3
Tightening torque	0.6 Nm

Classifications

eCl@ss

eCl@ss 5.1	27130801
eCl@ss 6.0	27130805

ETIM

ETIM 5.0	EC000941
----------	----------

Approvals

Approvals

Approvals

KEMA-KEUR

Ex Approvals

Approvals submitted


Approval details

KEMA-KEUR

Drawings

Type 2 surge arrester - BLT-T2-320-UT - 2906100

Circuit diagram



Dimensional drawing

