LIGHTS

2460 StealthLite Rechargeable LED

Save as PDF

Peli lights - Recoil torch - 2460 Recoil LED technology lights

The rechargeable version of the StealthLite 2410 LED. The StealthLite Rechargeable 2460 LED uses a long-life NiMH battery pack for extended burn time. It comes with a charger base unit that can be installed at home or work using the 220 V transformer, or in a vehicle through direct wiring or 12 V plug-in.

Black Yellow Submersible

Peli lights - Recoil torch - 2460 Recoil LED technology lights

ANSI FL1 Specifications

	High	
LIGHT SOURCE.	LED	
BATTERIES	4 AA NiMH (500 cycles) (Included)	
CHARGE TIME	NiMH Battery Pack 2-3 hrs.	
VOLTAGE	4.8	
LENGTH	17.8 cm (7")	
WEIGHT W/ BATTERIES	0.14 kg (4.8 oz.)	
WEIGHT W/O BATTERIES	0.12 kg (4.4 oz.)	

FL1 STANDARD	High	
LIGHT OUTPUT		
RUNTIME (hours/min)	4h 30m	
BEAM DISTANCE (meters)	153m	
PEAK BEAM INTENSITY (candela)	5828cd	
WATER RESISTANT		

Approvals

US FM C - Class I, Div. 2, Gp. ABCD T4A; Class II, Div. 2 Gp. FG

Materials

Body	Lens	Shroud	Switch Type
ABS Resin	Polycarbonate Resin	ABS	One-handed safety switch operation

Clip	Contact, Spring & Retainer	O-Ring	Night Vision Film
N/A	Stainless Steel and Phosphore Bronze	Ethylene Propylene	N/A

Configuration

Cat. #	Description

Peli lights - Recoil torch - 2460 Recoil LED technology lights Accessories

Cat. #	Description
700	Helmet Light Holder
750	Helmet Light Holder
770	Universal Helmet Light Holder
2469	NiMH Replacement Battery Pack
2458	220V Adapter NiMH
8056F	12V Plug-in for Fast Charger
6061F	Direct Wiring Rig for Fast Charger