

# Printed-circuit board connector - PTSM 0,5/ 3-HHI-2,5-THR WH R32 - 1814993


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Header, Nominal current: 6 A, Rated voltage (III/2): 250 V, Number of positions: 3, Pitch: 2.5 mm, Color: white, Contact surface: Tin, Mounting: Taped SMD/THT/THR components



## Key commercial data

Packing unit	500 pc
Minimum order quantity	500 pc
GTIN	 4 046356 761277
Weight per Piece (excluding packing)	1.6 g
Custom tariff number	85369010
Country of origin	Germany
Note	Made to Order (non-returnable)

## Technical data

### Dimensions

Pitch	2.5 mm
Dimension a	5 mm
Pin dimensions	0,6 x 0,4 mm
Hole diameter	1 mm

### General

Range of articles	PTSM 0,5/..-HHI-THR
Insulating material group	I
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/3)	160 V
Rated voltage (III/2)	250 V
Rated voltage (II/2)	400 V

# Printed-circuit board connector - PTSM 0,5/ 3-HHI-2,5-THR WH R32 - 1814993

## Technical data

### General

Nominal current I <sub>N</sub>	6 A
Maximum load current	6 A
Insulating material	PA
Inflammability class according to UL 94	V0
Color	white
Number of positions	3

## Classifications

### eCl@ss

eCl@ss 4.0	27141109
eCl@ss 4.1	27141109
eCl@ss 5.0	27141190
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101
eCl@ss 7.0	27440401
eCl@ss 8.0	27440402

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002637

### UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

## Approvals

### Approvals

---

#### Approvals

UL Recognized / EAC

---

#### Ex Approvals


---

# Printed-circuit board connector - PTSM 0,5/ 3-HHI-2,5-THR WH R32 - 1814993

## Approvals

Approvals submitted


## Approval details

UL Recognized 	
Nominal current I <sub>N</sub>	B 5 A
Nominal voltage U <sub>N</sub>	150 V

EAC
-----

## Drawings

Drilling diagram



Dimensioned drawing

