

Data Sheet

600 Watts Convection/Conduction Mounting

Total Power: 600 W
of Outputs: Single
Outputs: 28 V

Preliminary

SPECIAL FEATURES

- 600 W Full power at elevated temperatures
- Wide Operating Temperature Range (-40 to 85 °C Baseplate)
- Wide Output Adjust
- Remote Output On/Off
- AC_OK; DC_OK Signals
- 5V Standby Voltage
- Conduction-cooled
- I²C / PMBus
- Optional IP64 variant
- Optional 277 VAC input variant

COMPLIANCE

- EMI Class B
- EN61000 Immunity

SAFETY

- UL + CSA: 60950-1 2nd Ed. ANSI ES60601-1
- TUV: 60950-1 2nd Ed. 60601-1 3rd Ed.
- CB Scheme: IEC 60950-1 IEC 60601-1
- China CCC
- CE Mark



Electrical Specifications

Input	
Input range:	90 - 264 VAC ("U" Suffix) 180 - 305 VAC ("H" Suffix)
Frequency:	47 - 63 / 440 Hz
Input fusing:	Internal 12.5 A fuse on both L and N lines
Inrush current:	≤ 25 A peak
Power factor:	0.99 typical, meets EN61000-3-2
Harmonics:	Meets EN61000-3-2 Class B
Input current:	5.6 A @ 100 VAC typical
Hold up time:	20 ms min for Main Output (230 VAC)
Efficiency:	93.3% typical @ 230 VAC; 100% Load; 28 VDC
Leakage current:	< 400 uA @ 264 VAC / 60 Hz (U Suffix)
Isolation voltage:	PRI-SEC: 4,000 VAC, 2X MOPP PRI-Chassis: 1,500 VAC, 1X MOPP SEC-Chassis: 1,500 VAC, 1X MOPP
Auxilliary voltage:	5 VDC @ 1.5 A

Electrical Specifications

Output		
Output rating:	See Table 1	
Set point:	$\pm 0.5\%$	Factory set point
Total regulation:	Main Output: $\pm 2.0\%$ 5 Vsb: $\pm 5\%$	Combined Line / Load / Temperature
Rated load:	600 W maximum	From -40 to 85 °C Baseplate Temp / Derate TBD% up to 95 °C Baseplate Temp
Minimum load:	0 A	For both Main and 5 Vsb Outputs
Output voltage adjust range:	23.5 - 30.0 VDC	Maximum output power limited to 600 W. Output adjust range for other voltage variants are TBD.
Output noise:	Main Output: 1.0% max p-p 5 Vsb: 50 mV max p-p	Measured with 0.1 μ F Ceramic and 10 μ F Tantalum Cap, 20 MHz BW
Remote sense:	Compensation up to 500 mV	SK2 Pin 10: +Vout_RS / Pin4: -Vout_RS
Over current protection:	105 – 125%	Auto-recovery
Over voltage protection:	125 – 145% Vo, nom Main Output TBD 5Vsb	Latching / AC Recycle required for PSU restart
Over temperature protection:	> 95 °C Baseplate Temp	Output Shutdown / Auto-recovery
AC_OK	Open Collector; 0.7 VDC max / 10 mA	Active low when AC is present
DC_OK	Open Collector; 0.7 VDC max / 10 mA	Active low when Main Output is within regulation
Remote inhibit	Contact Closure	SK2 Pin 19: Open/Float = ON; Close/Ground = OFF
# Units in Parallel Operation:	TBD	SK2 Pin 5: IShare pin

Environmental Specifications

Operating temperature range:	-40 °C to +85 °C Baseplate Temperature
Storage temperature:	-40 °C to +85 °C
Humidity:	10% to 95%
Altitude:	Operating: 15,000 feet
Shock:	MIL-STD-810F 516.5 Procedure I, VI
Vibration:	MIL-STD-810F 514.5 Cat. 4, 10
Ingress Protection:	IP64 (for suffix "-4P")
MTBF (Calculated):	TBD

Ordering Information

Model Number*	Input	Vout	Output Current		Standby Output	Combined Line/ Load Regulation	Output Ripple
			Min	Max			
LCC600-28U-9P	90 - 264	28	0	21.4	5 V @ 1.5 A	2%	1%
LCC600-48U-9P	90 - 264	48	0	12.5	5 V @ 1.5 A	2%	1%
LCC600-36U-9P	90 - 264	36	0	16.7	5 V @ 1.5 A	2%	1%
LCC600-12U-9P	90 - 264	12	0	50.0	5 V @ 1.5 A	2%	1%


* Change "U" to "H" for 277 VAC input (180 - 305 VAC range)

* Change "9" to "4" for IP64 rated enclosure with fly leads


* Please contact factory for products' availability

Mechanical Drawings

-9P Suffix



-4P Suffix



Pin Assignment (INPUT)

Signals	Description	Notes
L	Live	Mating Connector: 350766-1 (Housing) 350536-1 (Contact Terminal)
N	Neutral	
G	Ground	

Pin Assignment (MAIN OUTPUT)

Signals	Description	Notes
+Vout	Positive Main Output	Terminal Block / M4 Screw / 12kgf-cm Torque / 14-22 AWG
+Vout		
+Vout		
-Vout	Return GND for -Vout Main Output	
-Vout		
-Vout		

Notes:

1) This is a preliminary datasheet subject to change.

Pin Assignment (SK2 – Signal & Control)

Signals	Description	Pin #
A2_Out	EEPROM Address	1
-VPROG	Return GND for ext voltage programming	2
A1_Out	EEPROM Address	3
-VOUT_RS	Remote Sense Return (Main O/P)	4
ISHARE	Load Share Voltage	5
A0_Out	EEPROM Address	6
SDA	Serial Data (I ² C)	7
+VPROG	Positive connection for ext voltage programming	8
SCL	Serial Clock Signal (I ² C)	9
+VOUT_RS	Remote Sense (Main O/P)	10
5VSB	5 V Standby Output	11
SGND	5 V Standby Return	12
5VSB	5 V Standby Output	13
G_DCOK_C	Global DC_OK Collector	14
WP	EEPROM Write Protect	15
G_DC_OK_E	Global DC_OK Emitter (GND)	16
SYS GND	Return GND for O/P Signal and I ² C Communication	17
G_AC_OK_C	Global AC_OK Collector	18
INH_EN#	Output Inhibit_Enable pin	19
G_AC_OK_E	Global AC_OK Emitter (GND)	20

SK2 Mating Connector: JST PN PHDR-20VS

Contact Pins: JST PN SPHD-001T-P0.5

WORLDWIDE OFFICES**Americas**

2900 S.Diablo Way
Tempe, AZ 85282
USA
+1 888 412 7832

Europe (UK)

Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX
United Kingdom
+44 (0) 1384 842 211

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
+852 2176 3333

ARTESYN
EMBEDDED TECHNOLOGIES

www.artesyn.com

While every precaution has been taken to ensure accuracy and completeness in this literature, Artesyn Embedded Technologies assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions. Artesyn Embedded Technologies, Artesyn and the Artesyn Embedded Technologies logo are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. © 2014 Artesyn Embedded Technologies, Inc.

For more information: www.artesyn.com/power
For support: productsupport.ep@artesyn.com