# Feed-through terminal block - PTU 4-TWIN BU - 3211860

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(http://phoenixcontact.com/download)

Feed-through terminal block, Connection type: Push-in connection, Screw connection, Cross section: 0.2 mm² - 6 mm², AWG :24- 12, Width: 6.2 mm, Color: blue, Mounting: NS 35/7,5, NS 35/15

## Why buy this product

- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- The compact design and front connection enable wiring in a confined space
- In addition to the testing facility in the double function shaft, all terminal blocks provide an additional test connection
- The Push-in TWIN connection is used inside the control cabinet and the universal screw connection is used on the end customer side

## Key commercial data

| | |
|---|---|
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| GTIN | 4 046356 802123 |
| Weight per Piece (excluding packing) | 3.34 g |
| Custom tariff number | 85369010 |
| Country of origin | Poland |
| Note | Made to Order (non-returnable) |

## Technical data

### General

| | |
|---|---|
| Number of levels | 1 |
| Number of connections | 3 |
| Color | blue |
| Insulating material | PA |
| Inflammability class according to UL 94 | V0 |
| Maximum load current | 32 A (with 6 mm² conductor cross section) |
| Rated surge voltage | 8 kV |
| Pollution degree | 3 |
| Surge voltage category | III |

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Technical data

### General

| | |
|---|---|
| Insulating material group | I |
| Connection in acc. with standard | IEC 60947-7-1 |
| Maximum load current | 38 A (the maximum load current must not be exceeded by the total current of all connected conductors) |
| Nominal current $I_N$ | 32 A |
| Nominal voltage $U_N$ | 800 V |
| Connection in acc. with standard | IEC 60947-7-1 |
| Maximum load current | 38 A (the maximum load current must not be exceeded by the total current of all connected conductors) |
| Nominal current $I_N$ | 32 A |
| Nominal voltage $U_N$ | 800 V |
| Open side panel | ja |

### Dimensions

| | |
|---|---|
| Width | 6.2 mm |
| End cover width | 2.2 mm |
| Length | 69.3 mm |
| Height NS 35/7,5 | 42.8 mm |
| Height NS 35/15 | 50.3 mm |

### Connection data

| | |
|---|---|
| Connection in acc. with standard | IEC 60947-7-1 |
| Connection method | Push-in connection |
| Conductor cross section solid min. | 0.2 mm² |
| Conductor cross section solid max. | 6 mm² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 10 |
| Conductor cross section stranded min. | 0.2 mm² |
| Conductor cross section stranded max. | 4 mm² |
| Min. AWG conductor cross section, stranded | 24 |
| Max. AWG conductor cross section, stranded | 12 |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.25 mm² |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 4 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve min. | 0.25 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve max. | 4 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 1 mm² |
| Minimum stripping length | 10 mm |
| Maximum stripping length | 12 mm |
| Internal cylindrical gage | A4 |

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Technical data

### Connection data

| | |
|---|---|
| Connection in acc. with standard | IEC 60947-7-1 |
| Connection method | Screw connection |
| Conductor cross section solid min. | 0.14 mm² |
| Conductor cross section solid max. | 6 mm² |
| Conductor cross section AWG/kcmil min. | 26 |
| Conductor cross section AWG/kcmil max | 10 |
| Conductor cross section stranded min. | 0.14 mm² |
| Conductor cross section stranded max. | 6 mm² |
| Min. AWG conductor cross section, stranded | 26 |
| Max. AWG conductor cross section, stranded | 12 |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.14 mm² |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 4 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve min. | 0.14 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve max. | 4 mm² |
| 2 conductors with same cross section, solid min. | 0.14 mm² |
| 2 conductors with same cross section, solid max. | 1.5 mm² |
| 2 conductors with same cross section, stranded min. | 0.14 mm² |
| 2 conductors with same cross section, stranded max. | 1.5 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 2.5 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. | 0.14 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. | 1.5 mm² |
| Minimum stripping length | 10 mm |
| Maximum stripping length | 12 mm |
| Screw thread | M3 |
| Tightening torque, min | 0.6 Nm |
| Tightening torque max | 0.8 Nm |

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 4.0 | 27141121 |
| eCl@ss 4.1 | 27141121 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |

### ETIM

| | |
|---|---|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

### UNSPSC

| | |
|---|---|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

## Approvals

### Approvals

Approvals

GL / LR / BV / UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approvals submitted

### Approval details

GL

LR

BV

UL Recognized

| | B | C |
|---|---|---|
| mm²/AWG/kcmil | 24-10 | 24-10 |

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Approvals

| | B | C |
|---|---|---|
| Nominal current IN | 30 A | 30 A |
| Nominal voltage UN | 600 V | 600 V |

cUL Recognized

| | B | C |
|---|---|---|
| mm²/AWG/kcmil | 24-10 | 24-10 |
| Nominal current IN | 30 A | 30 A |
| Nominal voltage UN | 600 V | 600 V |

EAC

cULus Recognized

## Accessories

### Accessories

### Documentation

Mounting material - PT-IL - 3208090

Operating decal for the push-in Technology

---

### End block

End clamp - CLIPFIX 35 - 3022218

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

End clamp - CLIPFIX 35-5 - 3022276

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

---

End clamp - E/NS 35 N - 0800886

End clamp, width: 9.5 mm, color: gray

---

## End cover

End cover - D-PTU 4-TWIN - 3211863

End cover, Length: 69.3 mm, Width: 2.2 mm

---

Spacer plate - DP PS-6 - 3036738

Spacer plate, Color: red

---

## Insulating sleeve

Insulating sleeve - MPS-IH WH - 0201663

Insulating sleeve, Color: white

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

Insulating sleeve - MPS-IH RD - 0201676

Insulating sleeve, Color: red

---

Insulating sleeve - MPS-IH BU - 0201689

Insulating sleeve, Color: blue

---

Insulating sleeve - MPS-IH YE - 0201692

Insulating sleeve, Color: yellow

---

Insulating sleeve - MPS-IH GN - 0201702

Insulating sleeve, Color: green

---

Insulating sleeve - MPS-IH GY - 0201728

Insulating sleeve, Color: gray

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

Insulating sleeve - MPS-IH BK - 0201731

Insulating sleeve, Color: black

---

Insulating sleeve - ISH 4/0,5 - 3002885

Insulating sleeve, Color: gray

---

Insulating sleeve - ISH 4/1,0 - 3002898

Insulating sleeve, Color: black

---

## Jumper

Plug-in bridge - FBS 2-6 - 3030336

Plug-in bridge, Length: 23 mm, Width: 10.7 mm, Number of positions: 2, Color: red

---

Plug-in bridge - FBS 3-6 - 3030242

Plug-in bridge, Length: 23 mm, Width: 16.9 mm, Number of positions: 3, Color: red

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

Plug-in bridge - FBS 4-6 - 3030255

Plug-in bridge, Length: 23 mm, Width: 23.1 mm, Number of positions: 4, Color: red

---

Plug-in bridge - FBS 5-6 - 3030349

Plug-in bridge, Length: 23 mm, Width: 29.3 mm, Number of positions: 5, Color: red

---

Plug-in bridge - FBS 10-6 - 3030271

Plug-in bridge, Length: 23 mm, Width: 60.3 mm, Number of positions: 10, Color: red

---

Plug-in bridge - FBS 20-6 - 3030365

Plug-in bridge, Length: 23 mm, Width: 122.3 mm, Number of positions: 20, Color: red

---

Plug-in bridge - FBSR 2-6 - 3033715

Plug-in bridge, Number of positions: 2, Color: red

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

Plug-in bridge - FBSR 3-6 - 3001594

Plug-in bridge, Number of positions: 3, Color: red

---

Plug-in bridge - FBSR 4-6 - 3001595

Plug-in bridge, Number of positions: 4, Color: red

---

Plug-in bridge - FBSR 5-6 - 3001596

Plug-in bridge, Number of positions: 5, Color: red

---

Plug-in bridge - FBSR 10-6 - 3033716

Plug-in bridge, Number of positions: 10, Color: red

---

## Labeled terminal marker

Zack marker strip - ZB 6 CUS - 0824992

Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 6.15 x 10.5 mm

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

### Zack marker strip - ZB 6,LGS:FORTL.ZAHLEN - 1051016

Zack marker strip, Strip, white, labeled, can be labeled with: Plotter, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 6.15 x 10.5 mm

---

### Zack marker strip - ZB 6,QR:FORTL.ZAHLEN - 1051029

Zack marker strip, Strip, white, labeled, can be labeled with: Plotter, Printed vertically: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 6.15 x 10.5 mm

---

### Zack marker strip - ZB 6,LGS:GLEICHE ZAHLEN - 1051032

Zack marker strip, Strip, white, labeled, can be labeled with: Plotter, Printed horizontally: Identical numbers 1 or 2, etc. up to 100, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 6.15 x 10.5 mm

---

### Marker for terminal blocks - ZB 6,LGS:L1-N,PE - 1051414

Marker for terminal blocks, Strip, white, labeled, can be labeled with: Plotter, Horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 6.15 x 10.5 mm

---

### Marker for terminal blocks - ZB 6,LGS:U-N - 1051430

Marker for terminal blocks, Strip, white, labeled, can be labeled with: Plotter, Printed horizontally: U, V, W, N, GND, U, V, W, N, GND, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 6.15 x 10.5 mm

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

Marker for terminal blocks - UC-TM 6 CUS - 0824589

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 5.6 x 10.5 mm

---

Marker for terminal blocks - UCT-TM 6 CUS - 0829602

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 5.6 x 10.5 mm

---

Zack Marker strip, flat - ZBF 6 CUS - 0825027

Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 5.15 x 6.15 mm

---

Marker for terminal blocks - UC-TMF 6 CUS - 0824646

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 5.6 x 5.1 mm

---

Marker for terminal blocks - UCT-TMF 6 CUS - 0829665

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 5.4 x 4.7 mm

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

### Zack Marker strip, flat - ZBF 6,LGS:FORTL.ZAHLEN - 0808749

Zack Marker strip, flat, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 100, Mounting type: Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 5.15 x 6.15 mm

---

### Zack Marker strip, flat - ZBF 6,QR:FORTL.ZAHLEN - 0808765

Zack Marker strip, flat, Strip, white, labeled, Printed vertically: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 100, Mounting type: Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 5.15 x 6.15 mm

---

### Zack Marker strip, flat - ZBF 6,LGS:GERADE ZAHLEN - 0810834

Zack Marker strip, flat, Strip, white, labeled, Printed horizontally: Consecutive numbers 2 - 20, 22 - 40, etc. up to 82 - 100, Mounting type: Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 5.15 x 6.15 mm

---

### Zack Marker strip, flat - ZBF 6,LGS:UNGERADE ZAHLEN - 0810876

Zack Marker strip, flat, Strip, white, labeled, Printed horizontally: Odd numbers 1 - 19, 21 - 39, etc. up to 81 - 99, Mounting type: Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 5.15 x 6.15 mm

---

### Marker for terminal blocks - TMT 6 R CUS - 0824488

Marker for terminal blocks, can be ordered: By line, white, labeled according to customer specifications, Mounting type: Snap into universal marker groove, Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 6.35 x 6.15 mm

---

## Marker carriers

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

### Group marker label for terminal marking - GBS-ZB/26X6 - 0809298

Group marking label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with ESL 26x6 mm or EST 25x6 mm, in the foot part with Zack marker strip, length: 29 mm

---

### Marker carriers - CARRIER-TM 300 - 0828282

Marker carriers, gray, unlabeled, Mounting type: Snap into flat marker groove, Lettering field: 10.5 x 300 mm

---

## Mounting rail

### DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733

DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

---

### DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681

DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

### DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119

DIN rail 35 mm (NS 35)

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

DIN rail - NS 35/ 7,5 WH UNPERF 2000MM - 1204122

DIN rail 35 mm (NS 35)

---

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704

DIN rail, unperforated, Width: 35 mm, Height: 7.5 mm, Length: 2000 mm, Color: silver

---

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421

DIN rail, material: Galvanized, perforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434

DIN rail, material: Galvanized, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM - 0801762

DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

End cap - NS 35/ 7,5 CAP - 1206560

DIN rail end piece, for DIN rail NS 35/7.5

---

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm

---

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714

DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail perforated - NS 35/15 WH PERF 2000MM - 0806602

DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/15 WH UNPERF 2000MM - 1204135

DIN rail 35 mm (NS 35)

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000 mm

---

DIN rail perforated - NS 35/15 ZN PERF 2000MM - 1206599

DIN rail, material: Galvanized, perforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/15 ZN UNPERF 2000MM - 1206586

DIN rail, material: Galvanized, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM - 1201895

DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m

---

End cap - NS 35/15 CAP - 1206573

DIN rail end piece, for DIN rail NS 35/15

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

DIN rail, unperforated - NS 35/15-2,3 UNPERF 2000MM - 1201798

DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

---

## Planning and marking software

Software - CLIP-PROJECT ADVANCED - 5146040

Multilingual software for easy planning of Phoenix Contact on DIN rails together with the integrated TRABTECH-select software module for planning comprehensive surge protection concepts.

---

Software - CLIP-PROJECT PROFESSIONAL - 5146053

Multi-lingual software for terminal strip project planning. A marking module allows professional labeling of markers and labels for marking terminal blocks, conductors, cables and devices. The additionally integrated software module TRABTECH-select for planning comprehensive surge protection concepts.

---

## Reducing bridge

Reducing bridge - RB ST (2,5/4)-1,5/S - 3214356

Reducing bridge, Number of positions: 2, Color: red

---

## Screwdriver tools

Screwdriver - SZF 1-0,6X3,5 - 1204517

Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

---

## Terminal marking

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

### Group marker label for terminal marking - GBS 5-25X12 - 0810588

Group marker label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with a 25 x 12 mm label or manually with the B-STIFT, in the foot part with ZB 5

### Zack marker strip - ZB 6:UNBEDRUCKT - 1051003

Zack marker strip, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 6.15 x 10.5 mm

### Marker for terminal blocks - UC-TM 6 - 0818085

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK CLED, BLUEMARK LED, Plotter, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 5.6 x 10.5 mm

### Marker for terminal blocks - UCT-TM 6 - 0828736

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Snap into tall marker groove, for terminal block width: 6.2 mm, Lettering field: 5.6 x 10.5 mm

### Zack Marker strip, flat - ZBF 6:UNBEDRUCKT - 0808710

Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 5.15 x 6.15 mm

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

Marker for terminal blocks - UC-TMF 6 - 0818140

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK CLED, BLUEMARK LED, Plotter, Mounting type: Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 5.6 x 5.1 mm

---

Marker for terminal blocks - UCT-TMF 6 - 0828746

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 5.4 x 4.7 mm

---

Marker for terminal blocks - TMT 6 R - 0816498

Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X, THERMOMARK S1.1, Perforated, Mounting type: Snap into universal marker groove, Snap into flat marker groove, for terminal block width: 6.2 mm, Lettering field: 6.35 x 6.15 mm

---

Marker for terminal blocks - TMT (EX9,5)R - 0828295

Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X, THERMOMARK S1.1, Mounting type: Snap into universal marker groove, Snap into tall marker groove, Lettering field: 9.5 x 50000 mm

---

## Test plug terminal block

Test plugs - MPS-MT - 0201744

Test plugs, Color: silver

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

Test adapter - PAI-4-FIX-5/6 BU - 3035975

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Blue

---

Test adapter - PAI-4-FIX-5/6 OG - 3035974

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Orange

---

Test adapter - PAI-4-FIX-5/6 YE - 3035977

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Yellow

---

Test adapter - PAI-4-FIX-5/6 RD - 3035976

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Red

---

Test adapter - PAI-4-FIX-5/6 GN - 3035978

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Green

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

Test adapter - PAI-4-FIX-5/6 BK - 3035980

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Black

---

Test adapter - PAI-4-FIX-5/6 GY - 3035982

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Gray

---

Test adapter - PAI-4-FIX-5/6 VT - 3035979

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Violet

---

Test adapter - PAI-4-FIX-5/6 BN - 3035981

Test adapter, for 4 mm Ø safety test plugs, latches into the bridge shaft; color: Brown

---

Test plugs - PS-6 - 3030996

Test plugs, Color: red

---

# Feed-through terminal block - PTU 4-TWIN BU - 3211860

## Accessories

Test plugs - PS-6/2,3MM RD - 3038736

Test plugs, Color: red

## Drawings

Circuit diagram



Phoenix Contact 2015 © - all rights reserved
http://www.phoenixcontact.com