# Feed-through terminal block - PT 1,5/S/2P - 3213784

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(http://phoenixcontact.com/download)

Feed-through terminal block, Connection method: Push-in / plug connection, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

## Why buy this product

- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- The compact design and front connection enable wiring in a confined space
- In addition to the testing facility in the double function shaft, all terminal blocks provide an additional test connection
- Tested for railway applications

## Key commercial data

| | |
|---|---|
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| GTIN | 4 046356 575690 |
| Weight per Piece (excluding packing) | 2.93 g |
| Custom tariff number | 85366990 |
| Country of origin | Poland |
| Note | Made to Order (non-returnable) |

## Technical data

### General

| | |
|---|---|
| Number of levels | 1 |
| Number of connections | 2 |
| Color | gray |
| Insulating material | PA |
| Inflammability class according to UL 94 | V0 |
| Area of application | Railway industry |
| | Mechanical engineering |
| | Plant engineering |
| Maximum load current | 17.5 A (with 1.5 mm² conductor cross section) |

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Technical data

### General

| | |
|---|---|
| Rated surge voltage | 6 kV |
| Pollution degree | 3 |
| Surge voltage category | III |
| Insulating material group | I |
| Connection in acc. with standard | IEC 61984 |
| Maximum load current | 17.5 A (with 1.5 mm² conductor cross section) |
| Nominal current $I_N$ | 17.5 A (observe derating) |
| Nominal voltage $U_N$ | 500 V |
| Maximum load current | 17.5 A (with 1.5 mm² conductor cross section) |
| Open side panel | ja |
| Insertion/withdrawal cycles mechanical | 100 |
| Tight fit on carrier | NS 35 |
| Setpoint | 1 N |
| Result of tight fit test | Test passed |
| Proof of thermal characteristics (needle flame) effective duration | 30 s |
| Result of thermal test | Test passed |
| Test specification, oscillation, broadband noise | DIN EN 50155 (VDE 0115-200):2008-03 |
| Test spectrum | Service life test category 1, class B, body mounted |
| Test frequency | $f_1$ = 5 Hz to $f_2$ = 150 Hz |
| ASD level | 1.857 $(m/s^2)^2$/Hz |
| Acceleration | 0.8g |
| Test duration per axis | 5 h |
| Test directions | X-, Y- and Z-axis |
| Oscillation, broadband noise test result | Test passed |
| Test specification, shock test | DIN EN 50155 (VDE 0115-200):2008-03 |
| Shock form | Half-sine |
| Acceleration | 5 g |
| Shock duration | 30 ms |
| Number of shocks per direction | 3 |
| Test directions | X-, Y- and Z-axis (pos. and neg.) |
| Shock test result | Test passed |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C |
| Static insulating material application in cold | -60 °C |

### Dimensions

| | |
|---|---|
| Width | 3.5 mm |
| End cover width | 2.2 mm |
| Length | 45.8 mm |
| Height NS 35/7,5 | 32 mm |
| Height NS 35/15 | 39.5 mm |

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Technical data

### Connection data

| | |
|---|---|
| Connection in acc. with standard | IEC 61984 |
| Connection method | Push-in / plug connection |
| Conductor cross section solid min. | 0.14 mm² |
| Conductor cross section solid max. | 1.5 mm² |
| Conductor cross section AWG/kcmil min. | 26 |
| Conductor cross section AWG/kcmil max | 14 |
| Conductor cross section stranded min. | 0.14 mm² |
| Conductor cross section stranded max. | 1.5 mm² |
| Min. AWG conductor cross section, stranded | 26 |
| Max. AWG conductor cross section, stranded | 14 |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.14 mm² |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 1.5 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve min. | 0.14 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve max. | 1 mm² |
| Internal cylindrical gage | A1 / B1 |

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 4.0 | 27141124 |
| eCl@ss 4.1 | 27141124 |
| eCl@ss 5.0 | 27141124 |
| eCl@ss 5.1 | 27141124 |
| eCl@ss 6.0 | 27141124 |
| eCl@ss 7.0 | 27141124 |
| eCl@ss 8.0 | 27141120 |

### ETIM

| | |
|---|---|
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

### UNSPSC

| | |
|---|---|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

## Approvals

### Approvals

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Approvals

Approvals

VDE Gutachten mit Fertigungsüberwachung / IECEE CB Scheme / UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approvals submitted

## Approval details

VDE Gutachten mit Fertigungsüberwachung

| | |
|---|---|
| Nominal current IN | 14.1 A |
| Nominal voltage UN | 500 V |

IECEE CB Scheme

| | |
|---|---|
| Nominal current IN | 14.1 A |
| Nominal voltage UN | 500 V |

UL Recognized

| | B | C | D |
|---|---|---|---|
| Nominal current IN | 15 A | 15 A | 5 A |
| Nominal voltage UN | 300 V | 300 V | 600 V |

cUL Recognized

| | B | C | D |
|---|---|---|---|
| Nominal current IN | 15 A | 15 A | 5 A |
| Nominal voltage UN | 300 V | 300 V | 600 V |

EAC

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Approvals

cULus Recognized

## Accessories

### Accessories

### Coding element

Coding star - PC - 3040588

Coding star, Length: 3 mm, Width: 3 mm, Height: 6 mm, Color: red

### Documentation

Mounting material - PT-IL - 3208090

Operating decal for the push-in Technology

### End block

End clamp - E/UK - 1201442

End clamp, for assembly on NS 32 or NS 35/7.5 DIN rail

End clamp - E/UK 1 - 1201413

End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

End clamp - CLIPFIX 35 - 3022218

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

---

End clamp - CLIPFIX 35-5 - 3022276

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

---

End clamp - E/NS 35 N - 0800886

End clamp, width: 9.5 mm, color: gray

---

## End cover

End cover - D-PT 1,5/S - 3208142

End cover, Length: 45 mm, Width: 2.2 mm, Height: 24.3 mm, Color: gray

---

## Jumper

Plug-in bridge - FBS 2-3,5 - 3213014

Plug-in bridge, Number of positions: 2, Color: red

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

Plug-in bridge - FBS 3-3,5 - 3213027

Plug-in bridge, Number of positions: 3, Color: red

---

Plug-in bridge - FBS 4-3,5 - 3213030

Plug-in bridge, Number of positions: 4, Color: red

---

Plug-in bridge - FBS 5-3,5 - 3213043

Plug-in bridge, Number of positions: 5, Color: red

---

Plug-in bridge - FBS 10-3,5 - 3213056

Plug-in bridge, Number of positions: 10, Color: red

---

Plug-in bridge - FBS 20-3,5 - 3213069

Plug-in bridge, Number of positions: 20, Color: red

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

Plug-in bridge - FBS 2-3,5 BU - 3213086

Plug-in bridge, Number of positions: 2, Color: blue

---

Plug-in bridge - FBS 3-3,5 BU - 3213099

Plug-in bridge, Number of positions: 3, Color: blue

---

Plug-in bridge - FBS 4-3,5 BU - 3213109

Plug-in bridge, Number of positions: 4, Color: blue

---

Plug-in bridge - FBS 5-3,5 BU - 3213112

Plug-in bridge, Number of positions: 5, Color: blue

---

Plug-in bridge - FBS 10-3,5 BU - 3213125

Plug-in bridge, Number of positions: 10, Color: blue

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

### Plug-in bridge - FBS 20-3,5 BU - 3213138

Plug-in bridge, Number of positions: 20, Color: blue

---

## Labeled terminal marker

### Zack marker strip - ZB 3,5 CUS - 0829415

Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, for terminal block width: 3.5 mm, Lettering field: 3.5 x 10.5 mm

---

### Zack marker strip - ZB 3,5,LGS:FORTL.ZAHLEN - 0801404

Zack marker strip, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 100, Mounting type: Snap into tall marker groove, for terminal block width: 3.5 mm, Lettering field: 3.5 x 10.5 mm

---

### Zack marker strip - ZB 3,5,QR:FORT.ZAHLEN - 0801405

Zack marker strip, Strip, white, labeled, Printed vertically: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 100, Mounting type: Snap into tall marker groove, for terminal block width: 3.5 mm, Lettering field: 3.5 x 10.5 mm

---

### Marker for terminal blocks - UCT-TM 3,5 CUS - 0829581

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into tall marker groove, for terminal block width: 3.5 mm, Lettering field: 2.95 x 10.5 mm

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

### Zack Marker strip, flat - ZBF 3,5 CUS - 0829394

Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 3.5 mm, Lettering field: 3.5 x 5.2 mm

---

### Zack Marker strip, flat - ZBF 3,5,LGS:FORTL.ZAHLEN - 0801406

Zack Marker strip, flat, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 100, Mounting type: Snap into flat marker groove, for terminal block width: 3.5 mm, Lettering field: 5.15 x 3.5 mm

---

### Zack Marker strip, flat - ZBF 3,5,QR:FORTL.ZAHLEN - 0801407

Zack Marker strip, flat, Strip, white, labeled, Printed vertically: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 100, Mounting type: Snap into flat marker groove, for terminal block width: 3.5 mm, Lettering field: 5.15 x 3.5 mm

---

### Marker for terminal blocks - UCT-TMF 3,5 CUS - 0829644

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 3.5 mm, Lettering field: 2.7 x 4.7 mm

---

## Marker carriers

### Group marker label for terminal marking - GBS-ZB/26X6 - 0809298

Group marking label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with ESL 26x6 mm or EST 25x6 mm, in the foot part with Zack marker strip, length: 29 mm

---

## Mounting rail

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733

DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

---

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681

DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119

DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/ 7,5 WH UNPERF 2000MM - 1204122

DIN rail 35 mm (NS 35)

---

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704

DIN rail, unperforated, Width: 35 mm, Height: 7.5 mm, Length: 2000 mm, Color: silver

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421

DIN rail, material: Galvanized, perforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434

DIN rail, material: Galvanized, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM - 0801762

DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

End cap - NS 35/ 7,5 CAP - 1206560

DIN rail end piece, for DIN rail NS 35/7.5

---

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714

DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail perforated - NS 35/15 WH PERF 2000MM - 0806602

DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/15 WH UNPERF 2000MM - 1204135

DIN rail 35 mm (NS 35)

---

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000 mm

---

DIN rail perforated - NS 35/15 ZN PERF 2000MM - 1206599

DIN rail, material: Galvanized, perforated, height 15 mm, width 35 mm, length: 2 m

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

DIN rail, unperforated - NS 35/15 ZN UNPERF 2000MM - 1206586

DIN rail, material: Galvanized, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM - 1201895

DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m

---

End cap - NS 35/15 CAP - 1206573

DIN rail end piece, for DIN rail NS 35/15

---

DIN rail, unperforated - NS 35/15-2,3 UNPERF 2000MM - 1201798

DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

---

## Partition plate

Partition plate - ATP-ST 4 - 3030721

Partition plate, Length: 61 mm, Width: 2 mm, Height: 42 mm, Color: gray

---

## Planning and marking software

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

### Software - CLIP-PROJECT ADVANCED - 5146040

Multilingual software for easy planning of Phoenix Contact on DIN rails together with the integrated TRABTECH-select software module for planning comprehensive surge protection concepts.

---

### Software - CLIP-PROJECT PROFESSIONAL - 5146053

Multi-lingual software for terminal strip project planning. A marking module allows professional labeling of markers and labels for marking terminal blocks, conductors, cables and devices. The additionally integrated software module TRABTECH-select for planning comprehensive surge protection concepts.

---

## Reducing bridge

### Reducing bridge - RB ST 6-1,5/S - 3213250

Reducing bridge, Number of positions: 2, Color: red

---

### Reducing bridge - RB ST 6-1,5/S - 3213250

Reducing bridge, Number of positions: 2, Color: red

---

## Screwdriver tools

### Screwdriver - SZF 0-0,4X2,5 - 1204504

Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.4 x 2.5 x 75 mm, 2-component grip, with non-slip grip

---

## Terminal marking

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

### Zack marker strip - ZB 3,5:UNBEDRUCKT - 0829414

Zack marker strip, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into tall marker groove, for terminal block width: 3.5 mm, Lettering field: 3.5 x 10.5 mm

---

### Marker for terminal blocks - UCT-TM 3,5 - 0829484

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Snap into tall marker groove, for terminal block width: 3.5 mm, Lettering field: 2.95 x 10.5 mm

---

### Zack Marker strip, flat - ZBF 3,5:UNBEDRUCKT - 0829392

Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into flat marker groove, for terminal block width: 3.5 mm, Lettering field: 3.5 x 5.2 mm

---

### Marker for terminal blocks - UCT-TMF 3,5 - 0829486

Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Snap into flat marker groove, for terminal block width: 3.5 mm, Lettering field: 2.7 x 4.7 mm

---

### Marker for terminal blocks - TMT (EX9,5)R - 0828295

Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X, THERMOMARK S1.1, Mounting type: Snap into universal marker groove, Snap into tall marker groove, Lettering field: 9.5 x 50000 mm

---

## Additional products

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

### Plug - PP-H 1,5/S/1 - 3212484

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: gray

### Plug - PP-H 1,5/S/1 BU - 3212497

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: blue

### Plug - PP-H 1,5/S/1 GNYE - 3212507

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: green-yellow

### Plug - PP-H 1,5/S/2 - 3212510

Plug, Connection method: Push-in connection, Number of positions: 2, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 7 mm, Height: 31.3 mm, Color: gray

### Plug - PP-H 1,5/S/3 - 3212523

Plug, Connection method: Push-in connection, Number of positions: 3, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 10.5 mm, Height: 31.3 mm, Color: gray

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

Plug - PP-H 1,5/S/4 - 3212536

Plug, Connection method: Push-in connection, Number of positions: 4, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 14 mm, Height: 31.3 mm, Color: gray

---

Plug - PP-H 1,5/S/5 - 3212549

Plug, Connection method: Push-in connection, Number of positions: 5, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 17.5 mm, Height: 31.3 mm, Color: gray

---

Plug - PP-H 1,5/S/6 - 3212552

Plug, Connection method: Push-in connection, Number of positions: 6, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 21 mm, Height: 31.3 mm, Color: gray

---

Plug - PP-H 1,5/S/7 - 3212565

Plug, Connection method: Push-in connection, Number of positions: 7, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 24.5 mm, Height: 31.3 mm, Color: gray

---

Plug - PP-H 1,5/S/8 - 3212578

Plug, Connection method: Push-in connection, Number of positions: 8, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 28 mm, Height: 31.3 mm, Color: gray

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

Plug - PP-H 1,5/S/9 - 3212581

Plug, Connection method: Push-in connection, Number of positions: 9, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 31.5 mm, Height: 31.3 mm, Color: gray

---

Plug - PP-H 1,5/S/10 - 3212594

Plug, Connection method: Push-in connection, Number of positions: 10, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 35 mm, Height: 31.3 mm, Color: gray

---

Plug - PP-H 1,5/S/11 - 3212604

Plug, Connection method: Push-in connection, Number of positions: 11, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 38.5 mm, Height: 31.3 mm, Color: gray

---

Plug - PP-H 1,5/S/12 - 3212617

Plug, Connection method: Push-in connection, Number of positions: 12, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 42 mm, Height: 31.3 mm, Color: gray

---

Plug - PP-H 1,5/S/13 - 3212620

Plug, Connection method: Push-in connection, Number of positions: 13, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 45.5 mm, Height: 31.3 mm, Color: gray

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

### Plug - PP-H 1,5/S/14 - 3212633

Plug, Connection method: Push-in connection, Number of positions: 14, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 49 mm, Height: 31.3 mm, Color: gray

---

### Plug - PP-H 1,5/S/15 - 3212646

Plug, Connection method: Push-in connection, Number of positions: 15, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 52.5 mm, Height: 31.3 mm, Color: gray

---

### Plug - PP-H 1,5/S/1-L - 3212659

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: gray

---

### Plug - PP-H 1,5/S/1-L BU - 3212662

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: blue

---

### Plug - PP-H 1,5/S/1-L GNYE - 3212675

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: green-yellow

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

Plug - PP-H 1,5/S/1-M - 3212688

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: gray

---

Plug - PP-H 1,5/S/1-M BU - 3212691

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: blue

---

Plug - PP-H 1,5/S/1-M GNYE - 3212701

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: green-yellow

---

Plug - PP-H 1,5/S/1-R - 3212714

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: gray

---

Plug - PP-H 1,5/S/1-R BU - 3212727

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: blue

---

# Feed-through terminal block - PT 1,5/S/2P - 3213784

## Accessories

Plug - PP-H 1,5/S/1-R GNYE - 3212730

Plug, Connection method: Push-in connection, Number of positions: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 31.3 mm, Color: green-yellow

---

Strain relief - PZ 1,5/S/2 - 3212918

Strain relief, Color: black

---

Latching - PRZ 1,5/S - 3212905

Latching, Length: 3 mm, Width: 3.5 mm, Color: orange

---

Latching - PR 1,5/S/2 - 3212895

Latching, Color: orange

---

Latching - PR 1,5/S - 3212882

Latching, Color: orange

---

## Drawings

Circuit diagram

Phoenix Contact 2015 © - all rights reserved
http://www.phoenixcontact.com