

Weller®

WR3M – High-End Rework



reddot design award
winner 2007



COOPER Hand Tools



Content

WR3M – Innovation newly designed	4-9
The WR3M	6
Accessories	8
Technical data	9
Scope of delivery	9
Weller Flexibility.	10-13
Refer to the matrix on page 26 to make your choice of connecting tools for the WR3M.	
Hot Air Nozzles	14-15
For hot air pencil HAP1 and HAP200	
Nozzles	16
For DSX80, DXV80	
Soldering Tips	17-22
Plug-in adjusted soldering tip set for WMRT	17
Soldering tips for WMRP	18
Soldering tips for WSP80, WP80 and MPR80	19-20
SMT soldering tip for reworks on SMT components	20
Soldering tips for micro soldering pencil WMP	21
Soldering tips for soldering iron WSP150	22
Additional Safety Rests	23-24
Accessories	25
Matrix	26
Make your choice of connecting tools.	



WR3M – Rework on the highest level

New Design

Weller has taken the rework station to the highest level; with the new WR3M.

The versatile repair station is specifically tailored to the needs and requirements of professional repairs to latest-technology electronic sub-assemblies in industrial production engineering and in the repair and laboratory fields.

3 independent tool channels

with automatic tool detection guarantee the simultaneous operation of 3 soldering tools.

Precise temperature control performance at the soldering tip is guaranteed by the digital control electrotechnology together with superior-quality sensor and heat-transfer technology. High-speed measured-value acquisition provides for maximum temperature precision and optimum dynamic temperature performance in load situations.



High-Speed Micro Tools

All Weller High-Speed Micro Tools such as the WMRP micro soldering pencil and the WMRT micro desoldering tweezers can be connected. But also extremely powerful accessories, such as the new HAP200 hot-air pencil, can be easily connected.

Hot-air pencil HAP200

The HAP 200 provides a directional hot air flow that is adjustable. Electronic temperature control from 150°F to 999°F. Different nozzles available as accessory. Finger switch controls adjustable pump. (For use with WR 3M only.)

HAP 200 Hot air pencil

WP 80 Soldering Iron, 80 W / 24 V

USB port

The WR3M is equipped with a mini USB port. The extensive PC software supplied can be used to update the software on the control unit. Software for monitoring, parameterising and data logging is included in the software package.

Operation simplicity

The big LCD display allows clear information and simple handling.

Innovative special functions such as automatic channel changing, temperature preselection buttons for each channel, Factory Calibration Check.



Accessories



WRK Rework Set

The newly developed, innovative desoldering system facilitates soldering and desoldering of large SMT components up to 30 x 30 mm. The desoldering system can be connected to the additional vacuum channel (pick up) of the WR 3M.



WVP

Components can be easily and safely moved with the aid of the WVP vacuum pipette. The housing is antistatic and the vacuum nipples are available in 2 different sizes. The desoldering system can be connected to the additional vacuum channel (pick up) of the WR 3M.

DXV80 Desoldering Iron 80 W / 24 V

DSX80 Desoldering Iron 80 W / 24 V (optional accessory)

Technical data

Dimensions:	L x W x H (inches): 10.75 x 9.25 x 4.02
Weight:	Approximately 14.8 lbs.
Power supply voltage:	120 VAC, 60 Hz
Power consumption:	400 Watts
EOS / ESD Properties	All Tool Handles, Cordsets and Air Flow are Static Free
Fuse:	4 Amp
Temperature control range:	Variable in (1) degree increments from 150°F – 999°F
Temperature accuracy:	± 17°F (Average tip temperature can be offset ± 9°F at idle with no load)
Temperature stability:	± 9°F
Hot Air / Vacuum Pump (duty cycle: 30 seconds on, 30 seconds off)	Max. vacuum 0.7 bar Max. delivery rate 18 l/min Hot air max. 15 l/min
Vacuum Pick-up Pump (duty cycle: 60 seconds on, 30 seconds off)	Max. vacuum 0.5 bar Max. delivery rate 1.7 l/min



WR3M scope of delivery

- Order No. WR3M
- WR3M repair station
 - Adapter for HAP 200 hot-air pencil
 - CD with USB software
 - USB cable



WR3000M set scope of delivery

- Order No. WR3M
- WR3M Repair Station
 - HAP200 Hot-air pencil with WDH30 Safety rest
 - DXV80 Desoldering iron with WDH40 Safety rest
 - WP80 Soldering iron with WDH10T Stop + go Safety rest
 - WVP Vacuum pick up
 - WDC2 Dry cleaner
 - Adapter for HAP200 Hot-air Pencil
 - CD with use software
 - USB cable
 - Nozzle replacement tool
 - 1.2mm and 3.0mm hot gas nozzles
 - Nozzle adapter for HAP200
 - 2.3mm and 2.5mm desoldering nozzles
 - Desoldering cleaning tools, brush, and spare filters
 - Color-coded clips for easy tool identification

WR3M – Innovation newly designed



- 3 tool channels with automatic tool detection



- Large LCD display



- Own vacuum channel for pick-up

- USB port

- Innovative special functions

- Comprehensive PC software

- All High-Speed Micro-Tools can be connected

- New powerful hot-air pencil

Weller Flexibility

Refer to the matrix to make your choice of connecting tools for the WR3M.
(See Matrix page 26)

HAP200 Hot air pencil set

HAP200
0052711799



The HAP200, 200 W/24 V, provides a directional hot airflow that is adjustable and static-free. Electronically temperature controlled from 150°F to 999°F. Different nozzles available as accessories. Finger switch controls speed adjustable pump. Hot air pencil set, consisting of HAP 200 with finger switch, WDH 30 Safety rest for pencil, nozzle 1,2 mm and 3,0 mm, key and nutdriver for nozzle changing. For pencil only, order 0052711699.

DSX80 Desoldering iron set and service kit

DSX80
0051318399



An 80 W/24 V desoldering iron for electronics rework. Electronically temperature controlled. Micro-finger switch controls quick-start, fast action vacuum pump. Different interchangeable tiptlets are available as accessories. DSX80 set, consisting of DSX80 Desoldering iron, WDH30 Safety rest, cleaning tool, glass collector, two desoldering nozzles, gasket, anti-bloc paste, filter. For pencil only, order 0051319099.

HAP1 Hot air pencil set

HAP1
0052711899



The HAP1, 100 W/24 V, provides a directional hot airflow that is adjustable and static-free. Electronically temperature controlled from 150°F to 999°F. Different nozzles available as accessories. Finger switch controls speed adjustable pump. Hot air pencil set, consisting of HAP1 with finger switch, WDH30 Safety rest for pencil, nozzle 1,2 and 3,0 mm, key and nutdriver for nozzle changing.

DXV80 Inline desoldering set


DXV80
0051318299



Connectable to all 80 W desoldering stations. Handle utilizes the replaceable solder collector to hold the extracted solder. Use off thred less DX nozzles. DXV80 set, consisting of DXV80 Desoldering iron, and WDH40 Safety rest for iron. For pencil only, order 0051318099.

WMRP Soldering pencil set for RT soldering tips

WMRP
0052919099



The RT soldering tips have an extremely short heat-up time. All component parts of the system, such as the sensor and heating element, are designed for optimum heat transfer. This ensures absolute efficiency in the utilization of the power provided by the supply unit. The recovery time is minimized. Changing soldering tips is quick, easy, and, most importantly, requires no tools. WMRP set, consisting of WMRP soldering pencil, RT3 soldering tip and WDH50 Safety rest. For pencil only, order 0052917199.

WP80 Micro Soldering pencil set

WP80
0052918199



The 80 W micro soldering pencil WP80 persuades with its short tip-to-grip design, being of big advantage for work under microscopes. The distance from grip to the tip is 40 mm only. WP80 set, consisting of WP80 soldering pencil and WDH10 Safety rest. For pencil only, order 0052918099.

WSP80 Micro soldering pencil set

WSP80
0052917899



A micro soldering pencil, 80 W/24 V. This soldering pencil can be universally used in all situations from extremely delicate soldering to those where there is a greater temperature requirement. WSP80 set, consisting of WSP80 Micro soldering pencil with WDH10 Safety rest. For pencil only, order WSP80.

MPR80 Peritronic soldering pencil set

MPR80
0053313199



An 80 W Antistatic Peritronic soldering pencil that gives all-round vision when making intricate connections. Antistatic cord and handle. Electronically temperature controlled. Consists of MPR80 Peritronic soldering iron and KH25P Safety rest.

Weller Flexibility

Refer to the matrix to make your choice of connecting tools for the WR3M.
(See Matrix page 26)

WMPT Micro soldering pencil set with stop + go stand

WMP
0053315999



The 65 W micro pencil is up to the task with superior performance for both heat-up and thermal efficiency. Suitable to handle all micro components and fine pitch tasks. The WMP provides an extremely short tip-to-grip distance. The heater is integrated into the handle. When the tip wears out the heating element goes on. WMP set consisting of WMP micro soldering pencil and WDH20T Safety rest with Stop + Go function for WMP. For pencil with WDH20 stand, order 0052917999. For pencil only, order WMP.

WMRT Tweezers set

WMRT
0051317399



The new WMRT desoldering tweezers 80 W/24 V enable with their twin parallel adjusted tiplets a significant precise and desoldering of very small SMD components. Placed in the Safety rest WDH60 the tips are automatically switched off for increasing endurance. For tweezers only, order 0051317299.

WSP150 Soldering iron set

WSP150
0052918999



The WSP150, 150 W/24 V, soldering iron was specially developed for soldering tasks with extremely high heat requirements. The 150 W heater power combined with optimal transfer of heat to the soldering tip guarantees the high performance capability of the soldering pencil. WSP150 set, consisting of WSP150 Soldering pencil, WDH30 Safety rest for iron. For pencil only, order 0052917099.

WTA50 Tweezers set

WTA50
0053313399




The tweezers are used to desolder SMD components. The tweezers have two moveable heating elements. WTA50 set, consisting of WTA50 Tweezers, AK51 Safety rest for Tweezers. For tweezers only, order 0051317199.

Weller Flexibility

Refer to the matrix to make your choice of connecting tools for the WR3M.
(See Matrix page 26)

WSB80 Solder Bath

WSB80
0052704099



The WSB80 is a very useful rework preparation tool. The solder bath is temperature controlled continuously from 150°F to 850°F via an existing 80 W power unit (sold separately). The solder bath can be used to tin wire ends and clean leads of all extraneous solder particles in preparation for reworking. (Usable with lead free solder.) Compatible with WD1, WD1M, WD2, WD2M, WRS3000, or WR3M power units.

WHP80 (80 W/24 V) Preheating Plate

WHP80
0052702899



With a heating surface of 80 x 50 mm, for preheating IC boards prior to micro rework. Compatible with WD1, WD1M, WD2, WD2M, WRS3000, or WR3M power units.

WVP Vacuum Pick-Up

WVP Vacuum pick-up
0052918499



Vacuum pick-up for easy manually handling of SMD components. The housing is antistatic. The vacuum nipples are available in two different sizes.

WSB150 Solder Bath


WSB150
0052704299



The WSB150 solder bath is optimally suited to tin coating and preparation of soldering components. It has a temperature range of 150°F – 999°F with heat output of 150 W. To guard against dripping solder residue, the solder bath is placed in a V2A tray, supplied as an optional extra. (Usable with lead free solder.) Compatible with WD2, WD2M, or WR3M power units.

WRK Chip Removal Kit

WRK Chip kit
0051515599



Innovative desoldering system to solder and desolder SMD components up to the size of 30 x 30 mm. Connectable to the additional vacuum channel of the WR3M.

Hot Air Nozzles


for hot air pencil HAP1 and HAP200











HAP1 (page 10)



HAP200 (page 10)



Adapter
Order No. 0058761728

	Description	Dimensions (mm)		Type	Order No.
		x	y		
 	Hot air nozzle four sides heated with hot plate	18.0 x 18.0		Q10	0058727785
		16.0 x 16.0		SK769B	0058727816
		12.0 x 12.0		SK709	0058727812
 	Hot air nozzle four sides heated with hot plate	12.5 x 15.0		Q08	0058727783
 	Hot air nozzle four sides heated with hot plate	15.0 x 10.0		Q06	0058727780
 	Hot air nozzle four sides heated with hot plate	6.0 x 9.0		Q04	0058727778
 	Hot air nozzle four sides heated with hot plate	6.0 x 6.5		Q02	0058727777
 	Hot air nozzles two sides heated with hot plate	10.0 x 18.0		D10	0058727784
 	Hot air nozzle two sides heated with hot plate	15.0 x 10.0		D08	0058727781
 	Hot air nozzle two sides heated with hot plate	10.0 x 13.0		D06	0058727782
	Hot air nozzle two sides heated with hot plate	10.5 x 10.5		D04	0058727779

Hot Air Nozzles


for hot air pencil HAP1 and HAP200









HAP1 (page 10)



HAP200 (page 10)



Adapter
Order No. 0058761728

	Description	Dimensions (mm)		Type	Order No.
		x	y		
 	Flat nozzle	12.0 x 1.5		F06	0058727772
 	Flat nozzle	10.5 x 1.5		F04	0058727773
 	Flat nozzle	8.0 x 1.5		F02	0058727774
 	Round nozzle long straight	Ø 2.0		R10	0058727787
 	Round nozzle long bent	Ø 2.0		R08	0058727786
 	Round nozzle	Ø 3.0		R06	0058727822
 	Round nozzle	Ø 1.2		R04	0058727821
 	Round nozzle	Ø 0.8		R02	0058727823
 	Dual nozzle	Ø 1.5 x 10.0		FD4	0058727775
 	Dual nozzle	Ø 1.5 x 8.0		FD2	0058727776

Nozzles

Threadless nozzles for desoldering iron
DSX80 and DXV80

The new X series nozzle feature a threadless fixture system whereby the nozzle is inserted into the head and locked into place by aplying a 1/4 turn. This feature allows the nozzles to be quickly and easily exchanged and also improves the rate of thermal transfer from the head to the nozzle.



DSX80 (page 10)



DXV80 (page 10)



	Model	Description	mm	mm	mm	Order No.
	DX110	Nozzle	1.9	0.7	23	0051314099
	DX111	Nozzle	2.5	0.7	23	0051314199
	DX112	Nozzle	2.3	1.0	23	0051314299
	DX113	Nozzle	2.5	1.2	23	0051314399
	DX113HM	Nozzle with improved thermal transfer	2.5	1.2	23	0051315099
	DX114	Nozzle	3.3	1.8	23	0051314499
	DX115	Nozzle	1.9	0.7	23	0051314599
	DX116	Nozzle	2.7	1.2	29	0051314699
	DX117	Nozzle	2.9	1.5	23	0051314799
	DX118	Nozzle	1.5	0.7	23	0051314899
	DX119	Needle Tiplet with not wettable stainless steel tube for removal of solder bridges in connection with hot air pencil	1.1	0.7	31	0051315199
	DX120	Nozzle without inside tube, for cleaning of SMD pads	2.5	1.1	22	0051315299
	Conus insert	cleaning tool				0058706794

Soldering Tips

Plug-in adjusted Soldering Tip Set for WMRT



WMRT (page 12)

	Type	Description	Width A	Thickness B	Order No.
	RTW 1	Tip set bent 45°	Ø 0.4mm		0054465199
	RTW 2	Tip set bent 45°, Chisel	0.7mm	0.4mm	0054465299
	RTW 3	Tip set bent 45°, Chisel	3mm	1.0mm	0054465399
	RTW 4	Tip set bent 45°, Chisel	6mm	1.0mm	0054465499

Soldering Tips

Soldering tips for WMRP



WMRP (page 10)

	Type	Description	Width A	Thickness B	Order No.
	RT1	Needle tip	Ø 0.2mm		0054460199
	RT1SC	Chisel	0.4mm	0.15mm	0054461299
	RT2	Round tip slim	Ø 0.8mm		0054460299
	RT3	Chisel tip	1.3mm	0.4mm	0054460399
	RT4	Chisel tip	1.5mm	0.4mm	0054460499
	RT5	Chisel tip bent 30°	0.8mm	0.4mm	0054460599
	RT6	Round tip 45° sloped	1.2mm		0054460699
	RT7	Knife tip 45° sloped	2.2mm		0054460799
	RT8	Chisel tip	2.2mm	0.4mm	0054460899
	RT9	Chisel tip	0.8mm	0.4mm	0054460999
	RT10GW	Gull wing	1.2mm	2.0mm	0054461099
	RT11	Chisel tip	3.6mm	0.9mm	0054461199
		Type K Thermocouple Assembly	1.5mm	0.4mm	K1101

Use only Weller® soldering tips. The use of non-Weller® components may void product warranty if the non-Weller® component causes damage to the unit.

Soldering Tips

for WSP80, WP80 and MPR80



WSP80 (page 11)



WP80 (page 10)



MPR80 (page 11)

	Type	Description	Width A	Thickness B	Length	Order No.
	LT 1SC	Chisel	0.4mm	0.14mm	15.0mm	LT1SC
	LT H	Chisel	0.8mm	0.4mm	13.5mm	LTH
	LT A	Chisel	1.6mm	0.7mm	13.5mm	LTA
	LT B	Chisel	2.4mm	0.8mm	13.5mm	LTB
	LT C	Chisel	3.2mm	0.8mm	13.5mm	LTC
	LT D	Chisel	4.6mm	0.8mm	13.5mm	LTD
	LT K	Chisel long	1.2mm	0.4mm	21.0mm	LTK
	LT L	Chisel long	2.0mm	1.0mm	21.0mm	LTL
	LT M	Chisel long	3.2mm	1.2mm	21.0mm	LTM
	LT HX	Chisel bent	0.8mm	0.4mm	18.0mm	LTHX
	LT ALX	Chisel bent	1.6mm	0.7mm	18.0mm	LTALX
	LT BX	Chisel bent	2.4mm	0.8mm	18.0mm	LTBX
	LT AX	Chisel bent	1.6mm	0.8mm	13.5mm	LTAX
	LT 4X	Chisel bent 30°	Ø 1.2mm	0.4mm	16.5mm	LT4X
	LT 1S	Round slim	Ø 0.2mm		15.0mm	LT1S
	LT 1SA		Ø 0.5mm		16.0mm	LT1SA
	LT 1A		Ø 0.5mm		14.0mm	LT1A
	LT 1	Round	Ø 0.25mm		14.0mm	LT1
	LT AS	Round	Ø 1.6mm		13.5mm	LTAS
	LT CS	Round	Ø 3.2mm		13.5mm	LTC
	LT 1SLX	Round slim bent 30°	Ø 2.0mm	Ø 0.4mm	20.5mm	LT1SLX
	LT 1X	Round bent 30°	Ø 0.4mm		12.5mm	LT1X
	LT 4	Round sloped 45° slim	Ø 1.2mm		15.0mm	LT4
	LT F	Round sloped 45°	Ø 1.2mm		13.5mm	LTF
	LT BB	Round sloped 45° long	2.4mm	4.0mm	18.0mm	LTBB
	LT CC	Round sloped 45° long	3.2mm	6.0mm	18.0mm	LTCC

All Weller “Longlife” tips are designed for working with leadfree application

Use only Weller® soldering tips. The use of non-Weller® components may void product warranty if the non-Weller® component causes damage to the unit.

Soldering Tips

for WSP80, WP80 and MPR80



WSP80 (page 11)



WP80 (page 10)



MPR80 (page 11)

	Type	Description	Width A	Thickness B	Length	Order No.
	LT 1L	Conical long	Ø 0.2mm		26.4mm	LT1L
	LT S	Conical long	Ø 0.4mm		21.0mm	LTS
	LT 1LX	Conical long bent	Ø 0.2mm		26.4mm	LT1LX
	LT GW	Gull wing 45°	Ø 2.3mm	3.2mm	18.8mm	LTGW
	LT KN	Knife tip	6.2mm		16.0mm	LTKN
		Type K Thermocouple Assembly	2.4mm	0.8mm	13.5mm	K181
		Type K Thermocouple Assembly for WP80	2.4mm	0.8mm	13.5mm	K1111

All Weller “Longlife” tips are designed for working with leadfree application

Use only Weller® soldering tips. The use of non-Weller® components may void product warranty if the non-Weller® component causes damage to the unit.

SMT soldering tip for reworks on SMT compontents


	Type	Description	Width A	Thickness B	Length C	Order No.
	LT SMT01	Blade	10.4mm	0.6mm	7.1mm	LTSMT01
	LT SMT02	Blade	16.8mm	0.6mm	7.1mm	LTSMT02
	LT SMT03	Blade	20.8mm	0.6mm	7.1mm	LTSMT03

Soldering Tips

for micro soldering pencil WMP



WMP (page 11)



	Description	Width A	Thickness B	Length C	Type/Order No.
	Chisel tip	0.4mm	0.15mm	14.0mm	NT1SC
		0.8mm	0.4mm	8.4mm	NTH
		1.2mm	0.4mm	8.4mm	NTK
		1.6mm	0.4mm	9.5mm	NTA
		1.6mm	0.4mm	7.4mm	NT6
		2.4mm	0.8mm	7.8mm	NTB
		3.2mm	0.8mm	8.2mm	NTC
		4.0mm	0.8mm	8.6mm	NTD
	Chisel tip, bent	1.6mm	0.4mm	8.2mm	NTAX
	Round tip, bent 45°	Ø 0.4mm		8.6mm	NT1X
	Round tip	Ø 0.25mm	–	7.4mm	NT1
	Round tip slim	Ø 0.25mm	–	8.5mm	NT1S
	Round tip, sloped 45°	Ø 1.2mm	–	9.9mm	NT4
	Gull wing	2.0mm	3.0mm	13.4mm	NTGW
	Type K Thermocouple Assembly	2.4mm	0.8mm	7.8mm	K191

Use only Weller® soldering tips. The use of non-Weller® components may void product warranty if the non-Weller® component causes damage to the unit.

Soldering Tips

for soldering iron WSP150



WSP150 (page 11)


	Type	Description	Width A	Thickness B	Order No.
	LHT C	Chisel	3.2mm	1.2mm	0054445599
	LHT D		5.0mm	1.8mm	0054445299
	LHT E		7.0mm	1.8mm	0054445199
	LHT F		9.3mm	1.8mm	0054445099
	LHT DX	Chisel bent	5mm	2mm	0054446299
	LHT EX		7mm	2mm	0054446199
	LHT FX		9mm	2mm	0054446099
	LHT D 45°	Sloped 45° for solar panel production	5mm	—	0054445699

Use only Weller® soldering tips. The use of non-Weller® components may void product warranty if the non-Weller® component causes damage to the unit.

Additional Safety Rests

Safety rests with Stop+Go Function

The safety rests with Stop+Go function have an integrated micro switch which is activated when the soldering iron is picked up or put down. The operator can decide between an immediate or delayed (20 min) temperature reduction (SETBACK) to 150°C (300°F) and program the power unit accordingly. For digital Soldering units only.



WMPT Soldering Set (0053315999)

Consisting of WMP Soldering Iron and WDH 20T Safety rest with Stop + Go function.

Standard Safety rests

complete with sponge

WDH10 (0051512199)



Safety rest for WP80 Micro soldering pencil and WSP80 Micro soldering pencil

WDH20 (0051512299)



Safety rest for WMP Micro soldering pencil

WDH30 (0051515299)



Safety rest for HAP200 Hot air pencil, HAP1 Hot air pencil, DSX80 Desoldering iron, and WSP150 Soldering iron

Accessories

WDH40 (0051515399)



Safety rest for DXV80 Desoldering iron

WDH50 (0051515699)



Safety rest for WMRP Micro soldering pencil with Stop + Go function

WMRTH (0051514699)



Safety rest for WMRT with Stop + Go function

WDH10T (0051516199)



Safety rest for WP80 and WSP80 Micro soldering pencil with Stop + Go function

WDH20T (0051516299)



Safety rest for WMP Micro soldering pencil with Stop + Go function

KH25P (0051503399)



Safety rest for MPR80 Peritronic soldering pencil

AK51 (0051504299)



Safety rest for WTA50 Tweezer

WDC Dry Cleaner (0051512499)



Soft solution for cleaning from lead free solder with metal wool. Replacement wools 0051382499 (2 pcs.)

WDC2 Dry Cleaner (0051512599)



Soft solution for cleaning from lead free solder with metal wool. For WDH safety rests. Replacement wools 0051382499 (2 pcs.)

Tip Activator (0051303199)



For regeneration of oxidized tips, works fast and easy with low temperature. Environmentally safe, no halides, lead, rosin or residue. Regular use will prolong life time of the tips.

Cleaning Tool (0051350099)



For cleaning of desoldering nozzles and for nozzle exchange.

Service Set (0051312499)



Spare filter for Desoldering iron DSX80 (available as of the third quarter 2007)

Barrel for Soldering Iron WSP80 and WP80



Barrel for WSP80	0058744710
Barrel long for WP80 (55mm)	0058744846
Barrel short for WP80 (40mm)	00 8744845

Cartridge (0058741815)



Spare cartridge for Desoldering iron DXV80 (5 pieces)

Polishing Bar (WPB1)



Grindstone for removal of compact oxid films


Sponge (0052241999)



Dimensions 70 x 55 x 16mm (5 pcs.)

Weller brings to the market an extended generation of versatile soldering / desoldering and hot air tools. Performance has been increased with soldering irons and desoldering irons up to 200 W.

The Weller WR3M station easily connects to a variety of new and existing Weller tools and accessories to provide even greater flexibility. The matrix below makes selection easy, and puts you firmly in control of all your workbench needs.

		Order No.	Soldering Tip Included	
	HAP200 Hot Air Pencil (WDH30 Safety rest for HAP200)	0052711799	None	
	HAP1 Hot Air Pencil (WDH30 Safety rest for HAP1)	0053311499	R 06	
	WMP Micro Soldering Pencil 65 W (WDH20 Safety rest for WMP)	0053315999	NT 1	
	DSX80 Desoldering Iron 80 W (WDH30 Safety rest for DSX80)	0053313899	DX 113HM	
	DXV80 Desoldering Iron 80 W (WDH40 Safety rest for DXV80)	0051318299	DX 113HM	
	WMRP Soldering Pencil (WDH50 Safety rest for WMRP)	0052918399	RT 3	
	WP80 Micro Soldering Pencil 80 W (WDH10 Safety rest for WP80)	0052918199	LTB	
	WSP150 Soldering Iron 150 W (WDH30 Safety rest for WSP150)	0053313599	LHTF	
	WSP80 Micro Soldering Pencil 80 W (WDH10 Safety rest for WSP80)	0053312599	LTB	
	MPR80 Antistatic Peritronic soldering pencil set (KH25P Safety rest for MPR80)	0053313199	LTB	
	WMRT Tweezer (WDH60 Safety rest for WMRT)	0051317399	RTW 2	
	WSB80 Solder Bath	0052704099	N/A	
	WTA50 Tweezer (AK51 Safety rest for WTA50)	0053313399	WTA 1	
	WSB150 Solder Bath	0052704299	N/A	
	WHP80 Preheating Plate	0052702899	N/A	



Campbell® Caulk Master® Crescent® Diamond® Erem® Kahnetics® Lufkin®
Nicholson® Plumb® H.K.Porter® Weller® Wire-Wrap® Wiss® Xcelite®

P.O. Box 728
Apex, NC 27502
www.cooperhandtools.com