WIRING DIAGRAM



LOCKNUT LN−M12



LOCKNUT LN−M5







SPECIFICATIONS

MEASURING RANGE [A...B]	0.1−1.5 mm
MIN. REPEAT ACCURACY	≤1% OF MEASURING RANGE [A−B] ≤0.5%, AFTER A HEATING PERIOD OF 0.5 H
REPRODUCIBILITY	≤14 µm ≤7 µm, AFTER A HEATING PERIOD OF 0.5 H
MAX. RELATIVE TEMPERATURE DRIFT	≤ ±.06%/C°
OPERATING TEMPERATURE	−10°C to +70°C (−14°F to +158°F)
OPERATING VOLTAGE	15−30 VDC
RIPPLE	≤10%
NO−LOAD CURRENT	≤8 mA
RATED INSULATION VOLTAGE	≤0.5 kV
OUTPUT FUNCTION	4−WIRE, ANALOG
SHORT−CIRCUIT PROTECTED	YES
WIRE−BREAK PROTECTION	INCORPORATED
VOLTAGE OUTPUT	0−10 V
CURRENT OUTPUT	0−20 mA
VOLTAGE OUTPUT LOAD RESISTANCE	≥ 4.7 kΩ
CURRENT OUTPUT LOAD RESISTOR	≤ 0.4 kΩ
READING RATE FREQUENCY	200 Hz
HOUSING MATERIAL	METAL, A2 1.4301 (AISI 304)
ACTIVE FACE	PLASTIC, PA12−GF30
CABLE/JACKET MATERIAL/LENGTH	ø2.4, PVC, 0.3 METERS
VIBRATION RESISTANCE	55 Hz (IN ALL 3 PLANES)
SHOCK RESISTANCE	30 g, 11 ms
DEGREE OF PROTECTION	IP 67

REV	DESCRIPTION	BY	DATE	ECO NO.
A	DRAWING RELEASE	RDS	03/07/03	

RELATED DOCUMENTS
1.
2.
3.
4.

MATERIAL

FINISH

3RD ANGLE PROJECTION

ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY

CONTACT TURCK FOR MORE INFORMATION

TURCK INC
High Technology Sensors and Automation Controls
3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1−800−544−7769
(763) 553−7300
(763) 553−0708 fax
turck.com

DRFT RDS | DATE 03/07/03
DSGN | SCALE NONE

UNIT OF MEASUREMENT
INCH [MILLIMETER]
DO NOT SCALE THIS DRAWING

DESCRIPTION
Bi 1.5−EG05−0.3−M12−SiU−H1141

IDENTIFICATION NO. M1533005 | REV A

FILE: m1533005 | SHEET 1 OF 1