

**219.6337**

**PLUG 3P+N+E IP66/IP67 63A 6h 346-415V AC**



### TechData

Rated current	63A
Commercial series	OPTIMA-EX[GD] Series
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Syntetical description	PLUG
Protection degree	IP66/IP67
Types of available outlets	STRAIGHT
Group and categories EX	II 2GD

### Approvals and Certifications



INERIS ATEX  
Institut National de l'Environnement  
Industriel et des Risques



INERIS IECEX  
Institut National de l'Environnement  
Industriel et des Risques



CE  
Declaration of conformity

### Standards and Laws



EN 60309-2/A2 (2012)  
[European Standard] Plugs, socket-outlets  
and couplers for industrial purposes. Part 2:  
Dimensional interchangeability requirements  
for pin and contact-tube accessories of  
harmonized configurations



EN 60309-1/A2 (2012)  
[European Standard] Plugs, socket-outlets  
and couplers for industrial purposes. Part 1:  
General requirements



EN 60309-1 (1999)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60079-7 (2007)  
[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"



EN 60079-0 (2009)  
[European Standard] Explosive atmospheres. General requirements.



EN 60079-31 (2009)  
[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"



EN 60079-1 (2007)  
[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures "d"

### Packaging

Description	Carton
Quantity	8
EAN code	8001636742717
Gross weight	7.032 KG
Volume	46878.5 CCM
Dimensions	305x580x265 (MM)