

Crimp contact - CK2,5-ED-0,50BU AU - 1674859


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Turned 2.5 crimp contact, individual female contact, core diameter 0.5 mm², gold-plated



Key Commercial Data

| | |
|--------------------------------------|--|
| Packing unit | 100 pc |
| GTIN |  4 017918 135553 |
| Weight per Piece (excluding packing) | 1.57 g |
| Custom tariff number | 74152900 |
| Country of origin | Germany |

Technical data

Electrical characteristics

| | |
|------|--|
| Note | for HC-M-06, HC-M-HV, HC-M-08, HC-M-20, HC-A, HC-BB, HC-B, and HC-HV contact carriers, the quality of a crimp connection is determined by DIN EN 60352-2, gold-plated contacts recommended at U < 5 V and I < 5 mA |
|------|--|

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

Mechanical characteristics

| | |
|---|-------------------------------|
| Conductor cross section | 0.5 mm ² |
| Connection cross section AWG | 20 |
| Stripping length of the individual wire | 7.5 mm (9.5 mm at HC-M-HV...) |
| Insertion/withdrawal cycles | ≥ 500 |

General

| | |
|-----------------------|---|
| Type | Individual female contact |
| Series | HC-M-06 |
| Connection method | Crimp connection |
| Assembly instructions | At voltages of < 5 V and currents < 5 mA, gold-plated contacts are recommended. |

Crimp contact - CK2,5-ED-0,50BU AU - 1674859

Technical data

General

| | |
|------------|---|
| Connection | for HC-M-06, HC-M-HV, HC-M-08, HC-M-20, HC-A, HC-BB, HC-B and HC-HV contact carriers. The quality of a crimp connection is determined by the DIN EN 60 352-2. |
|------------|---|

Material data

| | |
|--------------------------|--------------|
| Contact material | Copper alloy |
| Contact surface material | Gold-plated |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |
| eCl@ss 8.0 | 27440204 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000796 |
| ETIM 3.0 | EC000796 |
| ETIM 4.0 | EC000796 |
| ETIM 5.0 | EC000796 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211923 |
| UNSPSC 7.0901 | 39121522 |
| UNSPSC 11 | 39121522 |
| UNSPSC 12.01 | 39121522 |
| UNSPSC 13.2 | 39121522 |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Crimp contact - CK2,5-ED-0,50BU AU - 1674859

Approvals


Approvals submitted

Approval details

| |
|-----|
| EAC |
|-----|

Drawings

Dimensional drawing



Phoenix Contact 2015 © - all rights reserved
<http://www.phoenixcontact.com>