



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS PER QQ-B-626
- 2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 3. BERYLLIUM COPPER PER QQ-C-530
- 4. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 5. TEFLON MIL-P-19468

					DIMENSIONS ARE IN MILLIMETERS				PART NO.		<h2 style="text-align: center;">Amphenol - Kai Jack</h2> <p style="text-align: center;">TAINAN TAIWAN</p>				
					UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED				TITLE		
6	CONTACT PIN	NOTE 3	NOTE 4	1	SMAF-RSMAF-6	0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				DATE		SMA FEMALE TO SMA REVERSE POLARITY FEMALE ADAPTOR			
5	GASKET	SILICONE	RED	1	GS-6/43X06					DATE				04-24-00'	
4	RETAINER RING	NOTE 3	NATURAL	1	SMA5000-4-B					DATE				04-24-00'	
3	INSULATOR	NOTE 5	NATURAL	2	SMA5071A1-3T-50					DATE		04-24-00'			
2	BODY	NOTE 1	NOTE 2	1	SMA5071A1-2-B					DATE		04-24-00'			
1	SHELL	NOTE 1	NOTE 2	1	SMA5000-1-C	DATE		04-24-00'		DRAWING NO.					
NO. DESCRIPTION MATERIAL FINISH Q'TY DRAWING NO.					SCALE	5/1	ISSUE	A	DATE		FILE NO. F:\DWG\SMF\RSMAF\50\3GT50G				