

219.1636

PLUG 3P+E IP66/IP67 16A 6h 380-415V AC



TechData

Rated current	16A
Commercial series	OPTIMA-EX[GD] Series
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Syntetical description	PLUG
Protection degree	IP66/IP67
Types of available outlets	STRAIGHT
Group and categories EX	II 2GD

Approvals and Certifications



INERIS ATEX
Institut National de l'Environnement
Industriel et des Risques



INERIS IECEX
Institut National de l'Environnement
Industriel et des Risques



CE
Declaration of conformity

Standards and Laws



EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 1:
General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 2:
Dimensional interchangeability requirements
for pin and contact-tube accessories of
harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60079-7 (2007)
[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"



EN 60079-0 (2009)
[European Standard] Explosive atmospheres. General requirements.



EN 60079-31 (2009)
[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"



EN 60079-1 (2007)
[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures "d"



EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	12
EAN code	8001636742243
Gross weight	4.044 KG
Volume	23625 CCM
Dimensions	225x280x375 (MM)