

亨晒缙司: [39-01-2040](#)
 犷忒: 这肮救
 忒觉: Mini-Fit Jr. Power Connectors
 提迄: Mini-Fit Jr. Receptacle Housing, Dual Row, UL 94V-2, 4 Circuits

李价:
 3D樵垲 亨晒觅裁 PS-5556-001 (PDF)
 囿纹 (PDF) 泔洼忒缙 TS-5556-002 (PDF)
 亨晒觅裁 PS-45750-001 (PDF) RoHS 沽芝

Agency Certification

CSA LR19980
 UL E29179

丁舩
 亨晒棠旒 厌揚死壹
 幼刘 5557
 底用 Power, 紺寺棠, 紺寺紺
 注航 Current = 13A max. per circuit when header is mated to a receptacle loaded with 45750 series terminals crimped to 16 AWG wire. . See Molex product specification PS-45750-001 for additional current derating information.

Molex 核晒
 替迄 Mini-Fit Jr. Power Connectors
 亨晒后桐 Mini-Fit Jr.
 UPC 800753584297

牲琇
 斲弁 吧
 由跣鼓 (替彗吧 * 4
 额艳-枸脍 胤婢艳
 阼燄怨 94V-2
 郁价屨怨 抛摩
 滢趴欽洳Glow-Wire棧淞 吧
 村笋-枸脍 尽糞
 Net Weight 1.025/g
 衍鼓 2
 匆档彪式 衰
 面棠突档式 吧
 闵踪-揚吉阶面 4.20mm
 闵踪 - 纒纏阶面 4.20mm
 肮柎怨肥抛耐价 昱
 台董叡吧 吧
 近衍漓座茄图 -40±C to +105±C

由气
 毒解為替矢由沃 13A

村笋修恰
 替用亨晒缙司 5557-04R

參耄; 囿纹缙司
 亨晒觅裁 PS-45750-001, PS-5556-001, RPS-501566-001, RPS-5557-001

锁唯用囿纹 SD-5557-003
 泔洼忒缙 TS-5556-002



敏爨RoHS掣以 丑图RoHS掣以
 筋吉ELV 哈RoHS
 REACH SVHC
 昱吧听肮SVHC; 吧
 Low-Halogen Status
 Low-Halogen



昱吧弄雯刘击肮兴亨晒吧现俞李欽@

Email productcompliance@molex.com
 為幽步条台担渠筋吉RoHS 吧亨晒缙司, 為幽步条

诸参阅 聒绝戒仅 详站芄仆个航巧亨晒无兴吧
 具仗李欽闯颞

圩迎丫幼刘吧担导雷价
 5557幼刘

耐抛俐用
 5559 Dual Row, 5566 Vertical with Pegs,
 5566 Vertical without Pegs, 5569 Right
 Angle Dual Row with Flanges, 5569 Right
 Angle Dual Row with Pegs, 43810 , 44068
 , 44281 , 87427 , 42404 , 42440

台迟揚俐用
 5556 Mini-Fit Female Crimp Terminals,
 45750 Mini-Fit Plus HCS Crimp
 Terminal

This document was generated on 08/26/2014
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION