

Inline terminal - IB IL 400 ELR 1-3A - 2727352

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Inline power-level terminal blocks, electronic direct starter, up to 1.5 kW / 400 V AC



Product description

INTERBUS Inline power-level terminals enable standard three-phase motors to be switched, protected, and monitored via INTERBUS. The terminals in the product range are available as direct and reversing starters in electronic and electromechanical versions. Each power-level terminal is equipped with electronic motor protection and provides the same advantages as the INTERBUS motor starter, such as motor current monitoring, overcurrent protection, and quick shutdown according to IEC. The integrated controller supports motor current parameterization via INTERBUS in the performance ranges from 15 W to 1.5 kW and 0.1 kW to 3.7 kW. As with all Inline automation terminals, the power-level terminals can be snapped on and mounted on a DIN rail without tools. Labeling is carried out directly on the module using the familiar zack marker strip and a snap-on label with large-surface labeling option.


Additional features include:

- Mains voltage up to 400 V AC 3~
- Mains output power: electronic: 15 W to 1.5 kW, electromechanical version: 0.1 kW to 3.7 kW
- Manual local operation without bus supported
- Can be extended with brake function as an option
- Thermal motor monitoring using Inline thermistor terminal

Why buy this product

- Connection option for an external passive brake module
- Hand-held operator panel mode
- Integrated electronic motor protection in accordance with IEC 60947-4
- Diagnostic and status indicators
- Safe isolation between mains voltage and 24 V supply voltage according to EN 50178
- Motor current monitoring
- Motor control via OUT process data

Key commercial data

Packing unit	1 pc
GTIN	 4 017918 168476
Weight per Piece (excluding packing)	450.0 g
Custom tariff number	85389091
Country of origin	Germany

Technical data

Note

Inline terminal - IB IL 400 ELR 1-3A - 2727352

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	63 mm
Height	224 mm
Depth	109 mm

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 85 % (In conformity with DIN EN 61131-2)
Permissible humidity (storage/transport)	10 % ... 85 % (In conformity with DIN EN 61131-2)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above mean sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above mean sea level)
Degree of protection	IP20

Interfaces

Fieldbus system	Lokalbus
Designation	Inline local bus
Connection method	Inline data jumper
Transmission speed	500 kBit/s
Transmission physics	Copper

Power supply for module electronics

Connection method	Through the potential jumper
Designation	Terminal strips X11 and X12

Mains connection

Designation	Mains connection
Connection method	Power connector or power bridge
Designation connection point	Terminal strip; X11 and X12
Number of positions	5
Permissible conductor cross section	max. 2.5 mm ² (L1+L2+L3+N-PE)
Operating voltage	187 V AC ... 440 V AC +0 % (conductor voltage)
Max. current carrying capacity	20 A

Motor starter, output

Connection method	(3-phase), via COMBICON
Number	1
Output name	Motor outputs (three phases), short-circuit-proof with external line protection fuse 16 A
Designation connection point	Terminal strip; X10
Number of positions	4
Permissible conductor cross section	1 mm ² ... 2.5 mm ²

Inline terminal - IB IL 400 ELR 1-3A - 2727352

Technical data

Motor starter, output

Operating voltage	200 V AC ... 440 V AC
Frequency range	50 Hz ... 60 Hz
Nominal current range	0.2 A ... 3.6 A
Switching rate	Max. 30 per minute (observe derating)

Motor monitoring

Parameterization range	0.2 A ... 3.6 A (steps of 50/100/200 mA, via fieldbus)
Overspeed tripping	≥ 20 A (after 0.3 seconds)

Inline potentials

Communications power U_L	7.5 V
Current consumption from U_L	max. 45 mA
Segment supply voltage U_S	24 V DC (nominal value)
Current consumption from U_S	max. 50 mA

General

Weight	450 g
Note on weight specifications	Without plug
Mounting type	DIN rail
Protection class	I, IEC 61140, EN 61140, VDE 0140-1
Note	Notes on operation Line protection for the network supply line, max. 20 A. Observe derating of the POWER-COMBICON connector
Test section	Supply voltage U_L /400 V level 1.2 kV AC 50 Hz 1 min
	Supply voltage U_S /400 V level 1.2 kV AC 50 Hz 1 min
	Supply voltage U_S /brake control switch 1.2 kV AC 50 Hz 1 min
	Supply voltage U_L /brake control switch 1.2 kV AC 50 Hz 1 min
	Remote bus/400 V level 1.2 kV AC 50 Hz 1 min
	Remote bus/Brake control switch 1.2 kV AC 50 Hz 1 min
Conformance with EMC directives	Noise immunity test in accordance with EN 61000-6-2 Discharge of electrostatic electricity (ESD) EN 61000-4-2:1995/IEC 61000-4-2 6 kV contact discharge, criterion B; 8 kV air discharge, criterion B
	Electromagnetic fields EN 61000-4-3:1993/IEC 61000-4-3 Criterion A; field strength: 3 V/m
	Fast transients (Burst) EN 61000-4-4:1995/IEC 61000-4-4 Criterion B; Supply lines: 2 kV; Signal/data lines: 2 kV
	Transient surge voltage (Surge) EN 61000-4-5:1995/IEC 61000-4-5 Criterion B; supply lines DC: 0.5 kV/0.5 kV (symm./asymm.); criterion B; supply lines AC: 2 kV/4 kV (symm./asymm.)
	Conducted interference EN 61000-4-6:1993/IEC 61000-4-6 Criterion A; Test voltage 10 V
Noise emission	Noise emission test of the housing EN 55011:1991 class A in accordance with EN 61000-6-4
Mechanical tests	Vibration resistance in acc. with EN 60068-2-6/IEC 60068-2-6 2g, evaluation criterion 1
	Shock in acc. with EN 60068-2-27/IEC 60068-2-27 10g, evaluation criterion 1

Inline terminal - IB IL 400 ELR 1-3A - 2727352

Technical data

General

Diagnostics messages	Overcurrent Error message in the diagnostic code (bus) and display via the LED ERR on the module
	Output stage cannot be controlled Error message in the diagnostic code (bus) and display via the LED ERR on the module

Classifications

eCl@ss

eCl@ss 4.0	27250309
eCl@ss 4.1	27250309
eCl@ss 5.0	27250304
eCl@ss 5.1	27242609
eCl@ss 6.0	27242609
eCl@ss 7.0	27242609
eCl@ss 8.0	27242609

ETIM

ETIM 2.0	EC001433
ETIM 3.0	EC001601
ETIM 4.0	EC001601
ETIM 5.0	EC001605

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Inline terminal - IB IL 400 ELR 1-3A - 2727352

Approvals

Approval details

EAC

Accessories

Accessories

Bridge

Power bridge - IB IL 400 CN-BRG - 2836081



Power bridge, for Inline power-level terminal blocks

Power bridge - IB IL 400 CN-BRG - 2836081



Power bridge, for Inline power-level terminal blocks

Cover

Cover - IB IL 400 CN-COV - 2860947



Cover for 400 V mains connection of the Inline power terminal blocks

Extension module

Inline terminal - IB IL 24 BR/DC - 2742036



Inline extension module, for brake control in connection with Inline power terminal blocks, brake module for 24 V DC brakes

Inline terminal - IB IL 400 ELR 1-3A - 2727352

Accessories

Inline terminal - IB IL 400 BR - 2727394



Inline extension module, for brake control in conjunction with Inline power level terminals, brake module for 440 V DC or 440 V AC brakes

Labeling panel

Labeling field - IB IL FIELD 8 - 2727515

Labeling field, width: 48.8 mm



Operator interface

Operator panel - IBS HVO - 2836052



Handheld operator panel, for Inline power-level terminal blocks

Plug

Power plug - IB IL 400 CN-PWR-IN - 2836078



Power plug, for Inline power-level terminals

Terminal marking

Insert strip - ESL 62X46 - 0809502

Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems, Plotter: Laser printer, Mounting type: Insert, Lettering field: 62 x 46 mm



Inline terminal - IB IL 400 ELR 1-3A - 2727352

Accessories


Printed-circuit board connector - GMVSTBW 2,5 HV/ 4-ST-7,62 NZIL - 1893957




Motor-circuit connector, for Inline power-level terminal blocks

Drawings

Connection diagram



Dimensioned drawing



Inline terminal - IB IL 400 ELR 1-3A - 2727352

Block diagram

