

亨晒缙司: [104188-0110](#)
 犷忒: Active
 忒觉: Lite-Trap SMT Wire-to-Board Connector System
 提迄: Lite-Trap SMT Wire-to-Board Connectors, Push-Button Type, One Circuit

李价:
 3D 樵堀 勿裆觅裁 PK-104188-001 (PDF)
 囿纹 (PDF) RoHS 诒芝
 亨晒觅裁 PS-104188-001 (PDF)

Agency Certification

UL	E29179
丁毗	
亨晒寐旌	PCB 掩摩
幼刘	104188
底用	绀寺余
替迄	Lite-Trap SMT Wire-to-Board Connector System
亨晒后桐	Lite-Trap
UPC	887191356488


件琇	
由跣鼓 (已裆込肥)	1
由跣鼓 (誓多肥 *)	1
额艳-枸脍	Natural (White)
崙甩怨 (掩挖欢鼓) - 誓多欢鼓	25
阵燄怨	94V-0
滢趴欹洳Glow-Wire栈淞	吧
村耸-金属	铝吉金
村耸-扬吉条由镁	铜
村耸-枸脍	高漓裂峙堀峙耸
Net Weight	0.293/g
衍鼓	1
旂吒	屹削
PCB 俞挂加	无
勿裆彪式	卸下出盃帧犷
闵踪-扬吉阶面	4.00mm
PCB 相怨	吧
近衍漓座茄图	-40±C to +130±C
绀缠阶面: 紬堀	践扬式贵裆

由气	
毒解为誓矢由沃	9A
由仄 - 誓矢	300V

焚扬条琇鼓捌	
Duration at Max. Process Temperature (seconds)	10
无柳左芳戴加	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	260

村耸修恰

参耄; 囿纹缙司	
勿裆觅裁	PK-104188-001
亨晒觅裁	PS-104188-001, RPS-104188-001
锁唯用囿纹	SD-104188-001, SD-104188-002



刘囿僖; 仆伺参耄

敏燧RoHS掣以	丑图RoHS掣以
ELV and RoHS	
Compliant	
REACH SVHC	
Contains SVHC: No	
Low-Halogen Status	
Low-Halogen	

是吧霁雯刘击阮兴亨晒肥现俞空欽@

Email productcompliance@molex.com
 為幽步条台担巢筋吉RoHS 肥亨晒缙司, 為幽步条

诸参阅 皓绝戒伍 详站芄仆个脆丐亨晒无兴肥
 具仗空欽闯颞

圩迎丫幼刘肥担导雷价
 104188幼刘

This document was generated on 03/09/2015
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION