


## Inductive proximity switches


### IG5954

IGK2012-FRKG/US  
Metal thread M18x1  
Plug and socket

Increased sensing range  
Optical setting aid (2 LED)

Sensing range 12mm [nf]  
non-flush mountable



Electrical design	2-wire DC PNP/NPN
Output	normally open / closed programmable
Operating voltage [V]	10 ... 36 DC
Current rating [mA]	100
Minimum load current [mA]	4
Short-circuit protection	•
Reverse polarity protection / Overload protection	•
Voltage drop [V]	< 4,6
Leakage current [mA]	< 1
Switching frequency [Hz]	250
Real sensing range [mm]	12 ± 10%
Operating distance [mm]	0 ... 9,7
Switch-point drift [% / Sr]	-10 ... +10
Hysteresis [% / Sr]	3 ... 20
Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.5 / Cu approx. 0.4
Function display	
Switching status LED	yellow (4x90°)
setting aid LED	red
Operating temperature [°C]	-25 ... +70
Protection	IP 67 
EMC	EN 60947-5-2; EN 55011 class B
Housing material	special coated brass; CO-PC
Connection	M12 connector
Wiring	