

Mini-Lynx Globe

ML GLOBE 827 E27 20W SLV

0035601

Range features



PRODUCT OVERVIEW

Ordering number	0035601
Technology	Compact Fluorescent
Light colour	827 Homelight
Energy class	A
Average life (Rated) (h)	10000
Lamp shape	Globe
Lamp finish	Frosted
Dimmable	No
Cap/Base	E27
Type	GLOBE
EAN code	5410288356013
CRI (Ra)	80
Colour temperature (K)	2700
Luminous flux (Rated) (lm)	1200
Efficacy (Rated) (lm/w)	60
Watt (Nominal) (W)	20
Equivalent watt (W)	85
Voltage (V)	220-240

Mini-Lynx Globe

ML GLOBE 827 E27 20W SLV

0035601

DATA TABLE

General data

Ordering number	0035601
Dry applications use only	Yes
Technology	Compact Fluorescent
Energy saving lamp	Yes
Energy class	A
Average life (Rated) (h)	10000
Average life (Nominal) (h)	10000
Lamp finish	Frosted
Lamp shape	Globe
Dimmable	No
Cap/Base	E27
Type	GLOBE
EAN code	5410288356013
E-number SE	8357587
Long description	
Product name	ML GLOBE 827 E27 20W SLV
Lamp mercury content (mg)	<2
Starting time (max) (s)	<1.0
Warm-up time to 60% of full light (max) (s)	<100
Control gear required	NO
Intended purpose	General lighting
No. of switching cycles before premature failure (min)	30000
Special purpose lamp	No
Transformer required	No
Sales pack quantity	10
Optimal operating condition (°C)	25

Optical data

Light colour	827 Homelight
CRI (Ra)	80
Colour temperature (K)	2700
Luminous flux (Rated) (lm)	1200
Lumen maintenance at end of nominal life (%)	60
Luminous flux (Nominal) (lm)	1200

Mini-Lynx Globe

ML GLOBE 827 E27 20W SLV

0035601

Electrical data

kWh per 1000 hours burning time	20
Efficacy (Rated) (lm/w)	60
Watt (Rated) (W)	20
Watt (Nominal) (W)	20
Equivalent watt (W)	85
Voltage (V)	220-240
Lamp power factor	=0.55

Physical data


Weight (kg)	0.11
Lamp Length (mm) - C/L	139.5±2
Max. Lamp Diameter (mm) - D	95±1
Single packaging type	Box/Sleeve
Single package dimensions (L x W x H) (cm)	17.50 x 10.00 x 10.00
Outer package dimensions (L x W x H) (cm)	52.00 x 21.00 x 21.50

Mini-Lynx Globe

ML GLOBE 827 E27 20W SLV

0035601

TECHNICAL DRAWINGS



ENERGY LABEL

