

# Control stations and enclosures

Plastic control stations XAL D and XAL K

For Harmony® Ø 22 control and signalling units XB5

Stations for customer assembly: electrical blocks




ZEN L1111



ZAL VB



ZB5 SZ3



ZB5 AZ905



ZBE 101



ZBV B



ZBV V



ZB5 AZ009

## Electrical blocks and accessories for mounting in back of enclosure

Description	Description	Colour	Sold in lots of	Unit reference	Weight kg
<b>Electrical blocks with screw clamp terminal connections</b>					
Standard contact blocks (1)	N/O contact	–	5	ZEN L1111	0.015
	N/C contact	–	5	ZEN L1121	0.015
Light blocks with integral LED (1)	≈ 24 V	White	5	ZAL VB1	0.015
		Green	5	ZAL VB3	0.015
		Red	5	ZAL VB4	0.015
		Yellow	5	ZAL VB5	0.015
		Blue	5	ZAL VB6	0.015
		~ 110...120 V	White	5	ZAL VG1
		Green	5	ZAL VG3	0.015
		Red	5	ZAL VG4	0.015
		Yellow	5	ZAL VG5	0.015
		Blue	5	ZAL VG6	0.015
	~ 230...240 V	White	5	ZAL VM1	0.015
		Green	5	ZAL VM3	0.015
		Red	5	ZAL VM4	0.015
		Yellow	5	ZAL VM5	0.015
		Blue	5	ZAL VM6	0.015

Description	For use with	Sold in lots of	Unit reference	Weight kg
<b>Accessories for electrical blocks</b>				
Blanking plug	Ø 22 mm units	10	ZB5 SZ3	0.008
Nut	Head fixing	10	ZB5 AZ901	0.002
Volt-free terminal	Commoning/earth	10	XAL Z09	0.003
Bezel tool	For tightening nut ZB5 AZ901	1	ZB5 AZ905	0.016

## Electrical blocks and accessories for mounting beneath heads

Description	Description	Colour	Sold in lots of	Unit reference	Weight kg
<b>Electrical blocks with screw clamp terminal connections (2) (for use with body/fixing collar ZB5 AZ009)</b>					
Standard contact blocks	N/O contact	–	5	ZBE 101	0.016
	N/C contact	–	5	ZBE 102	0.016
Light blocks with integral LED	≈ 24 V	White	5	ZBV B1	0.016
		Green	5	ZBV B3	0.016
		Red	5	ZBV B4	0.016
		Yellow	5	ZBV B5	0.016
		Blue	5	ZBV B6	0.016
		~ 110...120 V	White	5	ZBV G1
		Green	5	ZBV G3	0.016
		Red	5	ZBV G4	0.016
		Yellow	5	ZBV G5	0.016
		Blue	5	ZBV G6	0.016
	~ 230...240 V	White	5	ZBV M1	0.016
		Green	5	ZBV M3	0.016
		Red	5	ZBV M4	0.016
		Yellow	5	ZBV M5	0.016
		Blue	5	ZBV M6	0.016

Description	For use with	Level of protection	Unit reference	Weight kg
<b>Accessories for electrical blocks</b>				
LED suppressors	Electrical light blocks with integral LED	~ 120 V	ZBZ VG	0.010
		~ 230 V	ZBZ VM	0.010
Body/fixing collar	Electrical blocks (contact or light)	–	ZB5 AZ009	0.006

(1) A maximum of 3 electrical blocks can be fitted per associated head.

(2) For electrical blocks for printed circuit board connection: please consult your customer care centre.