


Base strip - MSTBO 2,5/ 3-G1R BK - 2909633

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 3, Pitch: 5 mm, Assembly: Soldering

Key commercial data

Packing unit	200 pc
GTIN	 4 017918 405182
Weight per Piece (excluding packing)	1.74 g
Custom tariff number	85366990
Country of origin	India

Technical data

Dimensions

Pitch	5 mm
Dimension a	10 mm
Hole diameter	1.4 mm

General

Range of articles	MSTBO 2,5/..-G1R
Insulating material group	IIIa
Rated surge voltage (III/3)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV
Rated voltage (III/3)	250 V
Rated voltage (III/2)	320 V
Rated voltage (II/2)	400 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	12 A
Maximum load current	12 A
Insulating material	PBT
Inflammability class according to UL 94	V0
Number of positions	3

Base strip - MSTBO 2,5/ 3-G1R BK - 2909633

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC002637
ETIM 5.0	EC002637

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

CSA / UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / IECCE CB Scheme / CCA / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

	B	D
	Nominal current I _N	10 A

Base strip - MSTBO 2,5/ 3-G1R BK - 2909633

Approvals

	B	D
Nominal voltage UN	300 V	300 V

UL Recognized

	B	D
Nominal current IN	16 A	10 A
Nominal voltage UN	300 V	300 V

VDE Gutachten mit Fertigungsüberwachung

Nominal current IN	8 A
Nominal voltage UN	250 V

cUL Recognized

	B	D
Nominal current IN	16 A	10 A
Nominal voltage UN	300 V	300 V

IECEE CB Scheme

Nominal current IN	8 A
Nominal voltage UN	250 V

CCA

Nominal current IN	8 A
Nominal voltage UN	250 V

cULus Recognized

Accessories

Accessories

Base strip - MSTBO 2,5/ 3-G1R BK - 2909633

Accessories

Coding element

Coding section - CR MSTBO-G1 - 2199618



Coding section

Phoenix Contact 2014 © - all rights reserved
<http://www.phoenixcontact.com>