

NSYPAP86

reversible internal door polyester 2 locks grid pattern
forPLM86



Main

| | |
|------------------------------------|-----------------------------------------|
| Range | Thalassa |
| Accessory / separate part category | Enclosure accessory |
| Product or component type | Door |
| Device application | Multi-purpose |
| For enclosure nominal dimensions | |
| Mounting location | Front side |
| Range compatibility | Thalassa PLM |
| Device composition | 1 door 1 handle 4 fixing brackets |

Complementary

| | |
|-----------------|-----------------------------------------------------------------------------------------|
| Material | Polyester charged with fibreglass |
| Colour | Grey RAL 7032 |
| Lock type | Lock 5 mm double bar |
| Number of locks | 2 |
| Door type | Internal plain |
| Door opening | Reversible 110 ° |
| Height | Grid pattern : 715 mm |
| Width | Grid pattern : 505 mm |
| Depth | Available depth between enclosure door : 32 mm Available depth between rear : 244 mm |

Environment

Offer Sustainability

| | |
|----------------------------------|-----------------------------------------------------------------------|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0940 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.